



STYLO

STYLO

MAIN CHARACTERISTICS

Applications	Street lighting.
Optic	STE-M/S: Asymmetrical optic for suburban street lighting. STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. SV: Asymmetrical optic for very narrow urban streets or highway entrance/exit turns. S05/S07: Asymmetrical optic for street, urban and green areas lighting. STA/STA1: Asymmetrical optic for wide urban road and cycle-path lighting. Colour temperature: 4000K, 3000K, 2700K, 2200K (others in option) CRI ≥ 70 LOR= 100%, DLOR= 100%, ULOR= 0% Photobiological safety class: EXEMPT GROUP LED source efficiency: 185 lm/W @ 140mA, Tj=85°C, 4000K
Insulation class	II, I
Protection degree	IP66 IK08
Dimensions	See the drawing
Weight	max 11,5 kg
Exposed surface	Side: 0.09m ² – Top: 0.25m ² SCx: 0.043m ²
Mounting	On brackets with two accessories: Ø42-65mm Spigot entry 100mm.
Tilt Angle	Bracket: 0°/-5°/-10°/-15°
LED Modules	Removable / Replaceable
Gear tray	Removable plate.
Operating temp.	-40°C / +50°C
Storage temp.	-40°C / +80°C
Main reference standards	EN 60598-1, EN 60598-2-3, EN 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3



ELECTRICAL CHARACTERISTICS

Rated voltage	220+240V 50/60Hz
Power factor	>0,95 (at full load F, DA, DAC)
On-load switch	Optional, with integrated cable clamp.
Mains connection	For cable max section 4mm ²
Surge protection	Up to 12kV With SPD: CL.II: 10kV / 10kV CM/DM CL.I: 12kV / 10kV CM/DM Without SPD: CL.II: 10kV / 6kV CM/DM CL.I: 10kV / 6kV CM/DM
SPD (optional)	12kV-10kA, type 2+3, with LED signal and thermo fuse to disconnect load at the end of life.
Control system (options)	F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. DALI: Digital dimming interface DALI. NEMA: Socket 7 pin (ANSI C136.41). ZHAGA: Socket 4 pin (ZHAGA Book 18).
Optical unit lifetime (Tq=25°C)	>100.000hr L90B10 >100.000hr L90, TM-21

MATERIALS

Fixing	Die-cast aluminium UNI EN1706 powder painted.
Canopy	
Body	
Optic	99.85% aluminium with a surface finish in 99.95% with vacuum-sealed deposition. Alluminum grade class A+ (DIN EN 16268)
Screen	VP: Flat tempered glass 5mm thickness high transparency PC: Polycarbonate, UV resistant. (optional)
Cable gland	Plastic M20x1,5 – IP68 Plastic M25x1.5 – IP68 (optional)
Gasket	Polyurethane
Colour	Graphite - Cod. 01

STYLO VP 5P5 4000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7040.040-1M		1190	8,5	140	1240	6,2	50
STYLO VP 5P5 7040.050-1M		1460	10,2	143	1545	7,8	50
STYLO VP 5P5 7040.060-1M		1730	11,9	145	1847	9,4	50
STYLO VP 5P5 7040.070-1M		2000	13,6	147	2146	11	50
STYLO VP 5P5 7040.080-1M		2280	15,4	148	2441	12,7	50
STYLO VP 5P5 7040.090-1M		2550	17,2	148	2734	14,3	50
STYLO VP 5P5 7040.100-1M		2830	19,1	148	3023	16	50
STYLO VP 5P5 7040.120-1M		3370	22,9	147	3592	19,3	50
STYLO VP 5P5 7040.140-1M		3900	26,8	145	4150	22,7	50
STYLO VP 5P5 7040.160-1M		4400	30,8	142	4694	26,1	50
STYLO VP 5P5 7040.180-1M		4870	34,8	139	5227	29,6	50
STYLO VP 5P5 7040.200-1M		5290	38,8	136	5746	33,1	50
STYLO VP 5P5 7040.040-2M		2380	16	148	2480	12,4	50
STYLO VP 5P5 7040.050-2M		2920	19,5	149	3090	15,6	50
STYLO VP 5P5 7040.060-2M		3460	23	150	3694	18,8	50
STYLO VP 5P5 7040.070-2M		4010	26,6	150	4291	22	50
STYLO VP 5P5 7040.080-2M		4560	30,1	151	4882	25,3	50
STYLO VP 5P5 7040.090-2M		5110	33,8	151	5467	28,6	50
STYLO VP 5P5 7040.100-2M		5650	37,4	151	6046	31,9	50
STYLO VP 5P5 7040.120-2M		6720	44,8	149	7185	38,6	50
STYLO VP 5P5 7040.140-2M		7760	52,3	148	8299	45,4	50
STYLO VP 5P5 7040.160-2M		8750	59,9	146	9388	52,2	50
STYLO VP 5P5 7040.180-2M		9670	67,7	142	10453	59,1	50
STYLO VP 5P5 7040.200-2M		10510	75,6	139	11493	66,1	50
STYLO VP 5P5 7040.040-3M		3560	23,3	152	3721	18,5	50
STYLO VP 5P5 7040.050-3M		4380	28,5	153	4635	23,3	50
STYLO VP 5P5 7040.060-3M		5210	33,8	154	5541	28,2	50
STYLO VP 5P5 7040.070-3M		6030	39	154	6437	33,1	50
STYLO VP 5P5 7040.080-3M		6850	44,2	154	7323	38	50
STYLO VP 5P5 7040.090-3M		7670	49,5	154	8201	42,9	50
STYLO VP 5P5 7040.100-3M		8480	54,8	154	9069	47,9	50
STYLO VP 5P5 7040.120-3M		10070	65,6	153	10777	57,9	50
STYLO VP 5P5 7040.140-3M	S05	11600	76,7	151	12449	68	50
STYLO VP 5P5 7040.160-3M	S07	13060	88,2	148	14083	78,3	50
STYLO VP 5P5 7040.180-3M	STA	14420	100	144	15680	88,7	50
STYLO VP 5P5 7040.200-3M	STA1	15680	113	138	17239	99,2	35
STYLO VP 5P5 7040.040-4M	STE-S	4730	30	157	4961	24,7	50
STYLO VP 5P5 7040.050-4M	STU-S	5880	36,6	160	6180	31,1	50
STYLO VP 5P5 7040.060-4M		7010	43,4	161	7387	37,6	50
STYLO VP 5P5 7040.070-4M		8110	50,4	160	8582	44,1	50
STYLO VP 5P5 7040.080-4M		9190	57,4	160	9765	50,6	50
STYLO VP 5P5 7040.090-4M		10250	64,7	158	10934	57,2	50
STYLO VP 5P5 7040.100-4M		11290	72	156	12092	63,8	50
STYLO VP 5P5 7040.120-4M		13310	86,9	153	14370	77,2	50
STYLO VP 5P5 7040.140-4M		15260	102	149	16598	90,7	50
STYLO VP 5P5 7040.160-4M		17150	117	146	18777	104	50
STYLO VP 5P5 7040.180-4M		18980	132	143	20906	118	35
STYLO VP 5P5 7040.200-4M		20760	147	141	22986	132	35
STYLO VP 5P5 7040.060-5M		8750	53,4	163	9234	47	50
STYLO VP 5P5 7040.070-5M		10130	62,2	162	10728	55,1	50
STYLO VP 5P5 7040.080-5M		11500	71	161	12206	63,3	50
STYLO VP 5P5 7040.090-5M		12830	79,7	160	13668	71,5	50
STYLO VP 5P5 7040.100-5M		14150	88,6	159	15115	79,8	50
STYLO VP 5P5 7040.120-5M		16710	107	156	17962	96,5	50
STYLO VP 5P5 7040.140-5M		19190	125	153	20748	113	50
STYLO VP 5P5 7040.160-5M		21580	144	149	23471	130	35
STYLO VP 5P5 7040.180-5M		23890	164	145	26133	148	35
STYLO VP 5P5 7040.060-6M		10500	63,9	164	11081	56,4	50
STYLO VP 5P5 7040.070-6M		12160	74,3	163	12873	66,1	50
STYLO VP 5P5 7040.080-6M		13790	84,8	162	14647	75,9	50
STYLO VP 5P5 7040.090-6M		15390	95,4	161	16402	85,8	50
STYLO VP 5P5 7040.100-6M		16960	106	160	18138	95,7	50
STYLO VP 5P5 7040.120-6M		20010	128	156	21555	116	50
STYLO VP 5P5 7040.140-6M		22940	150	152	24897	136	50
STYLO VP 5P5 7040.160-6M		25760	173	148	28165	157	35
STYLO VP 5P5 7040.180-6M		28480	197	144	31359	177	35
STYLO VP 5P5 7040.060-7M		12220	74,4	164	12928	65,8	50
STYLO VP 5P5 7040.070-7M		14160	87	162	15019	77,2	50
STYLO VP 5P5 7040.080-7M		16090	99,6	161	17088	88,6	50
STYLO VP 5P5 7040.090-7M		17990	112	160	19135	100	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7040.100-7M		19870	125	158	21161	112	50
STYLO VP 5P5 7040.120-7M		23540	151	155	25147	135	50
STYLO VP 5P5 7040.140-7M		27090	177	153	29047	159	50
STYLO VP 5P5 7040.040-1M		1220	8,5	143	1240	6,2	50
STYLO VP 5P5 7040.050-1M		1490	10,2	146	1545	7,8	50
STYLO VP 5P5 7040.060-1M		1770	11,9	148	1847	9,4	50
STYLO VP 5P5 7040.070-1M		2040	13,6	149	2146	11	50
STYLO VP 5P5 7040.080-1M		2330	15,4	151	2441	12,7	50
STYLO VP 5P5 7040.090-1M		2610	17,2	151	2734	14,3	50
STYLO VP 5P5 7040.100-1M		2890	19,1	151	3023	16	50
STYLO VP 5P5 7040.120-1M		3450	22,9	150	3592	19,3	50
STYLO VP 5P5 7040.140-1M		3990	26,8	148	4150	22,7	50
STYLO VP 5P5 7040.160-1M		4500	30,8	146	4694	26,1	50
STYLO VP 5P5 7040.180-1M		4980	34,8	143	5227	29,6	50
STYLO VP 5P5 7040.200-1M		5410	38,8	139	5746	33,1	50
STYLO VP 5P5 7040.040-2M		2430	16	151	2480	12,4	50
STYLO VP 5P5 7040.050-2M		2980	19,5	152	3090	15,6	50
STYLO VP 5P5 7040.060-2M		3540	23	153	3694	18,8	50
STYLO VP 5P5 7040.070-2M		4100	26,6	154	4291	22	50
STYLO VP 5P5 7040.080-2M		4660	30,1	154	4882	25,3	50
STYLO VP 5P5 7040.090-2M		5220	33,8	154	5467	28,6	50
STYLO VP 5P5 7040.100-2M		5780	37,4	154	6046	31,9	50
STYLO VP 5P5 7040.120-2M		6880	44,8	153	7185	38,6	50
STYLO VP 5P5 7040.140-2M		7940	52,3	151	8299	45,4	50
STYLO VP 5P5 7040.160-2M		8950	59,9	149	9388	52,2	50
STYLO VP 5P5 7040.180-2M		9890	67,7	146	10453	59,1	50
STYLO VP 5P5 7040.200-2M		10750	75,6	142	11493	66,1	50
STYLO VP 5P5 7040.040-3M		3640	23,3	156	3721	18,5	50
STYLO VP 5P5 7040.050-3M		4480	28,5	157	4635	23,3	50
STYLO VP 5P5 7040.060-3M		5330	33,8	157	5541	28,2	50
STYLO VP 5P5 7040.070-3M		6170	39	158	6437	33,1	50
STYLO VP 5P5 7040.080-3M		7010	44,2	158	7323	38	50
STYLO VP 5P5 7040.090-3M		7840	49,5	158	8201	42,9	50
STYLO VP 5P5 7040.100-3M		8670	54,8	158	9069	47,9	50
STYLO VP 5P5 7040.120-3M		10290	65,6	156	10777	57,9	50
STYLO VP 5P5 7040.140-3M	STE-M	11860	76,7	154	12449	68	50
STYLO VP 5P5 7040.160-3M	STU-M	13350	88,2	151	14083	78,3	50
STYLO VP 5P5 7040.180-3M	SV	14750	100	147	15680	88,7	50
STYLO VP 5P5 7040.200-3M	STW	16040	113	141	17239	99,2	35
STYLO VP 5P5 7040.040-4M		4840	30	161	4961	24,7	50
STYLO VP 5P5 7040.050-4M		6020	36,6	164	6180	31,1	50
STYLO VP 5P5 7040.060-4M		7170	43,4	165	7387	37,6	50
STYLO VP 5P5 7040.070-4M		8300	50,4	164	8582	44,1	50
STYLO VP 5P5 7040.080-4M		9400	57,4	163	9765	50,6	50
STYLO VP 5P5 7040.090-4M		10490	64,7	162	10934	57,2	50
STYLO VP 5P5 7040.100-4M		11550	72	160	12092	63,8	50
STYLO VP 5P5 7040.120-4M		13620	86,9	156	14370	77,2	50
STYLO VP 5P5 7040.140-4M		15610	102	153	16598	90,7	50
STYLO VP 5P5 7040.160-4M		17540	117	149	18777	104	50
STYLO VP 5P5 7040.180-4M		19410	132	147	20906	118	35
STYLO VP 5P5 7040.200-4M		21230	147	144	22986	132	35
STYLO VP 5P5 7040.060-5M		8940	53,4	167	9234	47	50
STYLO VP 5P5 7040.070-5M		10360	62,2	166	10728	55,1	50
STYLO VP 5P5 7040.080-5M		11750	71	165	12206	63,3	50
STYLO VP 5P5 7040.090-5M		13120	79,7	164	13668	71,5	50
STYLO VP 5P5 7040.100-5M		14470	88,6	163	15115	79,8	50
STYLO VP 5P5 7040.120-5M		17100	107	159	17962	96,5	50
STYLO VP 5P5 7040.140-5M		19630	125	157	20748	113	50
STYLO VP 5P5 7040.160-5M		22080	144	153	23471	130	35
STYLO VP 5P5 7040.180-5M		24440	164	149	26133	148	35
STYLO VP 5P5 7040.060-6M		10740	63,9	168	11081	56,4	50
STYLO VP 5P5 7040.070-6M		12440	74,3	167	12873	66,1	50
STYLO VP 5P5 7040.080-6M		14110	84,8	166	14647	75,9	50
STYLO VP 5P5 7040.090-6M		15750	95,4	165	16402	85,8	50
STYLO VP 5P5 7040.100-6M		17350	106	163	18138	95,7	50
STYLO VP 5P5 7040.120-6M		20460	128	159	21555	116	50
STYLO VP 5P5 7040.140-6M		23460	150	156	24897	136	50
STYLO VP 5P5 7040.160-6M		26340	173	152	28165	157	35
STYLO VP 5P5 7040.180-6M		29120	197	147	31359	177	35
STYLO VP 5P5 7040.060-7M		12500	74,4	168	12928	65,8	50
STYLO VP 5P5 7040.070-7M		14480	87	166	15019	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7040.080-7M		16450	99,6	165	17088	88,6	50
STYLO VP 5P5 7040.090-7M		18400	112	164	19135	100	50
STYLO VP 5P5 7040.100-7M		20320	125	162	21161	112	50
STYLO VP 5P5 7040.120-7M		24080	151	159	25147	135	50
STYLO VP 5P5 7040.140-7M		27710	177	156	29047	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 5P5 3000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7030.040-1M		1120	8,5	131	1166	6,2	50
STYLO VP 5P5 7030.050-1M		1370	10,2	134	1452	7,8	50
STYLO VP 5P5 7030.060-1M		1630	11,9	136	1736	9,4	50
STYLO VP 5P5 7030.070-1M		1880	13,6	138	2017	11	50
STYLO VP 5P5 7030.080-1M		2140	15,4	138	2295	12,7	50
STYLO VP 5P5 7030.090-1M		2400	17,2	139	2570	14,3	50
STYLO VP 5P5 7030.100-1M		2660	19,1	139	2842	16	50
STYLO VP 5P5 7030.120-1M		3170	22,9	138	3377	19,3	50
STYLO VP 5P5 7030.140-1M		3670	26,8	136	3901	22,7	50
STYLO VP 5P5 7030.160-1M		4140	30,8	134	4413	26,1	50
STYLO VP 5P5 7030.180-1M		4580	34,8	131	4913	29,6	50
STYLO VP 5P5 7030.200-1M		4970	38,8	128	5402	33,1	50
STYLO VP 5P5 7030.040-2M		2240	16	140	2332	12,4	50
STYLO VP 5P5 7030.050-2M		2740	19,5	140	2905	15,6	50
STYLO VP 5P5 7030.060-2M		3260	23	141	3472	18,8	50
STYLO VP 5P5 7030.070-2M		3770	26,6	141	4034	22	50
STYLO VP 5P5 7030.080-2M		4280	30,1	142	4589	25,3	50
STYLO VP 5P5 7030.090-2M		4800	33,8	142	5139	28,6	50
STYLO VP 5P5 7030.100-2M		5310	37,4	141	5683	31,9	50
STYLO VP 5P5 7030.120-2M		6320	44,8	141	6754	38,6	50
STYLO VP 5P5 7030.140-2M		7290	52,3	139	7801	45,4	50
STYLO VP 5P5 7030.160-2M		8220	59,9	137	8825	52,2	50
STYLO VP 5P5 7030.180-2M		9090	67,7	134	9826	59,1	50
STYLO VP 5P5 7030.200-2M		9880	75,6	130	10803	66,1	50
STYLO VP 5P5 7030.040-3M		3350	23,3	143	3497	18,5	50
STYLO VP 5P5 7030.050-3M		4120	28,5	144	4357	23,3	50
STYLO VP 5P5 7030.060-3M		4900	33,8	144	5208	28,2	50
STYLO VP 5P5 7030.070-3M		5670	39	145	6050	33,1	50
STYLO VP 5P5 7030.080-3M		6440	44,2	145	6884	38	50
STYLO VP 5P5 7030.090-3M		7210	49,5	145	7709	42,9	50
STYLO VP 5P5 7030.100-3M		7970	54,8	145	8525	47,9	50
STYLO VP 5P5 7030.120-3M		9460	65,6	144	10131	57,9	50
STYLO VP 5P5 7030.140-3M	S05	10900	76,7	142	11702	68	50
STYLO VP 5P5 7030.160-3M	S07	12270	88,2	139	13238	78,3	50
STYLO VP 5P5 7030.180-3M	STA	13560	100	135	14739	88,7	50
STYLO VP 5P5 7030.200-3M	STA1	14740	113	130	16205	99,2	35
STYLO VP 5P5 7030.040-4M	STE-S	4450	30	148	4663	24,7	50
STYLO VP 5P5 7030.050-4M	STU-S	5530	36,6	151	5809	31,1	50
STYLO VP 5P5 7030.060-4M		6590	43,4	151	6944	37,6	50
STYLO VP 5P5 7030.070-4M		7620	50,4	151	8067	44,1	50
STYLO VP 5P5 7030.080-4M		8640	57,4	150	9179	50,6	50
STYLO VP 5P5 7030.090-4M		9640	64,7	148	10278	57,2	50
STYLO VP 5P5 7030.100-4M		10610	72	147	11367	63,8	50
STYLO VP 5P5 7030.120-4M		12510	86,9	143	13508	77,2	50
STYLO VP 5P5 7030.140-4M		14340	102	140	15602	90,7	50
STYLO VP 5P5 7030.160-4M		16120	117	137	17650	104	50
STYLO VP 5P5 7030.180-4M		17840	132	135	19652	118	35
STYLO VP 5P5 7030.200-4M		19510	147	132	21606	132	35
STYLO VP 5P5 7030.060-5M		8220	53,4	153	8680	47	50
STYLO VP 5P5 7030.070-5M		9530	62,2	153	10084	55,1	50
STYLO VP 5P5 7030.080-5M		10810	71	152	11473	63,3	50
STYLO VP 5P5 7030.090-5M		12060	79,7	151	12848	71,5	50
STYLO VP 5P5 7030.100-5M		13300	88,6	150	14208	79,8	50
STYLO VP 5P5 7030.120-5M		15710	107	146	16885	96,5	50
STYLO VP 5P5 7030.140-5M		18040	125	144	19503	113	50
STYLO VP 5P5 7030.160-5M		20290	144	140	22063	130	35
STYLO VP 5P5 7030.180-5M		22460	164	136	24565	148	35
STYLO VP 5P5 7030.060-6M		9870	63,9	154	10416	56,4	50
STYLO VP 5P5 7030.070-6M		11430	74,3	153	12101	66,1	50
STYLO VP 5P5 7030.080-6M		12960	84,8	152	13768	75,9	50
STYLO VP 5P5 7030.090-6M		14470	95,4	151	15418	85,8	50
STYLO VP 5P5 7030.100-6M		15940	106	150	17050	95,7	50
STYLO VP 5P5 7030.120-6M		18810	128	146	20262	116	50
STYLO VP 5P5 7030.140-6M		21560	150	143	23404	136	50
STYLO VP 5P5 7030.160-6M		24220	173	140	26476	157	35
STYLO VP 5P5 7030.180-6M		26770	197	135	29478	177	35
STYLO VP 5P5 7030.060-7M		11490	74,4	154	12152	65,8	50
STYLO VP 5P5 7030.070-7M		13310	87	152	14118	77,2	50
STYLO VP 5P5 7030.080-7M		15120	99,6	151	16063	88,6	50
STYLO VP 5P5 7030.090-7M		16910	112	150	17987	100	50

AEC Illuminazione

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7030.100-7M		18680	125	149	19891	112	50
STYLO VP 5P5 7030.120-7M		22130	151	146	23639	135	50
STYLO VP 5P5 7030.140-7M		25460	177	143	27304	159	50
STYLO VP 5P5 7030.040-1M		1150	8,5	135	1166	6,2	50
STYLO VP 5P5 7030.050-1M		1400	10,2	137	1452	7,8	50
STYLO VP 5P5 7030.060-1M		1660	11,9	139	1736	9,4	50
STYLO VP 5P5 7030.070-1M		1920	13,6	141	2017	11	50
STYLO VP 5P5 7030.080-1M		2190	15,4	142	2295	12,7	50
STYLO VP 5P5 7030.090-1M		2450	17,2	142	2570	14,3	50
STYLO VP 5P5 7030.100-1M		2720	19,1	142	2842	16	50
STYLO VP 5P5 7030.120-1M		3240	22,9	141	3377	19,3	50
STYLO VP 5P5 7030.140-1M		3750	26,8	139	3901	22,7	50
STYLO VP 5P5 7030.160-1M		4230	30,8	137	4413	26,1	50
STYLO VP 5P5 7030.180-1M		4680	34,8	134	4913	29,6	50
STYLO VP 5P5 7030.200-1M		5090	38,8	131	5402	33,1	50
STYLO VP 5P5 7030.040-2M		2280	16	142	2332	12,4	50
STYLO VP 5P5 7030.050-2M		2800	19,5	143	2905	15,6	50
STYLO VP 5P5 7030.060-2M		3330	23	144	3472	18,8	50
STYLO VP 5P5 7030.070-2M		3850	26,6	144	4034	22	50
STYLO VP 5P5 7030.080-2M		4380	30,1	145	4589	25,3	50
STYLO VP 5P5 7030.090-2M		4910	33,8	145	5139	28,6	50
STYLO VP 5P5 7030.100-2M		5430	37,4	145	5683	31,9	50
STYLO VP 5P5 7030.120-2M		6470	44,8	144	6754	38,6	50
STYLO VP 5P5 7030.140-2M		7460	52,3	142	7801	45,4	50
STYLO VP 5P5 7030.160-2M		8410	59,9	140	8825	52,2	50
STYLO VP 5P5 7030.180-2M		9300	67,7	137	9826	59,1	50
STYLO VP 5P5 7030.200-2M		10110	75,6	133	10803	66,1	50
STYLO VP 5P5 7030.040-3M		3420	23,3	146	3497	18,5	50
STYLO VP 5P5 7030.050-3M		4210	28,5	147	4357	23,3	50
STYLO VP 5P5 7030.060-3M		5010	33,8	148	5208	28,2	50
STYLO VP 5P5 7030.070-3M		5800	39	148	6050	33,1	50
STYLO VP 5P5 7030.080-3M		6590	44,2	149	6884	38	50
STYLO VP 5P5 7030.090-3M		7370	49,5	148	7709	42,9	50
STYLO VP 5P5 7030.100-3M		8150	54,8	148	8525	47,9	50
STYLO VP 5P5 7030.120-3M		9680	65,6	147	10131	57,9	50
STYLO VP 5P5 7030.140-3M	STE-M	11150	76,7	145	11702	68	50
STYLO VP 5P5 7030.160-3M	STU-M	12550	88,2	142	13238	78,3	50
STYLO VP 5P5 7030.180-3M	SV	13870	100	138	14739	88,7	50
STYLO VP 5P5 7030.200-3M	STW	15080	113	133	16205	99,2	35
STYLO VP 5P5 7030.040-4M		4550	30	151	4663	24,7	50
STYLO VP 5P5 7030.050-4M		5660	36,6	154	5809	31,1	50
STYLO VP 5P5 7030.060-4M		6740	43,4	155	6944	37,6	50
STYLO VP 5P5 7030.070-4M		7800	50,4	154	8067	44,1	50
STYLO VP 5P5 7030.080-4M		8840	57,4	154	9179	50,6	50
STYLO VP 5P5 7030.090-4M		9860	64,7	152	10278	57,2	50
STYLO VP 5P5 7030.100-4M		10860	72	150	11367	63,8	50
STYLO VP 5P5 7030.120-4M		12800	86,9	147	13508	77,2	50
STYLO VP 5P5 7030.140-4M		14670	102	143	15602	90,7	50
STYLO VP 5P5 7030.160-4M		16490	117	140	17650	104	50
STYLO VP 5P5 7030.180-4M		18240	132	138	19652	118	35
STYLO VP 5P5 7030.200-4M		19960	147	135	21606	132	35
STYLO VP 5P5 7030.060-5M		8400	53,4	157	8680	47	50
STYLO VP 5P5 7030.070-5M		9740	62,2	156	10084	55,1	50
STYLO VP 5P5 7030.080-5M		11050	71	155	11473	63,3	50
STYLO VP 5P5 7030.090-5M		12340	79,7	154	12848	71,5	50
STYLO VP 5P5 7030.100-5M		13600	88,6	153	14208	79,8	50
STYLO VP 5P5 7030.120-5M		16070	107	150	16885	96,5	50
STYLO VP 5P5 7030.140-5M		18450	125	147	19503	113	50
STYLO VP 5P5 7030.160-5M		20750	144	144	22063	130	35
STYLO VP 5P5 7030.180-5M		22970	164	140	24565	148	35
STYLO VP 5P5 7030.060-6M		10090	63,9	157	10416	56,4	50
STYLO VP 5P5 7030.070-6M		11700	74,3	157	12101	66,1	50
STYLO VP 5P5 7030.080-6M		13260	84,8	156	13768	75,9	50
STYLO VP 5P5 7030.090-6M		14800	95,4	155	15418	85,8	50
STYLO VP 5P5 7030.100-6M		16310	106	153	17050	95,7	50
STYLO VP 5P5 7030.120-6M		19240	128	150	20262	116	50
STYLO VP 5P5 7030.140-6M		22050	150	147	23404	136	50
STYLO VP 5P5 7030.160-6M		24760	173	143	26476	157	35
STYLO VP 5P5 7030.180-6M		27370	197	138	29478	177	35
STYLO VP 5P5 7030.060-7M		11750	74,4	157	12152	65,8	50
STYLO VP 5P5 7030.070-7M		13610	87	156	14118	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7030.080-7M		15460	99,6	155	16063	88,6	50
STYLO VP 5P5 7030.090-7M		17290	112	154	17987	100	50
STYLO VP 5P5 7030.100-7M		19100	125	152	19891	112	50
STYLO VP 5P5 7030.120-7M		22630	151	149	23639	135	50
STYLO VP 5P5 7030.140-7M		26050	177	147	27304	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 5P5 2700K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7027.040-1M		1070	8,5	125	1116	6,2	50
STYLO VP 5P5 7027.050-1M		1310	10,2	128	1391	7,8	50
STYLO VP 5P5 7027.060-1M		1560	11,9	131	1662	9,4	50
STYLO VP 5P5 7027.070-1M		1800	13,6	132	1931	11	50
STYLO VP 5P5 7027.080-1M		2050	15,4	133	2197	12,7	50
STYLO VP 5P5 7027.090-1M		2300	17,2	133	2460	14,3	50
STYLO VP 5P5 7027.100-1M		2550	19,1	133	2721	16	50
STYLO VP 5P5 7027.120-1M		3040	22,9	132	3233	19,3	50
STYLO VP 5P5 7027.140-1M		3510	26,8	130	3735	22,7	50
STYLO VP 5P5 7027.160-1M		3960	30,8	128	4225	26,1	50
STYLO VP 5P5 7027.180-1M		4380	34,8	125	4704	29,6	50
STYLO VP 5P5 7027.200-1M		4760	38,8	122	5172	33,1	50
STYLO VP 5P5 7027.040-2M		2140	16	133	2232	12,4	50
STYLO VP 5P5 7027.050-2M		2630	19,5	134	2781	15,6	50
STYLO VP 5P5 7027.060-2M		3120	23	135	3324	18,8	50
STYLO VP 5P5 7027.070-2M		3610	26,6	135	3862	22	50
STYLO VP 5P5 7027.080-2M		4100	30,1	136	4394	25,3	50
STYLO VP 5P5 7027.090-2M		4600	33,8	136	4921	28,6	50
STYLO VP 5P5 7027.100-2M		5090	37,4	136	5441	31,9	50
STYLO VP 5P5 7027.120-2M		6050	44,8	135	6466	38,6	50
STYLO VP 5P5 7027.140-2M		6980	52,3	133	7469	45,4	50
STYLO VP 5P5 7027.160-2M		7870	59,9	131	8450	52,2	50
STYLO VP 5P5 7027.180-2M		8700	67,7	128	9408	59,1	50
STYLO VP 5P5 7027.200-2M		9460	75,6	125	10344	66,1	50
STYLO VP 5P5 7027.040-3M		3200	23,3	137	3348	18,5	50
STYLO VP 5P5 7027.050-3M		3940	28,5	138	4172	23,3	50
STYLO VP 5P5 7027.060-3M		4690	33,8	138	4986	28,2	50
STYLO VP 5P5 7027.070-3M		5430	39	139	5793	33,1	50
STYLO VP 5P5 7027.080-3M		6170	44,2	139	6591	38	50
STYLO VP 5P5 7027.090-3M		6900	49,5	139	7381	42,9	50
STYLO VP 5P5 7027.100-3M		7630	54,8	139	8162	47,9	50
STYLO VP 5P5 7027.120-3M		9060	65,6	138	9700	57,9	50
STYLO VP 5P5 7027.140-3M	S05	10440	76,7	136	11204	68	50
STYLO VP 5P5 7027.160-3M	S07	11750	88,2	133	12674	78,3	50
STYLO VP 5P5 7027.180-3M	STA	12980	100	129	14112	88,7	50
STYLO VP 5P5 7027.200-3M	STA1	14110	113	124	15515	99,2	35
STYLO VP 5P5 7027.040-4M	STE-S	4260	30	142	4465	24,7	50
STYLO VP 5P5 7027.050-4M	STU-S	5290	36,6	144	5562	31,1	50
STYLO VP 5P5 7027.060-4M		6310	43,4	145	6649	37,6	50
STYLO VP 5P5 7027.070-4M		7300	50,4	144	7724	44,1	50
STYLO VP 5P5 7027.080-4M		8270	57,4	144	8788	50,6	50
STYLO VP 5P5 7027.090-4M		9230	64,7	142	9841	57,2	50
STYLO VP 5P5 7027.100-4M		10160	72	141	10883	63,8	50
STYLO VP 5P5 7027.120-4M		11980	86,9	137	12933	77,2	50
STYLO VP 5P5 7027.140-4M		13730	102	134	14938	90,7	50
STYLO VP 5P5 7027.160-4M		15430	117	131	16899	104	50
STYLO VP 5P5 7027.180-4M		17080	132	129	18816	118	35
STYLO VP 5P5 7027.200-4M		18680	147	127	20687	132	35
STYLO VP 5P5 7027.060-5M		7870	53,4	147	8311	47	50
STYLO VP 5P5 7027.070-5M		9120	62,2	146	9655	55,1	50
STYLO VP 5P5 7027.080-5M		10350	71	145	10985	63,3	50
STYLO VP 5P5 7027.090-5M		11550	79,7	144	12301	71,5	50
STYLO VP 5P5 7027.100-5M		12740	88,6	143	13604	79,8	50
STYLO VP 5P5 7027.120-5M		15040	107	140	16166	96,5	50
STYLO VP 5P5 7027.140-5M		17270	125	138	18673	113	50
STYLO VP 5P5 7027.160-5M		19420	144	134	21124	130	35
STYLO VP 5P5 7027.180-5M		21510	164	131	23519	148	35
STYLO VP 5P5 7027.060-6M		9450	63,9	147	9973	56,4	50
STYLO VP 5P5 7027.070-6M		10940	74,3	147	11586	66,1	50
STYLO VP 5P5 7027.080-6M		12410	84,8	146	13182	75,9	50
STYLO VP 5P5 7027.090-6M		13850	95,4	145	14762	85,8	50
STYLO VP 5P5 7027.100-6M		15260	106	143	16324	95,7	50
STYLO VP 5P5 7027.120-6M		18010	128	140	19399	116	50
STYLO VP 5P5 7027.140-6M		20650	150	137	22408	136	50
STYLO VP 5P5 7027.160-6M		23180	173	133	25349	157	35
STYLO VP 5P5 7027.180-6M		25630	197	130	28223	177	35
STYLO VP 5P5 7027.060-7M		11000	74,4	147	11635	65,8	50
STYLO VP 5P5 7027.070-7M		12750	87	146	13517	77,2	50
STYLO VP 5P5 7027.080-7M		14480	99,6	145	15379	88,6	50
STYLO VP 5P5 7027.090-7M		16190	112	144	17222	100	50

AEC Illuminazione

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7027.100-7M		17880	125	143	19045	112	50
STYLO VP 5P5 7027.120-7M		21190	151	140	22633	135	50
STYLO VP 5P5 7027.140-7M		24380	177	137	26142	159	50
STYLO VP 5P5 7027.040-1M		1100	8,5	129	1116	6,2	50
STYLO VP 5P5 7027.050-1M		1340	10,2	131	1391	7,8	50
STYLO VP 5P5 7027.060-1M		1590	11,9	133	1662	9,4	50
STYLO VP 5P5 7027.070-1M		1840	13,6	135	1931	11	50
STYLO VP 5P5 7027.080-1M		2090	15,4	135	2197	12,7	50
STYLO VP 5P5 7027.090-1M		2350	17,2	136	2460	14,3	50
STYLO VP 5P5 7027.100-1M		2600	19,1	136	2721	16	50
STYLO VP 5P5 7027.120-1M		3100	22,9	135	3233	19,3	50
STYLO VP 5P5 7027.140-1M		3590	26,8	133	3735	22,7	50
STYLO VP 5P5 7027.160-1M		4050	30,8	131	4225	26,1	50
STYLO VP 5P5 7027.180-1M		4480	34,8	128	4704	29,6	50
STYLO VP 5P5 7027.200-1M		4870	38,8	125	5172	33,1	50
STYLO VP 5P5 7027.040-2M		2190	16	136	2232	12,4	50
STYLO VP 5P5 7027.050-2M		2680	19,5	137	2781	15,6	50
STYLO VP 5P5 7027.060-2M		3190	23	138	3324	18,8	50
STYLO VP 5P5 7027.070-2M		3690	26,6	138	3862	22	50
STYLO VP 5P5 7027.080-2M		4200	30,1	139	4394	25,3	50
STYLO VP 5P5 7027.090-2M		4700	33,8	139	4921	28,6	50
STYLO VP 5P5 7027.100-2M		5200	37,4	139	5441	31,9	50
STYLO VP 5P5 7027.120-2M		6190	44,8	138	6466	38,6	50
STYLO VP 5P5 7027.140-2M		7150	52,3	136	7469	45,4	50
STYLO VP 5P5 7027.160-2M		8060	59,9	134	8450	52,2	50
STYLO VP 5P5 7027.180-2M		8900	67,7	131	9408	59,1	50
STYLO VP 5P5 7027.200-2M		9680	75,6	128	10344	66,1	50
STYLO VP 5P5 7027.040-3M		3280	23,3	140	3348	18,5	50
STYLO VP 5P5 7027.050-3M		4030	28,5	141	4172	23,3	50
STYLO VP 5P5 7027.060-3M		4790	33,8	141	4986	28,2	50
STYLO VP 5P5 7027.070-3M		5550	39	142	5793	33,1	50
STYLO VP 5P5 7027.080-3M		6310	44,2	142	6591	38	50
STYLO VP 5P5 7027.090-3M		7060	49,5	142	7381	42,9	50
STYLO VP 5P5 7027.100-3M		7800	54,8	142	8162	47,9	50
STYLO VP 5P5 7027.120-3M		9260	65,6	141	9700	57,9	50
STYLO VP 5P5 7027.140-3M	STE-M	10670	76,7	139	11204	68	50
STYLO VP 5P5 7027.160-3M	STU-M	12020	88,2	136	12674	78,3	50
STYLO VP 5P5 7027.180-3M	SV	13280	100	132	14112	88,7	50
STYLO VP 5P5 7027.200-3M	STW	14440	113	127	15515	99,2	35
STYLO VP 5P5 7027.040-4M		4360	30	145	4465	24,7	50
STYLO VP 5P5 7027.050-4M		5420	36,6	148	5562	31,1	50
STYLO VP 5P5 7027.060-4M		6450	43,4	148	6649	37,6	50
STYLO VP 5P5 7027.070-4M		7470	50,4	148	7724	44,1	50
STYLO VP 5P5 7027.080-4M		8460	57,4	147	8788	50,6	50
STYLO VP 5P5 7027.090-4M		9440	64,7	145	9841	57,2	50
STYLO VP 5P5 7027.100-4M		10400	72	144	10883	63,8	50
STYLO VP 5P5 7027.120-4M		12250	86,9	140	12933	77,2	50
STYLO VP 5P5 7027.140-4M		14050	102	137	14938	90,7	50
STYLO VP 5P5 7027.160-4M		15780	117	134	16899	104	50
STYLO VP 5P5 7027.180-4M		17470	132	132	18816	118	35
STYLO VP 5P5 7027.200-4M		19110	147	130	20687	132	35
STYLO VP 5P5 7027.060-5M		8050	53,4	150	8311	47	50
STYLO VP 5P5 7027.070-5M		9320	62,2	149	9655	55,1	50
STYLO VP 5P5 7027.080-5M		10580	71	149	10985	63,3	50
STYLO VP 5P5 7027.090-5M		11810	79,7	148	12301	71,5	50
STYLO VP 5P5 7027.100-5M		13020	88,6	146	13604	79,8	50
STYLO VP 5P5 7027.120-5M		15390	107	143	16166	96,5	50
STYLO VP 5P5 7027.140-5M		17670	125	141	18673	113	50
STYLO VP 5P5 7027.160-5M		19870	144	137	21124	130	35
STYLO VP 5P5 7027.180-5M		22000	164	134	23519	148	35
STYLO VP 5P5 7027.060-6M		9670	63,9	151	9973	56,4	50
STYLO VP 5P5 7027.070-6M		11200	74,3	150	11586	66,1	50
STYLO VP 5P5 7027.080-6M		12700	84,8	149	13182	75,9	50
STYLO VP 5P5 7027.090-6M		14170	95,4	148	14762	85,8	50
STYLO VP 5P5 7027.100-6M		15620	106	147	16324	95,7	50
STYLO VP 5P5 7027.120-6M		18420	128	143	19399	116	50
STYLO VP 5P5 7027.140-6M		21110	150	140	22408	136	50
STYLO VP 5P5 7027.160-6M		23710	173	137	25349	157	35
STYLO VP 5P5 7027.180-6M		26210	197	133	28223	177	35
STYLO VP 5P5 7027.060-7M		11250	74,4	151	11635	65,8	50
STYLO VP 5P5 7027.070-7M		13040	87	149	13517	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7027.080-7M		14810	99,6	148	15379	88,6	50
STYLO VP 5P5 7027.090-7M		16560	112	147	17222	100	50
STYLO VP 5P5 7027.100-7M		18290	125	146	19045	112	50
STYLO VP 5P5 7027.120-7M		21670	151	143	22633	135	50
STYLO VP 5P5 7027.140-7M		24940	177	140	26142	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 5P5 2200K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7022.040-1M		960	8,5	112	1005	6,2	50
STYLO VP 5P5 7022.050-1M		1180	10,2	115	1251	7,8	50
STYLO VP 5P5 7022.060-1M		1400	11,9	117	1496	9,4	50
STYLO VP 5P5 7022.070-1M		1620	13,6	119	1738	11	50
STYLO VP 5P5 7022.080-1M		1850	15,4	120	1977	12,7	50
STYLO VP 5P5 7022.090-1M		2070	17,2	120	2214	14,3	50
STYLO VP 5P5 7022.100-1M		2290	19,1	119	2449	16	50
STYLO VP 5P5 7022.120-1M		2730	22,9	119	2910	19,3	50
STYLO VP 5P5 7022.140-1M		3160	26,8	117	3361	22,7	50
STYLO VP 5P5 7022.160-1M		3560	30,8	115	3802	26,1	50
STYLO VP 5P5 7022.180-1M		3940	34,8	113	4233	29,6	50
STYLO VP 5P5 7022.200-1M		4280	38,8	110	4655	33,1	50
STYLO VP 5P5 7022.040-2M		1930	16	120	2009	12,4	50
STYLO VP 5P5 7022.050-2M		2360	19,5	121	2503	15,6	50
STYLO VP 5P5 7022.060-2M		2810	23	122	2992	18,8	50
STYLO VP 5P5 7022.070-2M		3250	26,6	122	3476	22	50
STYLO VP 5P5 7022.080-2M		3690	30,1	122	3955	25,3	50
STYLO VP 5P5 7022.090-2M		4140	33,8	122	4428	28,6	50
STYLO VP 5P5 7022.100-2M		4580	37,4	122	4897	31,9	50
STYLO VP 5P5 7022.120-2M		5450	44,8	121	5820	38,6	50
STYLO VP 5P5 7022.140-2M		6290	52,3	120	6722	45,4	50
STYLO VP 5P5 7022.160-2M		7090	59,9	118	7605	52,2	50
STYLO VP 5P5 7022.180-2M		7830	67,7	115	8467	59,1	50
STYLO VP 5P5 7022.200-2M		8510	75,6	112	9309	66,1	50
STYLO VP 5P5 7022.040-3M		2880	23,3	123	3014	18,5	50
STYLO VP 5P5 7022.050-3M		3550	28,5	124	3754	23,3	50
STYLO VP 5P5 7022.060-3M		4220	33,8	124	4488	28,2	50
STYLO VP 5P5 7022.070-3M		4890	39	125	5214	33,1	50
STYLO VP 5P5 7022.080-3M		5550	44,2	125	5932	38	50
STYLO VP 5P5 7022.090-3M		6210	49,5	125	6643	42,9	50
STYLO VP 5P5 7022.100-3M		6870	54,8	125	7346	47,9	50
STYLO VP 5P5 7022.120-3M		8160	65,6	124	8730	57,9	50
STYLO VP 5P5 7022.140-3M	S05	9400	76,7	122	10083	68	50
STYLO VP 5P5 7022.160-3M	S07	10580	88,2	119	11407	78,3	50
STYLO VP 5P5 7022.180-3M	STA	11680	100	116	12700	88,7	50
STYLO VP 5P5 7022.200-3M	STA1	12700	113	112	13964	99,2	35
STYLO VP 5P5 7022.040-4M	STE-S	3830	30	127	4018	24,7	50
STYLO VP 5P5 7022.050-4M	STU-S	4760	36,6	130	5006	31,1	50
STYLO VP 5P5 7022.060-4M		5680	43,4	130	5984	37,6	50
STYLO VP 5P5 7022.070-4M		6570	50,4	130	6952	44,1	50
STYLO VP 5P5 7022.080-4M		7450	57,4	129	7909	50,6	50
STYLO VP 5P5 7022.090-4M		8300	64,7	128	8857	57,2	50
STYLO VP 5P5 7022.100-4M		9140	72	126	9795	63,8	50
STYLO VP 5P5 7022.120-4M		10780	86,9	124	11640	77,2	50
STYLO VP 5P5 7022.140-4M		12360	102	121	13445	90,7	50
STYLO VP 5P5 7022.160-4M		13890	117	118	15209	104	50
STYLO VP 5P5 7022.180-4M		15370	132	116	16934	118	35
STYLO VP 5P5 7022.200-4M		16820	147	114	18618	132	35
STYLO VP 5P5 7022.060-5M		7080	53,4	132	7480	47	50
STYLO VP 5P5 7022.070-5M		8210	62,2	131	8689	55,1	50
STYLO VP 5P5 7022.080-5M		9310	71	131	9887	63,3	50
STYLO VP 5P5 7022.090-5M		10400	79,7	130	11071	71,5	50
STYLO VP 5P5 7022.100-5M		11460	88,6	129	12243	79,8	50
STYLO VP 5P5 7022.120-5M		13540	107	126	14550	96,5	50
STYLO VP 5P5 7022.140-5M		15540	125	124	16806	113	50
STYLO VP 5P5 7022.160-5M		17480	144	121	19012	130	35
STYLO VP 5P5 7022.180-5M		19350	164	117	21167	148	35
STYLO VP 5P5 7022.060-6M		8500	63,9	133	8976	56,4	50
STYLO VP 5P5 7022.070-6M		9850	74,3	132	10427	66,1	50
STYLO VP 5P5 7022.080-6M		11170	84,8	131	11864	75,9	50
STYLO VP 5P5 7022.090-6M		12470	95,4	130	13285	85,8	50
STYLO VP 5P5 7022.100-6M		13740	106	129	14692	95,7	50
STYLO VP 5P5 7022.120-6M		16210	128	126	17459	116	50
STYLO VP 5P5 7022.140-6M		18580	150	123	20167	136	50
STYLO VP 5P5 7022.160-6M		20870	173	120	22814	157	35
STYLO VP 5P5 7022.180-6M		23070	197	117	25401	177	35
STYLO VP 5P5 7022.060-7M		9900	74,4	133	10472	65,8	50
STYLO VP 5P5 7022.070-7M		11470	87	131	12165	77,2	50
STYLO VP 5P5 7022.080-7M		13030	99,6	130	13841	88,6	50
STYLO VP 5P5 7022.090-7M		14570	112	130	15500	100	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7022.100-7M		16090	125	128	17140	112	50
STYLO VP 5P5 7022.120-7M		19070	151	126	20369	135	50
STYLO VP 5P5 7022.140-7M		21940	177	123	23528	159	50
STYLO VP 5P5 7022.040-1M		990	8,5	116	1005	6,2	50
STYLO VP 5P5 7022.050-1M		1210	10,2	118	1251	7,8	50
STYLO VP 5P5 7022.060-1M		1430	11,9	120	1496	9,4	50
STYLO VP 5P5 7022.070-1M		1660	13,6	122	1738	11	50
STYLO VP 5P5 7022.080-1M		1880	15,4	122	1977	12,7	50
STYLO VP 5P5 7022.090-1M		2110	17,2	122	2214	14,3	50
STYLO VP 5P5 7022.100-1M		2340	19,1	122	2449	16	50
STYLO VP 5P5 7022.120-1M		2790	22,9	121	2910	19,3	50
STYLO VP 5P5 7022.140-1M		3230	26,8	120	3361	22,7	50
STYLO VP 5P5 7022.160-1M		3650	30,8	118	3802	26,1	50
STYLO VP 5P5 7022.180-1M		4030	34,8	115	4233	29,6	50
STYLO VP 5P5 7022.200-1M		4380	38,8	112	4655	33,1	50
STYLO VP 5P5 7022.040-2M		1970	16	123	2009	12,4	50
STYLO VP 5P5 7022.050-2M		2420	19,5	124	2503	15,6	50
STYLO VP 5P5 7022.060-2M		2870	23	124	2992	18,8	50
STYLO VP 5P5 7022.070-2M		3320	26,6	124	3476	22	50
STYLO VP 5P5 7022.080-2M		3780	30,1	125	3955	25,3	50
STYLO VP 5P5 7022.090-2M		4230	33,8	125	4428	28,6	50
STYLO VP 5P5 7022.100-2M		4680	37,4	125	4897	31,9	50
STYLO VP 5P5 7022.120-2M		5570	44,8	124	5820	38,6	50
STYLO VP 5P5 7022.140-2M		6430	52,3	122	6722	45,4	50
STYLO VP 5P5 7022.160-2M		7250	59,9	121	7605	52,2	50
STYLO VP 5P5 7022.180-2M		8010	67,7	118	8467	59,1	50
STYLO VP 5P5 7022.200-2M		8710	75,6	115	9309	66,1	50
STYLO VP 5P5 7022.040-3M		2950	23,3	126	3014	18,5	50
STYLO VP 5P5 7022.050-3M		3630	28,5	127	3754	23,3	50
STYLO VP 5P5 7022.060-3M		4310	33,8	127	4488	28,2	50
STYLO VP 5P5 7022.070-3M		5000	39	128	5214	33,1	50
STYLO VP 5P5 7022.080-3M		5680	44,2	128	5932	38	50
STYLO VP 5P5 7022.090-3M		6350	49,5	128	6643	42,9	50
STYLO VP 5P5 7022.100-3M		7020	54,8	128	7346	47,9	50
STYLO VP 5P5 7022.120-3M		8340	65,6	127	8730	57,9	50
STYLO VP 5P5 7022.140-3M	STE-M	9610	76,7	125	10083	68	50
STYLO VP 5P5 7022.160-3M	STU-M	10820	88,2	122	11407	78,3	50
STYLO VP 5P5 7022.180-3M	SV	11950	100	119	12700	88,7	50
STYLO VP 5P5 7022.200-3M	STW	12990	113	114	13964	99,2	35
STYLO VP 5P5 7022.040-4M		3920	30	130	4018	24,7	50
STYLO VP 5P5 7022.050-4M		4870	36,6	133	5006	31,1	50
STYLO VP 5P5 7022.060-4M		5810	43,4	133	5984	37,6	50
STYLO VP 5P5 7022.070-4M		6720	50,4	133	6952	44,1	50
STYLO VP 5P5 7022.080-4M		7620	57,4	132	7909	50,6	50
STYLO VP 5P5 7022.090-4M		8490	64,7	131	8857	57,2	50
STYLO VP 5P5 7022.100-4M		9360	72	130	9795	63,8	50
STYLO VP 5P5 7022.120-4M		11030	86,9	126	11640	77,2	50
STYLO VP 5P5 7022.140-4M		12640	102	123	13445	90,7	50
STYLO VP 5P5 7022.160-4M		14210	117	121	15209	104	50
STYLO VP 5P5 7022.180-4M		15720	132	119	16934	118	35
STYLO VP 5P5 7022.200-4M		17200	147	117	18618	132	35
STYLO VP 5P5 7022.060-5M		7240	53,4	135	7480	47	50
STYLO VP 5P5 7022.070-5M		8390	62,2	134	8689	55,1	50
STYLO VP 5P5 7022.080-5M		9520	71	134	9887	63,3	50
STYLO VP 5P5 7022.090-5M		10630	79,7	133	11071	71,5	50
STYLO VP 5P5 7022.100-5M		11720	88,6	132	12243	79,8	50
STYLO VP 5P5 7022.120-5M		13850	107	129	14550	96,5	50
STYLO VP 5P5 7022.140-5M		15900	125	127	16806	113	50
STYLO VP 5P5 7022.160-5M		17880	144	124	19012	130	35
STYLO VP 5P5 7022.180-5M		19800	164	120	21167	148	35
STYLO VP 5P5 7022.060-6M		8700	63,9	136	8976	56,4	50
STYLO VP 5P5 7022.070-6M		10080	74,3	135	10427	66,1	50
STYLO VP 5P5 7022.080-6M		11430	84,8	134	11864	75,9	50
STYLO VP 5P5 7022.090-6M		12750	95,4	133	13285	85,8	50
STYLO VP 5P5 7022.100-6M		14050	106	132	14692	95,7	50
STYLO VP 5P5 7022.120-6M		16580	128	129	17459	116	50
STYLO VP 5P5 7022.140-6M		19000	150	126	20167	136	50
STYLO VP 5P5 7022.160-6M		21340	173	123	22814	157	35
STYLO VP 5P5 7022.180-6M		23590	197	119	25401	177	35
STYLO VP 5P5 7022.060-7M		10120	74,4	136	10472	65,8	50
STYLO VP 5P5 7022.070-7M		11730	87	134	12165	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 5P5 7022.080-7M		13330	99,6	133	13841	88,6	50
STYLO VP 5P5 7022.090-7M		14900	112	133	15500	100	50
STYLO VP 5P5 7022.100-7M		16460	125	131	17140	112	50
STYLO VP 5P5 7022.120-7M		19500	151	129	20369	135	50
STYLO VP 5P5 7022.140-7M		22450	177	126	23528	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 4P4 4000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7040.050-1M		1160	8,3	139	1236	6,2	50
STYLO VP 4P4 7040.060-1M		1380	9,6	143	1477	7,5	50
STYLO VP 4P4 7040.070-1M		1600	11	145	1716	8,8	50
STYLO VP 4P4 7040.080-1M		1820	12,4	146	1953	10,1	50
STYLO VP 4P4 7040.090-1M		2040	13,8	147	2187	11,4	50
STYLO VP 4P4 7040.100-1M		2260	15,3	147	2418	12,8	50
STYLO VP 4P4 7040.120-1M		2700	18,4	146	2874	15,4	50
STYLO VP 4P4 7040.140-1M		3120	21,5	145	3320	18,1	50
STYLO VP 4P4 7040.160-1M		3520	24,7	142	3755	20,9	50
STYLO VP 4P4 7040.180-1M		3890	27,9	139	4181	23,6	50
STYLO VP 4P4 7040.200-1M		4230	31	136	4597	26,4	50
STYLO VP 4P4 7040.050-2M		2330	16	145	2472	12,5	50
STYLO VP 4P4 7040.060-2M		2770	18,7	148	2955	15	50
STYLO VP 4P4 7040.070-2M		3210	21,5	149	3433	17,6	50
STYLO VP 4P4 7040.080-2M		3650	24,3	150	3906	20,3	50
STYLO VP 4P4 7040.090-2M		4080	27,1	150	4374	22,9	50
STYLO VP 4P4 7040.100-2M		4520	30	150	4837	25,5	50
STYLO VP 4P4 7040.120-2M		5380	35,9	149	5748	30,9	50
STYLO VP 4P4 7040.140-2M		6210	41,9	148	6639	36,3	50
STYLO VP 4P4 7040.160-2M		7000	48	145	7511	41,8	50
STYLO VP 4P4 7040.180-2M		7740	54,2	142	8362	47,3	50
STYLO VP 4P4 7040.200-2M		8410	60,5	139	9194	52,9	50
STYLO VP 4P4 7040.050-3M		3510	23,3	150	3708	18,7	50
STYLO VP 4P4 7040.060-3M		4160	27,4	151	4432	22,6	50
STYLO VP 4P4 7040.070-3M		4820	31,5	153	5149	26,5	50
STYLO VP 4P4 7040.080-3M		5480	35,6	153	5859	30,4	50
STYLO VP 4P4 7040.090-3M		6130	39,8	154	6561	34,3	50
STYLO VP 4P4 7040.100-3M		6780	44	154	7255	38,3	50
STYLO VP 4P4 7040.120-3M		8050	52,6	153	8622	46,3	50
STYLO VP 4P4 7040.140-3M		9280	61,5	150	9959	54,4	50
STYLO VP 4P4 7040.160-3M	S05	10450	70,7	147	11266	62,6	50
STYLO VP 4P4 7040.180-3M	S07	11540	80,3	143	12544	70,9	50
STYLO VP 4P4 7040.200-3M	STE-S	12540	90,4	138	13791	79,3	35
STYLO VP 4P4 7040.050-4M		4700	30	156	4944	24,9	50
STYLO VP 4P4 7040.060-4M		5600	35,3	158	5910	30,1	50
STYLO VP 4P4 7040.070-4M		6480	40,7	159	6866	35,3	50
STYLO VP 4P4 7040.080-4M		7350	46,3	158	7812	40,5	50
STYLO VP 4P4 7040.090-4M		8200	52	157	8748	45,8	50
STYLO VP 4P4 7040.100-4M		9030	57,8	156	9674	51,1	50
STYLO VP 4P4 7040.120-4M		10650	69,7	152	11496	61,7	50
STYLO VP 4P4 7040.140-4M		12210	81,8	149	13279	72,6	50
STYLO VP 4P4 7040.160-4M		13720	94	145	15022	83,5	50
STYLO VP 4P4 7040.180-4M		15190	106	143	16725	94,6	35
STYLO VP 4P4 7040.200-4M		16610	118	140	18389	106	35
STYLO VP 4P4 7040.080-5M		9200	57,2	160	9765	50,6	50
STYLO VP 4P4 7040.090-5M		10270	64,1	160	10934	57,2	50
STYLO VP 4P4 7040.100-5M		11320	71,1	159	12092	63,8	50
STYLO VP 4P4 7040.120-5M		13370	85,3	156	14370	77,2	50
STYLO VP 4P4 7040.140-5M		15350	100	153	16598	90,7	50
STYLO VP 4P4 7040.160-5M		17260	115	150	18777	104	35
STYLO VP 4P4 7040.180-5M		19110	131	145	20906	118	35
STYLO VP 4P4 7040.080-6M		11040	68,4	161	11717	60,8	50
STYLO VP 4P4 7040.090-6M		12320	76,7	160	13121	68,6	50
STYLO VP 4P4 7040.100-6M		13570	85,1	159	14510	76,6	50
STYLO VP 4P4 7040.120-6M		16010	102	156	17244	92,6	50
STYLO VP 4P4 7040.140-6M		18350	120	152	19918	109	50
STYLO VP 4P4 7040.160-6M		20610	138	149	22532	125	35
STYLO VP 4P4 7040.180-6M		22780	158	144	25087	142	35
STYLO VP 4P4 7040.080-7M		12860	79,7	161	13670	70,9	50
STYLO VP 4P4 7040.090-7M		14390	89,8	160	15308	80,1	50
STYLO VP 4P4 7040.100-7M		15890	100	158	16929	89,4	50
STYLO VP 4P4 7040.120-7M		18830	121	155	20118	108	50
STYLO VP 4P4 7040.140-7M		21670	142	152	23238	127	50
STYLO VP 4P4 7040.050-1M		1180	8,3	142	1236	6,2	50
STYLO VP 4P4 7040.060-1M		1400	9,6	145	1477	7,5	50
STYLO VP 4P4 7040.070-1M	STA	1620	11	147	1716	8,8	50
STYLO VP 4P4 7040.080-1M	STA1	1840	12,4	148	1953	10,1	50
STYLO VP 4P4 7040.090-1M	STU-S	2070	13,8	150	2187	11,4	50
STYLO VP 4P4 7040.100-1M		2290	15,3	149	2418	12,8	50
STYLO VP 4P4 7040.120-1M		2730	18,4	148	2874	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7040.140-1M		3160	21,5	146	3320	18,1	50
STYLO VP 4P4 7040.160-1M		3570	24,7	144	3755	20,9	50
STYLO VP 4P4 7040.180-1M		3940	27,9	141	4181	23,6	50
STYLO VP 4P4 7040.200-1M		4280	31	138	4597	26,4	50
STYLO VP 4P4 7040.050-2M		2360	16	147	2472	12,5	50
STYLO VP 4P4 7040.060-2M		2800	18,7	149	2955	15	50
STYLO VP 4P4 7040.070-2M		3240	21,5	150	3433	17,6	50
STYLO VP 4P4 7040.080-2M		3690	24,3	151	3906	20,3	50
STYLO VP 4P4 7040.090-2M		4130	27,1	152	4374	22,9	50
STYLO VP 4P4 7040.100-2M		4570	30	152	4837	25,5	50
STYLO VP 4P4 7040.120-2M		5440	35,9	151	5748	30,9	50
STYLO VP 4P4 7040.140-2M		6280	41,9	149	6639	36,3	50
STYLO VP 4P4 7040.160-2M		7080	48	147	7511	41,8	50
STYLO VP 4P4 7040.180-2M		7820	54,2	144	8362	47,3	50
STYLO VP 4P4 7040.200-2M		8500	60,5	140	9194	52,9	50
STYLO VP 4P4 7040.050-3M		3540	23,3	151	3708	18,7	50
STYLO VP 4P4 7040.060-3M		4210	27,4	153	4432	22,6	50
STYLO VP 4P4 7040.070-3M		4880	31,5	154	5149	26,5	50
STYLO VP 4P4 7040.080-3M		5540	35,6	155	5859	30,4	50
STYLO VP 4P4 7040.090-3M		6200	39,8	155	6561	34,3	50
STYLO VP 4P4 7040.100-3M		6860	44	155	7255	38,3	50
STYLO VP 4P4 7040.120-3M		8150	52,6	154	8622	46,3	50
STYLO VP 4P4 7040.140-3M		9390	61,5	152	9959	54,4	50
STYLO VP 4P4 7040.160-3M		10570	70,7	149	11266	62,6	50
STYLO VP 4P4 7040.180-3M		11680	80,3	145	12544	70,9	50
STYLO VP 4P4 7040.200-3M		12690	90,4	140	13791	79,3	35
STYLO VP 4P4 7040.050-4M		4760	30	158	4944	24,9	50
STYLO VP 4P4 7040.060-4M		5670	35,3	160	5910	30,1	50
STYLO VP 4P4 7040.070-4M		6570	40,7	161	6866	35,3	50
STYLO VP 4P4 7040.080-4M		7440	46,3	160	7812	40,5	50
STYLO VP 4P4 7040.090-4M		8300	52	159	8748	45,8	50
STYLO VP 4P4 7040.100-4M		9140	57,8	158	9674	51,1	50
STYLO VP 4P4 7040.120-4M		10770	69,7	154	11496	61,7	50
STYLO VP 4P4 7040.140-4M		12350	81,8	150	13279	72,6	50
STYLO VP 4P4 7040.160-4M		13880	94	147	15022	83,5	50
STYLO VP 4P4 7040.180-4M		15360	106	144	16725	94,6	35
STYLO VP 4P4 7040.200-4M		16800	118	142	18389	106	35
STYLO VP 4P4 7040.080-5M		9300	57,2	162	9765	50,6	50
STYLO VP 4P4 7040.090-5M		10380	64,1	161	10934	57,2	50
STYLO VP 4P4 7040.100-5M		11450	71,1	161	12092	63,8	50
STYLO VP 4P4 7040.120-5M		13530	85,3	158	14370	77,2	50
STYLO VP 4P4 7040.140-5M		15530	100	155	16598	90,7	50
STYLO VP 4P4 7040.160-5M		17470	115	151	18777	104	35
STYLO VP 4P4 7040.180-5M		19330	131	147	20906	118	35
STYLO VP 4P4 7040.080-6M		11160	68,4	163	11717	60,8	50
STYLO VP 4P4 7040.090-6M		12450	76,7	162	13121	68,6	50
STYLO VP 4P4 7040.100-6M		13720	85,1	161	14510	76,6	50
STYLO VP 4P4 7040.120-6M		16190	102	158	17244	92,6	50
STYLO VP 4P4 7040.140-6M		18560	120	154	19918	109	50
STYLO VP 4P4 7040.160-6M		20840	138	151	22532	125	35
STYLO VP 4P4 7040.180-6M		23040	158	145	25087	142	35
STYLO VP 4P4 7040.080-7M		13010	79,7	163	13670	70,9	50
STYLO VP 4P4 7040.090-7M		14550	89,8	162	15308	80,1	50
STYLO VP 4P4 7040.100-7M		16070	100	160	16929	89,4	50
STYLO VP 4P4 7040.120-7M		19050	121	157	20118	108	50
STYLO VP 4P4 7040.140-7M		21920	142	154	23238	127	50
STYLO VP 4P4 7040.050-1M		1200	8,3	144	1236	6,2	50
STYLO VP 4P4 7040.060-1M		1430	9,6	148	1477	7,5	50
STYLO VP 4P4 7040.070-1M		1650	11	150	1716	8,8	50
STYLO VP 4P4 7040.080-1M		1880	12,4	151	1953	10,1	50
STYLO VP 4P4 7040.090-1M		2110	13,8	152	2187	11,4	50
STYLO VP 4P4 7040.100-1M		2340	15,3	152	2418	12,8	50
STYLO VP 4P4 7040.120-1M		2790	18,4	151	2874	15,4	50
STYLO VP 4P4 7040.140-1M		3230	21,5	150	3320	18,1	50
STYLO VP 4P4 7040.160-1M		3650	24,7	147	3755	20,9	50
STYLO VP 4P4 7040.180-1M		4030	27,9	144	4181	23,6	50
STYLO VP 4P4 7040.200-1M		4380	31	141	4597	26,4	50
STYLO VP 4P4 7040.050-2M		2420	16	151	2472	12,5	50
STYLO VP 4P4 7040.060-2M		2870	18,7	153	2955	15	50
STYLO VP 4P4 7040.070-2M		3320	21,5	154	3433	17,6	50
STYLO VP 4P4 7040.080-2M		3780	24,3	155	3906	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7040.090-2M		4230	27,1	156	4374	22,9	50
STYLO VP 4P4 7040.100-2M		4680	30	156	4837	25,5	50
STYLO VP 4P4 7040.120-2M		5560	35,9	154	5748	30,9	50
STYLO VP 4P4 7040.140-2M		6420	41,9	153	6639	36,3	50
STYLO VP 4P4 7040.160-2M		7240	48	150	7511	41,8	50
STYLO VP 4P4 7040.180-2M		8000	54,2	147	8362	47,3	50
STYLO VP 4P4 7040.200-2M		8700	60,5	143	9194	52,9	50
STYLO VP 4P4 7040.050-3M		3630	23,3	155	3708	18,7	50
STYLO VP 4P4 7040.060-3M		4310	27,4	157	4432	22,6	50
STYLO VP 4P4 7040.070-3M		5000	31,5	158	5149	26,5	50
STYLO VP 4P4 7040.080-3M		5680	35,6	159	5859	30,4	50
STYLO VP 4P4 7040.090-3M		6350	39,8	159	6561	34,3	50
STYLO VP 4P4 7040.100-3M		7020	44	159	7255	38,3	50
STYLO VP 4P4 7040.120-3M		8330	52,6	158	8622	46,3	50
STYLO VP 4P4 7040.140-3M		9600	61,5	156	9959	54,4	50
STYLO VP 4P4 7040.160-3M		10810	70,7	152	11266	62,6	50
STYLO VP 4P4 7040.180-3M		11940	80,3	148	12544	70,9	50
STYLO VP 4P4 7040.200-3M		12980	90,4	143	13791	79,3	35
STYLO VP 4P4 7040.050-4M		4870	30	162	4944	24,9	50
STYLO VP 4P4 7040.060-4M		5810	35,3	164	5910	30,1	50
STYLO VP 4P4 7040.070-4M		6720	40,7	165	6866	35,3	50
STYLO VP 4P4 7040.080-4M		7620	46,3	164	7812	40,5	50
STYLO VP 4P4 7040.090-4M		8490	52	163	8748	45,8	50
STYLO VP 4P4 7040.100-4M		9350	57,8	161	9674	51,1	50
STYLO VP 4P4 7040.120-4M		11020	69,7	158	11496	61,7	50
STYLO VP 4P4 7040.140-4M		12630	81,8	154	13279	72,6	50
STYLO VP 4P4 7040.160-4M		14190	94	150	15022	83,5	50
STYLO VP 4P4 7040.180-4M		15710	106	148	16725	94,6	35
STYLO VP 4P4 7040.200-4M		17190	118	145	18389	106	35
STYLO VP 4P4 7040.080-5M		9510	57,2	166	9765	50,6	50
STYLO VP 4P4 7040.090-5M		10620	64,1	165	10934	57,2	50
STYLO VP 4P4 7040.100-5M		11710	71,1	164	12092	63,8	50
STYLO VP 4P4 7040.120-5M		13840	85,3	162	14370	77,2	50
STYLO VP 4P4 7040.140-5M		15890	100	158	16598	90,7	50
STYLO VP 4P4 7040.160-5M		17870	115	155	18777	104	35
STYLO VP 4P4 7040.180-5M		19790	131	151	20906	118	35
STYLO VP 4P4 7040.080-6M		11420	68,4	166	11717	60,8	50
STYLO VP 4P4 7040.090-6M		12740	76,7	166	13121	68,6	50
STYLO VP 4P4 7040.100-6M		14040	85,1	164	14510	76,6	50
STYLO VP 4P4 7040.120-6M		16560	102	162	17244	92,6	50
STYLO VP 4P4 7040.140-6M		18990	120	158	19918	109	50
STYLO VP 4P4 7040.160-6M		21330	138	154	22532	125	35
STYLO VP 4P4 7040.180-6M		23570	158	149	25087	142	35
STYLO VP 4P4 7040.080-7M		13310	79,7	167	13670	70,9	50
STYLO VP 4P4 7040.090-7M		14880	89,8	165	15308	80,1	50
STYLO VP 4P4 7040.100-7M		16440	100	164	16929	89,4	50
STYLO VP 4P4 7040.120-7M		19490	121	161	20118	108	50
STYLO VP 4P4 7040.140-7M		22430	142	157	23238	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 4P4 3000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7030.050-1M	STE-S	1090	8,3	131	1162	6,2	50
STYLO VP 4P4 7030.060-1M		1300	9,6	135	1389	7,5	50
STYLO VP 4P4 7030.070-1M		1500	11	136	1613	8,8	50
STYLO VP 4P4 7030.080-1M		1710	12,4	137	1836	10,1	50
STYLO VP 4P4 7030.090-1M		1920	13,8	139	2056	11,4	50
STYLO VP 4P4 7030.100-1M		2120	15,3	138	2273	12,8	50
STYLO VP 4P4 7030.120-1M		2530	18,4	137	2702	15,4	50
STYLO VP 4P4 7030.140-1M		2930	21,5	136	3120	18,1	50
STYLO VP 4P4 7030.160-1M		3310	24,7	134	3530	20,9	50
STYLO VP 4P4 7030.180-1M		3660	27,9	131	3930	23,6	50
STYLO VP 4P4 7030.200-1M		3980	31	128	4321	26,4	50
STYLO VP 4P4 7030.050-2M		2190	16	136	2324	12,5	50
STYLO VP 4P4 7030.060-2M		2600	18,7	139	2778	15	50
STYLO VP 4P4 7030.070-2M		3010	21,5	140	3227	17,6	50
STYLO VP 4P4 7030.080-2M		3430	24,3	141	3671	20,3	50
STYLO VP 4P4 7030.090-2M		3840	27,1	141	4111	22,9	50
STYLO VP 4P4 7030.100-2M		4250	30	141	4547	25,5	50
STYLO VP 4P4 7030.120-2M		5060	35,9	140	5403	30,9	50
STYLO VP 4P4 7030.140-2M		5840	41,9	139	6241	36,3	50
STYLO VP 4P4 7030.160-2M		6580	48	137	7060	41,8	50
STYLO VP 4P4 7030.180-2M		7270	54,2	134	7861	47,3	50
STYLO VP 4P4 7030.200-2M		7910	60,5	130	8643	52,9	50
STYLO VP 4P4 7030.050-3M		3300	23,3	141	3486	18,7	50
STYLO VP 4P4 7030.060-3M		3910	27,4	142	4166	22,6	50
STYLO VP 4P4 7030.070-3M		4530	31,5	143	4840	26,5	50
STYLO VP 4P4 7030.080-3M		5150	35,6	144	5507	30,4	50
STYLO VP 4P4 7030.090-3M		5760	39,8	144	6167	34,3	50
STYLO VP 4P4 7030.100-3M		6370	44	144	6820	38,3	50
STYLO VP 4P4 7030.120-3M		7570	52,6	143	8105	46,3	50
STYLO VP 4P4 7030.140-3M		8720	61,5	141	9361	54,4	50
STYLO VP 4P4 7030.160-3M		9820	70,7	138	10590	62,6	50
STYLO VP 4P4 7030.180-3M		10850	80,3	135	11791	70,9	50
STYLO VP 4P4 7030.200-3M		11790	90,4	130	12964	79,3	35
STYLO VP 4P4 7030.050-4M		4420	30	147	4648	24,9	50
STYLO VP 4P4 7030.060-4M		5270	35,3	149	5555	30,1	50
STYLO VP 4P4 7030.070-4M		6100	40,7	149	6454	35,3	50
STYLO VP 4P4 7030.080-4M		6910	46,3	149	7343	40,5	50
STYLO VP 4P4 7030.090-4M		7710	52	148	8223	45,8	50
STYLO VP 4P4 7030.100-4M		8490	57,8	146	9093	51,1	50
STYLO VP 4P4 7030.120-4M		10010	69,7	143	10806	61,7	50
STYLO VP 4P4 7030.140-4M		11480	81,8	140	12482	72,6	50
STYLO VP 4P4 7030.160-4M		12900	94	137	14120	83,5	50
STYLO VP 4P4 7030.180-4M		14270	106	134	15721	94,6	35
STYLO VP 4P4 7030.200-4M		15610	118	132	17285	106	35
STYLO VP 4P4 7030.080-5M		8650	57,2	151	9179	50,6	50
STYLO VP 4P4 7030.090-5M		9650	64,1	150	10278	57,2	50
STYLO VP 4P4 7030.100-5M		10640	71,1	149	11367	63,8	50
STYLO VP 4P4 7030.120-5M		12570	85,3	147	13508	77,2	50
STYLO VP 4P4 7030.140-5M		14430	100	144	15602	90,7	50
STYLO VP 4P4 7030.160-5M		16230	115	141	17650	104	35
STYLO VP 4P4 7030.180-5M		17970	131	137	19652	118	35
STYLO VP 4P4 7030.080-6M		10370	68,4	151	11014	60,8	50
STYLO VP 4P4 7030.090-6M		11580	76,7	150	12334	68,6	50
STYLO VP 4P4 7030.100-6M		12760	85,1	149	13640	76,6	50
STYLO VP 4P4 7030.120-6M		15050	102	147	16209	92,6	50
STYLO VP 4P4 7030.140-6M		17250	120	143	18723	109	50
STYLO VP 4P4 7030.160-6M		19370	138	140	21180	125	35
STYLO VP 4P4 7030.180-6M		21410	158	135	23582	142	35
STYLO VP 4P4 7030.080-7M		12090	79,7	151	12850	70,9	50
STYLO VP 4P4 7030.090-7M		13520	89,8	150	14390	80,1	50
STYLO VP 4P4 7030.100-7M		14940	100	149	15913	89,4	50
STYLO VP 4P4 7030.120-7M		17700	121	146	18911	108	50
STYLO VP 4P4 7030.140-7M		20370	142	143	21843	127	50
STYLO VP 4P4 7030.050-1M	STA STA1 STU-S	1110	8,3	133	1162	6,2	50
STYLO VP 4P4 7030.060-1M		1310	9,6	136	1389	7,5	50
STYLO VP 4P4 7030.070-1M		1520	11	138	1613	8,8	50
STYLO VP 4P4 7030.080-1M		1730	12,4	139	1836	10,1	50
STYLO VP 4P4 7030.090-1M		1940	13,8	140	2056	11,4	50
STYLO VP 4P4 7030.100-1M		2150	15,3	140	2273	12,8	50
STYLO VP 4P4 7030.120-1M		2570	18,4	139	2702	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7030.140-1M		2970	21,5	138	3120	18,1	50
STYLO VP 4P4 7030.160-1M		3350	24,7	135	3530	20,9	50
STYLO VP 4P4 7030.180-1M		3710	27,9	132	3930	23,6	50
STYLO VP 4P4 7030.200-1M		4020	31	129	4321	26,4	50
STYLO VP 4P4 7030.050-2M		2220	16	138	2324	12,5	50
STYLO VP 4P4 7030.060-2M		2630	18,7	140	2778	15	50
STYLO VP 4P4 7030.070-2M		3050	21,5	141	3227	17,6	50
STYLO VP 4P4 7030.080-2M		3470	24,3	142	3671	20,3	50
STYLO VP 4P4 7030.090-2M		3880	27,1	143	4111	22,9	50
STYLO VP 4P4 7030.100-2M		4300	30	143	4547	25,5	50
STYLO VP 4P4 7030.120-2M		5110	35,9	142	5403	30,9	50
STYLO VP 4P4 7030.140-2M		5900	41,9	140	6241	36,3	50
STYLO VP 4P4 7030.160-2M		6650	48	138	7060	41,8	50
STYLO VP 4P4 7030.180-2M		7350	54,2	135	7861	47,3	50
STYLO VP 4P4 7030.200-2M		7990	60,5	132	8643	52,9	50
STYLO VP 4P4 7030.050-3M		3330	23,3	142	3486	18,7	50
STYLO VP 4P4 7030.060-3M		3960	27,4	144	4166	22,6	50
STYLO VP 4P4 7030.070-3M		4580	31,5	145	4840	26,5	50
STYLO VP 4P4 7030.080-3M		5210	35,6	146	5507	30,4	50
STYLO VP 4P4 7030.090-3M		5830	39,8	146	6167	34,3	50
STYLO VP 4P4 7030.100-3M		6450	44	146	6820	38,3	50
STYLO VP 4P4 7030.120-3M		7660	52,6	145	8105	46,3	50
STYLO VP 4P4 7030.140-3M		8830	61,5	143	9361	54,4	50
STYLO VP 4P4 7030.160-3M		9940	70,7	140	10590	62,6	50
STYLO VP 4P4 7030.180-3M		10980	80,3	136	11791	70,9	50
STYLO VP 4P4 7030.200-3M		11930	90,4	131	12964	79,3	35
STYLO VP 4P4 7030.050-4M		4480	30	149	4648	24,9	50
STYLO VP 4P4 7030.060-4M		5330	35,3	150	5555	30,1	50
STYLO VP 4P4 7030.070-4M		6170	40,7	151	6454	35,3	50
STYLO VP 4P4 7030.080-4M		7000	46,3	151	7343	40,5	50
STYLO VP 4P4 7030.090-4M		7800	52	150	8223	45,8	50
STYLO VP 4P4 7030.100-4M		8590	57,8	148	9093	51,1	50
STYLO VP 4P4 7030.120-4M		10130	69,7	145	10806	61,7	50
STYLO VP 4P4 7030.140-4M		11610	81,8	141	12482	72,6	50
STYLO VP 4P4 7030.160-4M		13040	94	138	14120	83,5	50
STYLO VP 4P4 7030.180-4M		14440	106	136	15721	94,6	35
STYLO VP 4P4 7030.200-4M		15790	118	133	17285	106	35
STYLO VP 4P4 7030.080-5M		8740	57,2	152	9179	50,6	50
STYLO VP 4P4 7030.090-5M		9760	64,1	152	10278	57,2	50
STYLO VP 4P4 7030.100-5M		10760	71,1	151	11367	63,8	50
STYLO VP 4P4 7030.120-5M		12710	85,3	149	13508	77,2	50
STYLO VP 4P4 7030.140-5M		14600	100	146	15602	90,7	50
STYLO VP 4P4 7030.160-5M		16420	115	142	17650	104	35
STYLO VP 4P4 7030.180-5M		18170	131	138	19652	118	35
STYLO VP 4P4 7030.080-6M		10490	68,4	153	11014	60,8	50
STYLO VP 4P4 7030.090-6M		11700	76,7	152	12334	68,6	50
STYLO VP 4P4 7030.100-6M		12900	85,1	151	13640	76,6	50
STYLO VP 4P4 7030.120-6M		15220	102	149	16209	92,6	50
STYLO VP 4P4 7030.140-6M		17450	120	145	18723	109	50
STYLO VP 4P4 7030.160-6M		19590	138	141	21180	125	35
STYLO VP 4P4 7030.180-6M		21660	158	137	23582	142	35
STYLO VP 4P4 7030.080-7M		12230	79,7	153	12850	70,9	50
STYLO VP 4P4 7030.090-7M		13680	89,8	152	14390	80,1	50
STYLO VP 4P4 7030.100-7M		15110	100	151	15913	89,4	50
STYLO VP 4P4 7030.120-7M		17900	121	147	18911	108	50
STYLO VP 4P4 7030.140-7M		20600	142	145	21843	127	50
STYLO VP 4P4 7030.050-1M		1130	8,3	136	1162	6,2	50
STYLO VP 4P4 7030.060-1M		1340	9,6	139	1389	7,5	50
STYLO VP 4P4 7030.070-1M		1550	11	140	1613	8,8	50
STYLO VP 4P4 7030.080-1M		1770	12,4	142	1836	10,1	50
STYLO VP 4P4 7030.090-1M		1980	13,8	143	2056	11,4	50
STYLO VP 4P4 7030.100-1M		2200	15,3	143	2273	12,8	50
STYLO VP 4P4 7030.120-1M		2620	18,4	142	2702	15,4	50
STYLO VP 4P4 7030.140-1M		3040	21,5	141	3120	18,1	50
STYLO VP 4P4 7030.160-1M		3430	24,7	138	3530	20,9	50
STYLO VP 4P4 7030.180-1M		3790	27,9	135	3930	23,6	50
STYLO VP 4P4 7030.200-1M		4120	31	132	4321	26,4	50
STYLO VP 4P4 7030.050-2M		2270	16	141	2324	12,5	50
STYLO VP 4P4 7030.060-2M		2700	18,7	144	2778	15	50
STYLO VP 4P4 7030.070-2M		3130	21,5	145	3227	17,6	50
STYLO VP 4P4 7030.080-2M		3550	24,3	146	3671	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7030.090-2M		3980	27,1	146	4111	22,9	50
STYLO VP 4P4 7030.100-2M		4400	30	146	4547	25,5	50
STYLO VP 4P4 7030.120-2M		5230	35,9	145	5403	30,9	50
STYLO VP 4P4 7030.140-2M		6030	41,9	143	6241	36,3	50
STYLO VP 4P4 7030.160-2M		6800	48	141	7060	41,8	50
STYLO VP 4P4 7030.180-2M		7520	54,2	138	7861	47,3	50
STYLO VP 4P4 7030.200-2M		8180	60,5	135	8643	52,9	50
STYLO VP 4P4 7030.050-3M		3410	23,3	146	3486	18,7	50
STYLO VP 4P4 7030.060-3M		4060	27,4	148	4166	22,6	50
STYLO VP 4P4 7030.070-3M		4700	31,5	149	4840	26,5	50
STYLO VP 4P4 7030.080-3M		5330	35,6	149	5507	30,4	50
STYLO VP 4P4 7030.090-3M		5970	39,8	149	6167	34,3	50
STYLO VP 4P4 7030.100-3M		6600	44	150	6820	38,3	50
STYLO VP 4P4 7030.120-3M		7830	52,6	148	8105	46,3	50
STYLO VP 4P4 7030.140-3M		9020	61,5	146	9361	54,4	50
STYLO VP 4P4 7030.160-3M		10160	70,7	143	10590	62,6	50
STYLO VP 4P4 7030.180-3M		11220	80,3	139	11791	70,9	50
STYLO VP 4P4 7030.200-3M		12200	90,4	134	12964	79,3	35
STYLO VP 4P4 7030.050-4M		4580	30	152	4648	24,9	50
STYLO VP 4P4 7030.060-4M		5460	35,3	154	5555	30,1	50
STYLO VP 4P4 7030.070-4M		6320	40,7	155	6454	35,3	50
STYLO VP 4P4 7030.080-4M		7160	46,3	154	7343	40,5	50
STYLO VP 4P4 7030.090-4M		7980	52	153	8223	45,8	50
STYLO VP 4P4 7030.100-4M		8790	57,8	152	9093	51,1	50
STYLO VP 4P4 7030.120-4M		10360	69,7	148	10806	61,7	50
STYLO VP 4P4 7030.140-4M		11870	81,8	145	12482	72,6	50
STYLO VP 4P4 7030.160-4M		13340	94	141	14120	83,5	50
STYLO VP 4P4 7030.180-4M		14770	106	139	15721	94,6	35
STYLO VP 4P4 7030.200-4M		16160	118	136	17285	106	35
STYLO VP 4P4 7030.080-5M		8940	57,2	156	9179	50,6	50
STYLO VP 4P4 7030.090-5M		9980	64,1	155	10278	57,2	50
STYLO VP 4P4 7030.100-5M		11010	71,1	154	11367	63,8	50
STYLO VP 4P4 7030.120-5M		13010	85,3	152	13508	77,2	50
STYLO VP 4P4 7030.140-5M		14940	100	149	15602	90,7	50
STYLO VP 4P4 7030.160-5M		16800	115	146	17650	104	35
STYLO VP 4P4 7030.180-5M		18600	131	141	19652	118	35
STYLO VP 4P4 7030.080-6M		10730	68,4	156	11014	60,8	50
STYLO VP 4P4 7030.090-6M		11980	76,7	156	12334	68,6	50
STYLO VP 4P4 7030.100-6M		13200	85,1	155	13640	76,6	50
STYLO VP 4P4 7030.120-6M		15570	102	152	16209	92,6	50
STYLO VP 4P4 7030.140-6M		17850	120	148	18723	109	50
STYLO VP 4P4 7030.160-6M		20050	138	145	21180	125	35
STYLO VP 4P4 7030.180-6M		22160	158	140	23582	142	35
STYLO VP 4P4 7030.080-7M		12510	79,7	156	12850	70,9	50
STYLO VP 4P4 7030.090-7M		13990	89,8	155	14390	80,1	50
STYLO VP 4P4 7030.100-7M		15450	100	154	15913	89,4	50
STYLO VP 4P4 7030.120-7M		18320	121	151	18911	108	50
STYLO VP 4P4 7030.140-7M		21080	142	148	21843	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 4P4 2700K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7027.050-1M	STE-S	1050	8,3	126	1112	6,2	50
STYLO VP 4P4 7027.060-1M		1240	9,6	129	1330	7,5	50
STYLO VP 4P4 7027.070-1M		1440	11	130	1545	8,8	50
STYLO VP 4P4 7027.080-1M		1640	12,4	132	1758	10,1	50
STYLO VP 4P4 7027.090-1M		1840	13,8	133	1968	11,4	50
STYLO VP 4P4 7027.100-1M		2030	15,3	132	2177	12,8	50
STYLO VP 4P4 7027.120-1M		2430	18,4	132	2587	15,4	50
STYLO VP 4P4 7027.140-1M		2810	21,5	130	2988	18,1	50
STYLO VP 4P4 7027.160-1M		3170	24,7	128	3380	20,9	50
STYLO VP 4P4 7027.180-1M		3510	27,9	125	3763	23,6	50
STYLO VP 4P4 7027.200-1M		3810	31	122	4137	26,4	50
STYLO VP 4P4 7027.050-2M		2100	16	131	2225	12,5	50
STYLO VP 4P4 7027.060-2M		2490	18,7	133	2659	15	50
STYLO VP 4P4 7027.070-2M		2890	21,5	134	3090	17,6	50
STYLO VP 4P4 7027.080-2M		3280	24,3	134	3515	20,3	50
STYLO VP 4P4 7027.090-2M		3680	27,1	135	3936	22,9	50
STYLO VP 4P4 7027.100-2M		4070	30	135	4353	25,5	50
STYLO VP 4P4 7027.120-2M		4840	35,9	134	5173	30,9	50
STYLO VP 4P4 7027.140-2M		5590	41,9	133	5975	36,3	50
STYLO VP 4P4 7027.160-2M		6300	48	131	6760	41,8	50
STYLO VP 4P4 7027.180-2M		6960	54,2	128	7526	47,3	50
STYLO VP 4P4 7027.200-2M		7570	60,5	125	8275	52,9	50
STYLO VP 4P4 7027.050-3M		3150	23,3	135	3337	18,7	50
STYLO VP 4P4 7027.060-3M		3750	27,4	136	3989	22,6	50
STYLO VP 4P4 7027.070-3M		4340	31,5	137	4634	26,5	50
STYLO VP 4P4 7027.080-3M		4930	35,6	138	5273	30,4	50
STYLO VP 4P4 7027.090-3M		5520	39,8	138	5905	34,3	50
STYLO VP 4P4 7027.100-3M		6100	44	138	6530	38,3	50
STYLO VP 4P4 7027.120-3M		7250	52,6	137	7760	46,3	50
STYLO VP 4P4 7027.140-3M		8350	61,5	135	8963	54,4	50
STYLO VP 4P4 7027.160-3M		9400	70,7	132	10140	62,6	50
STYLO VP 4P4 7027.180-3M		10390	80,3	129	11289	70,9	50
STYLO VP 4P4 7027.200-3M		11290	90,4	124	12412	79,3	35
STYLO VP 4P4 7027.050-4M		4230	30	141	4450	24,9	50
STYLO VP 4P4 7027.060-4M		5040	35,3	142	5319	30,1	50
STYLO VP 4P4 7027.070-4M		5840	40,7	143	6179	35,3	50
STYLO VP 4P4 7027.080-4M		6610	46,3	142	7030	40,5	50
STYLO VP 4P4 7027.090-4M		7380	52	141	7873	45,8	50
STYLO VP 4P4 7027.100-4M		8130	57,8	140	8706	51,1	50
STYLO VP 4P4 7027.120-4M		9580	69,7	137	10346	61,7	50
STYLO VP 4P4 7027.140-4M		10990	81,8	134	11951	72,6	50
STYLO VP 4P4 7027.160-4M		12350	94	131	13519	83,5	50
STYLO VP 4P4 7027.180-4M		13670	106	128	15052	94,6	35
STYLO VP 4P4 7027.200-4M		14950	118	126	16550	106	35
STYLO VP 4P4 7027.080-5M		8280	57,2	144	8788	50,6	50
STYLO VP 4P4 7027.090-5M		9240	64,1	144	9841	57,2	50
STYLO VP 4P4 7027.100-5M		10190	71,1	143	10883	63,8	50
STYLO VP 4P4 7027.120-5M		12030	85,3	141	12933	77,2	50
STYLO VP 4P4 7027.140-5M		13820	100	138	14938	90,7	50
STYLO VP 4P4 7027.160-5M		15540	115	135	16899	104	35
STYLO VP 4P4 7027.180-5M		17200	131	131	18816	118	35
STYLO VP 4P4 7027.080-6M		9930	68,4	145	10546	60,8	50
STYLO VP 4P4 7027.090-6M		11080	76,7	144	11809	68,6	50
STYLO VP 4P4 7027.100-6M		12210	85,1	143	13059	76,6	50
STYLO VP 4P4 7027.120-6M		14410	102	141	15520	92,6	50
STYLO VP 4P4 7027.140-6M		16520	120	137	17926	109	50
STYLO VP 4P4 7027.160-6M		18540	138	134	20279	125	35
STYLO VP 4P4 7027.180-6M		20500	158	129	22579	142	35
STYLO VP 4P4 7027.080-7M		11580	79,7	145	12303	70,9	50
STYLO VP 4P4 7027.090-7M		12950	89,8	144	13777	80,1	50
STYLO VP 4P4 7027.100-7M		14300	100	143	15236	89,4	50
STYLO VP 4P4 7027.120-7M		16950	121	140	18106	108	50
STYLO VP 4P4 7027.140-7M		19500	142	137	20914	127	50
STYLO VP 4P4 7027.050-1M	STA STA1 STU-S	1060	8,3	127	1112	6,2	50
STYLO VP 4P4 7027.060-1M		1260	9,6	131	1330	7,5	50
STYLO VP 4P4 7027.070-1M		1460	11	132	1545	8,8	50
STYLO VP 4P4 7027.080-1M		1660	12,4	133	1758	10,1	50
STYLO VP 4P4 7027.090-1M		1860	13,8	134	1968	11,4	50
STYLO VP 4P4 7027.100-1M		2060	15,3	134	2177	12,8	50
STYLO VP 4P4 7027.120-1M		2460	18,4	133	2587	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7027.140-1M		2840	21,5	132	2988	18,1	50
STYLO VP 4P4 7027.160-1M		3210	24,7	129	3380	20,9	50
STYLO VP 4P4 7027.180-1M		3550	27,9	127	3763	23,6	50
STYLO VP 4P4 7027.200-1M		3850	31	124	4137	26,4	50
STYLO VP 4P4 7027.050-2M		2130	16	133	2225	12,5	50
STYLO VP 4P4 7027.060-2M		2520	18,7	134	2659	15	50
STYLO VP 4P4 7027.070-2M		2920	21,5	135	3090	17,6	50
STYLO VP 4P4 7027.080-2M		3320	24,3	136	3515	20,3	50
STYLO VP 4P4 7027.090-2M		3720	27,1	137	3936	22,9	50
STYLO VP 4P4 7027.100-2M		4110	30	137	4353	25,5	50
STYLO VP 4P4 7027.120-2M		4900	35,9	136	5173	30,9	50
STYLO VP 4P4 7027.140-2M		5650	41,9	134	5975	36,3	50
STYLO VP 4P4 7027.160-2M		6370	48	132	6760	41,8	50
STYLO VP 4P4 7027.180-2M		7040	54,2	129	7526	47,3	50
STYLO VP 4P4 7027.200-2M		7650	60,5	126	8275	52,9	50
STYLO VP 4P4 7027.050-3M		3190	23,3	136	3337	18,7	50
STYLO VP 4P4 7027.060-3M		3790	27,4	138	3989	22,6	50
STYLO VP 4P4 7027.070-3M		4390	31,5	139	4634	26,5	50
STYLO VP 4P4 7027.080-3M		4990	35,6	140	5273	30,4	50
STYLO VP 4P4 7027.090-3M		5580	39,8	140	5905	34,3	50
STYLO VP 4P4 7027.100-3M		6170	44	140	6530	38,3	50
STYLO VP 4P4 7027.120-3M		7330	52,6	139	7760	46,3	50
STYLO VP 4P4 7027.140-3M		8450	61,5	137	8963	54,4	50
STYLO VP 4P4 7027.160-3M		9510	70,7	134	10140	62,6	50
STYLO VP 4P4 7027.180-3M		10510	80,3	130	11289	70,9	50
STYLO VP 4P4 7027.200-3M		11420	90,4	126	12412	79,3	35
STYLO VP 4P4 7027.050-4M		4290	30	143	4450	24,9	50
STYLO VP 4P4 7027.060-4M		5110	35,3	144	5319	30,1	50
STYLO VP 4P4 7027.070-4M		5910	40,7	145	6179	35,3	50
STYLO VP 4P4 7027.080-4M		6700	46,3	144	7030	40,5	50
STYLO VP 4P4 7027.090-4M		7470	52	143	7873	45,8	50
STYLO VP 4P4 7027.100-4M		8230	57,8	142	8706	51,1	50
STYLO VP 4P4 7027.120-4M		9700	69,7	139	10346	61,7	50
STYLO VP 4P4 7027.140-4M		11120	81,8	135	11951	72,6	50
STYLO VP 4P4 7027.160-4M		12490	94	132	13519	83,5	50
STYLO VP 4P4 7027.180-4M		13820	106	130	15052	94,6	35
STYLO VP 4P4 7027.200-4M		15120	118	128	16550	106	35
STYLO VP 4P4 7027.080-5M		8370	57,2	146	8788	50,6	50
STYLO VP 4P4 7027.090-5M		9350	64,1	145	9841	57,2	50
STYLO VP 4P4 7027.100-5M		10310	71,1	145	10883	63,8	50
STYLO VP 4P4 7027.120-5M		12170	85,3	142	12933	77,2	50
STYLO VP 4P4 7027.140-5M		13980	100	139	14938	90,7	50
STYLO VP 4P4 7027.160-5M		15720	115	136	16899	104	35
STYLO VP 4P4 7027.180-5M		17400	131	132	18816	118	35
STYLO VP 4P4 7027.080-6M		10040	68,4	146	10546	60,8	50
STYLO VP 4P4 7027.090-6M		11210	76,7	146	11809	68,6	50
STYLO VP 4P4 7027.100-6M		12350	85,1	145	13059	76,6	50
STYLO VP 4P4 7027.120-6M		14570	102	142	15520	92,6	50
STYLO VP 4P4 7027.140-6M		16700	120	139	17926	109	50
STYLO VP 4P4 7027.160-6M		18760	138	135	20279	125	35
STYLO VP 4P4 7027.180-6M		20740	158	131	22579	142	35
STYLO VP 4P4 7027.080-7M		11710	79,7	146	12303	70,9	50
STYLO VP 4P4 7027.090-7M		13090	89,8	145	13777	80,1	50
STYLO VP 4P4 7027.100-7M		14460	100	144	15236	89,4	50
STYLO VP 4P4 7027.120-7M		17140	121	141	18106	108	50
STYLO VP 4P4 7027.140-7M		19730	142	138	20914	127	50
STYLO VP 4P4 7027.050-1M		1080	8,3	130	1112	6,2	50
STYLO VP 4P4 7027.060-1M		1280	9,6	133	1330	7,5	50
STYLO VP 4P4 7027.070-1M		1490	11	135	1545	8,8	50
STYLO VP 4P4 7027.080-1M		1690	12,4	136	1758	10,1	50
STYLO VP 4P4 7027.090-1M		1900	13,8	137	1968	11,4	50
STYLO VP 4P4 7027.100-1M		2110	15,3	137	2177	12,8	50
STYLO VP 4P4 7027.120-1M		2510	18,4	136	2587	15,4	50
STYLO VP 4P4 7027.140-1M		2910	21,5	135	2988	18,1	50
STYLO VP 4P4 7027.160-1M		3280	24,7	132	3380	20,9	50
STYLO VP 4P4 7027.180-1M		3630	27,9	130	3763	23,6	50
STYLO VP 4P4 7027.200-1M		3940	31	127	4137	26,4	50
STYLO VP 4P4 7027.050-2M		2180	16	136	2225	12,5	50
STYLO VP 4P4 7027.060-2M		2580	18,7	137	2659	15	50
STYLO VP 4P4 7027.070-2M		2990	21,5	139	3090	17,6	50
STYLO VP 4P4 7027.080-2M		3400	24,3	139	3515	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7027.090-2M		3810	27,1	140	3936	22,9	50
STYLO VP 4P4 7027.100-2M		4210	30	140	4353	25,5	50
STYLO VP 4P4 7027.120-2M		5010	35,9	139	5173	30,9	50
STYLO VP 4P4 7027.140-2M		5780	41,9	137	5975	36,3	50
STYLO VP 4P4 7027.160-2M		6510	48	135	6760	41,8	50
STYLO VP 4P4 7027.180-2M		7200	54,2	132	7526	47,3	50
STYLO VP 4P4 7027.200-2M		7830	60,5	129	8275	52,9	50
STYLO VP 4P4 7027.050-3M		3270	23,3	140	3337	18,7	50
STYLO VP 4P4 7027.060-3M		3880	27,4	141	3989	22,6	50
STYLO VP 4P4 7027.070-3M		4500	31,5	142	4634	26,5	50
STYLO VP 4P4 7027.080-3M		5110	35,6	143	5273	30,4	50
STYLO VP 4P4 7027.090-3M		5720	39,8	143	5905	34,3	50
STYLO VP 4P4 7027.100-3M		6320	44	143	6530	38,3	50
STYLO VP 4P4 7027.120-3M		7500	52,6	142	7760	46,3	50
STYLO VP 4P4 7027.140-3M		8640	61,5	140	8963	54,4	50
STYLO VP 4P4 7027.160-3M		9730	70,7	137	10140	62,6	50
STYLO VP 4P4 7027.180-3M		10740	80,3	133	11289	70,9	50
STYLO VP 4P4 7027.200-3M		11680	90,4	129	12412	79,3	35
STYLO VP 4P4 7027.050-4M		4390	30	146	4450	24,9	50
STYLO VP 4P4 7027.060-4M		5230	35,3	148	5319	30,1	50
STYLO VP 4P4 7027.070-4M		6050	40,7	148	6179	35,3	50
STYLO VP 4P4 7027.080-4M		6850	46,3	147	7030	40,5	50
STYLO VP 4P4 7027.090-4M		7640	52	146	7873	45,8	50
STYLO VP 4P4 7027.100-4M		8420	57,8	145	8706	51,1	50
STYLO VP 4P4 7027.120-4M		9920	69,7	142	10346	61,7	50
STYLO VP 4P4 7027.140-4M		11370	81,8	138	11951	72,6	50
STYLO VP 4P4 7027.160-4M		12770	94	135	13519	83,5	50
STYLO VP 4P4 7027.180-4M		14140	106	133	15052	94,6	35
STYLO VP 4P4 7027.200-4M		15470	118	131	16550	106	35
STYLO VP 4P4 7027.080-5M		8560	57,2	149	8788	50,6	50
STYLO VP 4P4 7027.090-5M		9560	64,1	149	9841	57,2	50
STYLO VP 4P4 7027.100-5M		10540	71,1	148	10883	63,8	50
STYLO VP 4P4 7027.120-5M		12450	85,3	145	12933	77,2	50
STYLO VP 4P4 7027.140-5M		14300	100	143	14938	90,7	50
STYLO VP 4P4 7027.160-5M		16090	115	139	16899	104	35
STYLO VP 4P4 7027.180-5M		17810	131	135	18816	118	35
STYLO VP 4P4 7027.080-6M		10270	68,4	150	10546	60,8	50
STYLO VP 4P4 7027.090-6M		11470	76,7	149	11809	68,6	50
STYLO VP 4P4 7027.100-6M		12640	85,1	148	13059	76,6	50
STYLO VP 4P4 7027.120-6M		14910	102	146	15520	92,6	50
STYLO VP 4P4 7027.140-6M		17090	120	142	17926	109	50
STYLO VP 4P4 7027.160-6M		19190	138	139	20279	125	35
STYLO VP 4P4 7027.180-6M		21220	158	134	22579	142	35
STYLO VP 4P4 7027.080-7M		11980	79,7	150	12303	70,9	50
STYLO VP 4P4 7027.090-7M		13390	89,8	149	13777	80,1	50
STYLO VP 4P4 7027.100-7M		14800	100	148	15236	89,4	50
STYLO VP 4P4 7027.120-7M		17540	121	144	18106	108	50
STYLO VP 4P4 7027.140-7M		20190	142	142	20914	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO VP 4P4 2200K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7022.050-1M	STE-S	940	8,3	113	1001	6,2	50
STYLO VP 4P4 7022.060-1M		1120	9,6	116	1197	7,5	50
STYLO VP 4P4 7022.070-1M		1290	11	117	1390	8,8	50
STYLO VP 4P4 7022.080-1M		1470	12,4	118	1582	10,1	50
STYLO VP 4P4 7022.090-1M		1650	13,8	119	1771	11,4	50
STYLO VP 4P4 7022.100-1M		1830	15,3	119	1959	12,8	50
STYLO VP 4P4 7022.120-1M		2180	18,4	118	2328	15,4	50
STYLO VP 4P4 7022.140-1M		2530	21,5	117	2689	18,1	50
STYLO VP 4P4 7022.160-1M		2850	24,7	115	3042	20,9	50
STYLO VP 4P4 7022.180-1M		3150	27,9	112	3387	23,6	50
STYLO VP 4P4 7022.200-1M		3430	31	110	3724	26,4	50
STYLO VP 4P4 7022.050-2M		1890	16	118	2002	12,5	50
STYLO VP 4P4 7022.060-2M		2240	18,7	119	2394	15	50
STYLO VP 4P4 7022.070-2M		2600	21,5	120	2781	17,6	50
STYLO VP 4P4 7022.080-2M		2950	24,3	121	3164	20,3	50
STYLO VP 4P4 7022.090-2M		3310	27,1	122	3543	22,9	50
STYLO VP 4P4 7022.100-2M		3660	30	122	3918	25,5	50
STYLO VP 4P4 7022.120-2M		4360	35,9	121	4656	30,9	50
STYLO VP 4P4 7022.140-2M		5030	41,9	120	5378	36,3	50
STYLO VP 4P4 7022.160-2M		5670	48	118	6084	41,8	50
STYLO VP 4P4 7022.180-2M		6270	54,2	115	6774	47,3	50
STYLO VP 4P4 7022.200-2M		6810	60,5	112	7447	52,9	50
STYLO VP 4P4 7022.050-3M		2840	23,3	121	3004	18,7	50
STYLO VP 4P4 7022.060-3M		3370	27,4	122	3590	22,6	50
STYLO VP 4P4 7022.070-3M		3910	31,5	124	4171	26,5	50
STYLO VP 4P4 7022.080-3M		4440	35,6	124	4746	30,4	50
STYLO VP 4P4 7022.090-3M		4970	39,8	124	5314	34,3	50
STYLO VP 4P4 7022.100-3M		5490	44	124	5877	38,3	50
STYLO VP 4P4 7022.120-3M		6520	52,6	123	6984	46,3	50
STYLO VP 4P4 7022.140-3M		7520	61,5	122	8067	54,4	50
STYLO VP 4P4 7022.160-3M		8460	70,7	119	9126	62,6	50
STYLO VP 4P4 7022.180-3M		9350	80,3	116	10160	70,9	50
STYLO VP 4P4 7022.200-3M		10160	90,4	112	11171	79,3	35
STYLO VP 4P4 7022.050-4M		3810	30	127	4005	24,9	50
STYLO VP 4P4 7022.060-4M		4540	35,3	128	4787	30,1	50
STYLO VP 4P4 7022.070-4M		5250	40,7	128	5561	35,3	50
STYLO VP 4P4 7022.080-4M		5950	46,3	128	6327	40,5	50
STYLO VP 4P4 7022.090-4M		6640	52	127	7086	45,8	50
STYLO VP 4P4 7022.100-4M		7310	57,8	126	7836	51,1	50
STYLO VP 4P4 7022.120-4M		8630	69,7	123	9312	61,7	50
STYLO VP 4P4 7022.140-4M		9890	81,8	120	10756	72,6	50
STYLO VP 4P4 7022.160-4M		11110	94	118	12167	83,5	50
STYLO VP 4P4 7022.180-4M		12300	106	116	13547	94,6	35
STYLO VP 4P4 7022.200-4M		13450	118	113	14895	106	35
STYLO VP 4P4 7022.080-5M		7450	57,2	130	7909	50,6	50
STYLO VP 4P4 7022.090-5M		8320	64,1	129	8857	57,2	50
STYLO VP 4P4 7022.100-5M		9170	71,1	128	9795	63,8	50
STYLO VP 4P4 7022.120-5M		10830	85,3	126	11640	77,2	50
STYLO VP 4P4 7022.140-5M		12430	100	124	13445	90,7	50
STYLO VP 4P4 7022.160-5M		13980	115	121	15209	104	35
STYLO VP 4P4 7022.180-5M		15480	131	118	16934	118	35
STYLO VP 4P4 7022.080-6M		8940	68,4	130	9491	60,8	50
STYLO VP 4P4 7022.090-6M		9980	76,7	130	10628	68,6	50
STYLO VP 4P4 7022.100-6M		10990	85,1	129	11753	76,6	50
STYLO VP 4P4 7022.120-6M		12970	102	127	13968	92,6	50
STYLO VP 4P4 7022.140-6M		14860	120	123	16134	109	50
STYLO VP 4P4 7022.160-6M		16690	138	120	18251	125	35
STYLO VP 4P4 7022.180-6M		18450	158	116	20321	142	35
STYLO VP 4P4 7022.080-7M		10420	79,7	130	11073	70,9	50
STYLO VP 4P4 7022.090-7M		11650	89,8	129	12400	80,1	50
STYLO VP 4P4 7022.100-7M		12870	100	128	13712	89,4	50
STYLO VP 4P4 7022.120-7M		15250	121	126	16296	108	50
STYLO VP 4P4 7022.140-7M		17550	142	123	18822	127	50
STYLO VP 4P4 7022.050-1M	STA STA1 STU-S	950	8,3	114	1001	6,2	50
STYLO VP 4P4 7022.060-1M		1130	9,6	117	1197	7,5	50
STYLO VP 4P4 7022.070-1M		1310	11	119	1390	8,8	50
STYLO VP 4P4 7022.080-1M		1490	12,4	120	1582	10,1	50
STYLO VP 4P4 7022.090-1M		1670	13,8	121	1771	11,4	50
STYLO VP 4P4 7022.100-1M		1850	15,3	120	1959	12,8	50
STYLO VP 4P4 7022.120-1M		2210	18,4	120	2328	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7022.140-1M		2560	21,5	119	2689	18,1	50
STYLO VP 4P4 7022.160-1M		2890	24,7	117	3042	20,9	50
STYLO VP 4P4 7022.180-1M		3190	27,9	114	3387	23,6	50
STYLO VP 4P4 7022.200-1M		3470	31	111	3724	26,4	50
STYLO VP 4P4 7022.050-2M		1910	16	119	2002	12,5	50
STYLO VP 4P4 7022.060-2M		2270	18,7	121	2394	15	50
STYLO VP 4P4 7022.070-2M		2630	21,5	122	2781	17,6	50
STYLO VP 4P4 7022.080-2M		2990	24,3	123	3164	20,3	50
STYLO VP 4P4 7022.090-2M		3340	27,1	123	3543	22,9	50
STYLO VP 4P4 7022.100-2M		3700	30	123	3918	25,5	50
STYLO VP 4P4 7022.120-2M		4410	35,9	122	4656	30,9	50
STYLO VP 4P4 7022.140-2M		5090	41,9	121	5378	36,3	50
STYLO VP 4P4 7022.160-2M		5730	48	119	6084	41,8	50
STYLO VP 4P4 7022.180-2M		6340	54,2	116	6774	47,3	50
STYLO VP 4P4 7022.200-2M		6890	60,5	113	7447	52,9	50
STYLO VP 4P4 7022.050-3M		2870	23,3	123	3004	18,7	50
STYLO VP 4P4 7022.060-3M		3410	27,4	124	3590	22,6	50
STYLO VP 4P4 7022.070-3M		3950	31,5	125	4171	26,5	50
STYLO VP 4P4 7022.080-3M		4490	35,6	126	4746	30,4	50
STYLO VP 4P4 7022.090-3M		5030	39,8	126	5314	34,3	50
STYLO VP 4P4 7022.100-3M		5560	44	126	5877	38,3	50
STYLO VP 4P4 7022.120-3M		6600	52,6	125	6984	46,3	50
STYLO VP 4P4 7022.140-3M		7610	61,5	123	8067	54,4	50
STYLO VP 4P4 7022.160-3M		8560	70,7	121	9126	62,6	50
STYLO VP 4P4 7022.180-3M		9460	80,3	117	10160	70,9	50
STYLO VP 4P4 7022.200-3M		10280	90,4	113	11171	79,3	35
STYLO VP 4P4 7022.050-4M		3860	30	128	4005	24,9	50
STYLO VP 4P4 7022.060-4M		4600	35,3	130	4787	30,1	50
STYLO VP 4P4 7022.070-4M		5320	40,7	130	5561	35,3	50
STYLO VP 4P4 7022.080-4M		6030	46,3	130	6327	40,5	50
STYLO VP 4P4 7022.090-4M		6720	52	129	7086	45,8	50
STYLO VP 4P4 7022.100-4M		7400	57,8	128	7836	51,1	50
STYLO VP 4P4 7022.120-4M		8730	69,7	125	9312	61,7	50
STYLO VP 4P4 7022.140-4M		10000	81,8	122	10756	72,6	50
STYLO VP 4P4 7022.160-4M		11240	94	119	12167	83,5	50
STYLO VP 4P4 7022.180-4M		12440	106	117	13547	94,6	35
STYLO VP 4P4 7022.200-4M		13610	118	115	14895	106	35
STYLO VP 4P4 7022.080-5M		7530	57,2	131	7909	50,6	50
STYLO VP 4P4 7022.090-5M		8410	64,1	131	8857	57,2	50
STYLO VP 4P4 7022.100-5M		9270	71,1	130	9795	63,8	50
STYLO VP 4P4 7022.120-5M		10960	85,3	128	11640	77,2	50
STYLO VP 4P4 7022.140-5M		12580	100	125	13445	90,7	50
STYLO VP 4P4 7022.160-5M		14150	115	123	15209	104	35
STYLO VP 4P4 7022.180-5M		15660	131	119	16934	118	35
STYLO VP 4P4 7022.080-6M		9040	68,4	132	9491	60,8	50
STYLO VP 4P4 7022.090-6M		10080	76,7	131	10628	68,6	50
STYLO VP 4P4 7022.100-6M		11110	85,1	130	11753	76,6	50
STYLO VP 4P4 7022.120-6M		13110	102	128	13968	92,6	50
STYLO VP 4P4 7022.140-6M		15030	120	125	16134	109	50
STYLO VP 4P4 7022.160-6M		16880	138	122	18251	125	35
STYLO VP 4P4 7022.180-6M		18660	158	118	20321	142	35
STYLO VP 4P4 7022.080-7M		10540	79,7	132	11073	70,9	50
STYLO VP 4P4 7022.090-7M		11780	89,8	131	12400	80,1	50
STYLO VP 4P4 7022.100-7M		13020	100	130	13712	89,4	50
STYLO VP 4P4 7022.120-7M		15430	121	127	16296	108	50
STYLO VP 4P4 7022.140-7M		17760	142	125	18822	127	50
STYLO VP 4P4 7022.050-1M		970	8,3	116	1001	6,2	50
STYLO VP 4P4 7022.060-1M		1160	9,6	120	1197	7,5	50
STYLO VP 4P4 7022.070-1M		1340	11	121	1390	8,8	50
STYLO VP 4P4 7022.080-1M		1520	12,4	122	1582	10,1	50
STYLO VP 4P4 7022.090-1M		1710	13,8	123	1771	11,4	50
STYLO VP 4P4 7022.100-1M		1900	15,3	124	1959	12,8	50
STYLO VP 4P4 7022.120-1M		2260	18,4	122	2328	15,4	50
STYLO VP 4P4 7022.140-1M		2620	21,5	121	2689	18,1	50
STYLO VP 4P4 7022.160-1M		2950	24,7	119	3042	20,9	50
STYLO VP 4P4 7022.180-1M		3270	27,9	117	3387	23,6	50
STYLO VP 4P4 7022.200-1M		3550	31	114	3724	26,4	50
STYLO VP 4P4 7022.050-2M		1960	16	122	2002	12,5	50
STYLO VP 4P4 7022.060-2M		2330	18,7	124	2394	15	50
STYLO VP 4P4 7022.070-2M		2690	21,5	125	2781	17,6	50
STYLO VP 4P4 7022.080-2M		3060	24,3	125	3164	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO VP 4P4 7022.090-2M		3430	27,1	126	3543	22,9	50
STYLO VP 4P4 7022.100-2M		3790	30	126	3918	25,5	50
STYLO VP 4P4 7022.120-2M		4510	35,9	125	4656	30,9	50
STYLO VP 4P4 7022.140-2M		5200	41,9	124	5378	36,3	50
STYLO VP 4P4 7022.160-2M		5860	48	122	6084	41,8	50
STYLO VP 4P4 7022.180-2M		6480	54,2	119	6774	47,3	50
STYLO VP 4P4 7022.200-2M		7050	60,5	116	7447	52,9	50
STYLO VP 4P4 7022.050-3M		2940	23,3	126	3004	18,7	50
STYLO VP 4P4 7022.060-3M		3490	27,4	127	3590	22,6	50
STYLO VP 4P4 7022.070-3M		4050	31,5	128	4171	26,5	50
STYLO VP 4P4 7022.080-3M		4600	35,6	129	4746	30,4	50
STYLO VP 4P4 7022.090-3M		5140	39,8	129	5314	34,3	50
STYLO VP 4P4 7022.100-3M		5690	44	129	5877	38,3	50
STYLO VP 4P4 7022.120-3M		6750	52,6	128	6984	46,3	50
STYLO VP 4P4 7022.140-3M		7780	61,5	126	8067	54,4	50
STYLO VP 4P4 7022.160-3M		8750	70,7	123	9126	62,6	50
STYLO VP 4P4 7022.180-3M		9670	80,3	120	10160	70,9	50
STYLO VP 4P4 7022.200-3M		10510	90,4	116	11171	79,3	35
STYLO VP 4P4 7022.050-4M		3950	30	131	4005	24,9	50
STYLO VP 4P4 7022.060-4M		4700	35,3	133	4787	30,1	50
STYLO VP 4P4 7022.070-4M		5440	40,7	133	5561	35,3	50
STYLO VP 4P4 7022.080-4M		6170	46,3	133	6327	40,5	50
STYLO VP 4P4 7022.090-4M		6880	52	132	7086	45,8	50
STYLO VP 4P4 7022.100-4M		7570	57,8	130	7836	51,1	50
STYLO VP 4P4 7022.120-4M		8930	69,7	128	9312	61,7	50
STYLO VP 4P4 7022.140-4M		10230	81,8	125	10756	72,6	50
STYLO VP 4P4 7022.160-4M		11490	94	122	12167	83,5	50
STYLO VP 4P4 7022.180-4M		12720	106	120	13547	94,6	35
STYLO VP 4P4 7022.200-4M		13920	118	117	14895	106	35
STYLO VP 4P4 7022.080-5M		7700	57,2	134	7909	50,6	50
STYLO VP 4P4 7022.090-5M		8600	64,1	134	8857	57,2	50
STYLO VP 4P4 7022.100-5M		9490	71,1	133	9795	63,8	50
STYLO VP 4P4 7022.120-5M		11210	85,3	131	11640	77,2	50
STYLO VP 4P4 7022.140-5M		12870	100	128	13445	90,7	50
STYLO VP 4P4 7022.160-5M		14480	115	125	15209	104	35
STYLO VP 4P4 7022.180-5M		16030	131	122	16934	118	35
STYLO VP 4P4 7022.080-6M		9250	68,4	135	9491	60,8	50
STYLO VP 4P4 7022.090-6M		10320	76,7	134	10628	68,6	50
STYLO VP 4P4 7022.100-6M		11370	85,1	133	11753	76,6	50
STYLO VP 4P4 7022.120-6M		13420	102	131	13968	92,6	50
STYLO VP 4P4 7022.140-6M		15380	120	128	16134	109	50
STYLO VP 4P4 7022.160-6M		17270	138	125	18251	125	35
STYLO VP 4P4 7022.180-6M		19090	158	120	20321	142	35
STYLO VP 4P4 7022.080-7M		10780	79,7	135	11073	70,9	50
STYLO VP 4P4 7022.090-7M		12060	89,8	134	12400	80,1	50
STYLO VP 4P4 7022.100-7M		13320	100	133	13712	89,4	50
STYLO VP 4P4 7022.120-7M		15780	121	130	16296	108	50
STYLO VP 4P4 7022.140-7M		18170	142	127	18822	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 5P5 4000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7040.040-1M		1110	8,5	130	1240	6,2	50
STYLO PC 5P5 7040.050-1M		1360	10,2	133	1545	7,8	50
STYLO PC 5P5 7040.060-1M		1620	11,9	136	1847	9,4	50
STYLO PC 5P5 7040.070-1M		1870	13,6	137	2146	11	50
STYLO PC 5P5 7040.080-1M		2130	15,4	138	2441	12,7	50
STYLO PC 5P5 7040.090-1M		2390	17,2	138	2734	14,3	50
STYLO PC 5P5 7040.100-1M		2640	19,1	138	3023	16	50
STYLO PC 5P5 7040.120-1M		3140	22,9	137	3592	19,3	50
STYLO PC 5P5 7040.140-1M		3630	26,8	135	4150	22,7	50
STYLO PC 5P5 7040.160-1M		4100	30,8	133	4694	26,1	50
STYLO PC 5P5 7040.180-1M		4530	34,8	130	5227	29,6	50
STYLO PC 5P5 7040.200-1M		4930	38,8	127	5746	33,1	50
STYLO PC 5P5 7040.040-2M		2220	16	138	2480	12,4	50
STYLO PC 5P5 7040.050-2M		2720	19,5	139	3090	15,6	50
STYLO PC 5P5 7040.060-2M		3220	23	140	3694	18,8	50
STYLO PC 5P5 7040.070-2M		3730	26,6	140	4291	22	50
STYLO PC 5P5 7040.080-2M		4240	30,1	140	4882	25,3	50
STYLO PC 5P5 7040.090-2M		4750	33,8	140	5467	28,6	50
STYLO PC 5P5 7040.100-2M		5260	37,4	140	6046	31,9	50
STYLO PC 5P5 7040.120-2M		6260	44,8	139	7185	38,6	50
STYLO PC 5P5 7040.140-2M		7230	52,3	138	8299	45,4	50
STYLO PC 5P5 7040.160-2M		8150	59,9	136	9388	52,2	50
STYLO PC 5P5 7040.180-2M		9010	67,7	133	10453	59,1	50
STYLO PC 5P5 7040.200-2M		9790	75,6	129	11493	66,1	50
STYLO PC 5P5 7040.040-3M		3320	23,3	142	3721	18,5	50
STYLO PC 5P5 7040.050-3M		4080	28,5	143	4635	23,3	50
STYLO PC 5P5 7040.060-3M		4850	33,8	143	5541	28,2	50
STYLO PC 5P5 7040.070-3M		5620	39	144	6437	33,1	50
STYLO PC 5P5 7040.080-3M		6380	44,2	144	7323	38	50
STYLO PC 5P5 7040.090-3M		7150	49,5	144	8201	42,9	50
STYLO PC 5P5 7040.100-3M		7900	54,8	144	9069	47,9	50
STYLO PC 5P5 7040.120-3M		9380	65,6	142	10777	57,9	50
STYLO PC 5P5 7040.140-3M	S05	10810	76,7	140	12449	68	50
STYLO PC 5P5 7040.160-3M	S07	12170	88,2	137	14083	78,3	50
STYLO PC 5P5 7040.180-3M	STA	13440	100	134	15680	88,7	50
STYLO PC 5P5 7040.200-3M	STA1	14610	113	129	17239	99,2	35
STYLO PC 5P5 7040.040-4M	STE-S	4410	30	147	4961	24,7	50
STYLO PC 5P5 7040.050-4M	STU-S	5480	36,6	149	6180	31,1	50
STYLO PC 5P5 7040.060-4M		6530	43,4	150	7387	37,6	50
STYLO PC 5P5 7040.070-4M		7560	50,4	149	8582	44,1	50
STYLO PC 5P5 7040.080-4M		8560	57,4	149	9765	50,6	50
STYLO PC 5P5 7040.090-4M		9550	64,7	147	10934	57,2	50
STYLO PC 5P5 7040.100-4M		10520	72	146	12092	63,8	50
STYLO PC 5P5 7040.120-4M		12400	86,9	142	14370	77,2	50
STYLO PC 5P5 7040.140-4M		14220	102	139	16598	90,7	50
STYLO PC 5P5 7040.160-4M		15980	117	136	18777	104	50
STYLO PC 5P5 7040.180-4M		17680	132	133	20906	118	35
STYLO PC 5P5 7040.200-4M		19340	147	131	22986	132	35
STYLO PC 5P5 7040.060-5M		8160	53,4	152	9234	47	50
STYLO PC 5P5 7040.070-5M		9450	62,2	151	10728	55,1	50
STYLO PC 5P5 7040.080-5M		10720	71	150	12206	63,3	50
STYLO PC 5P5 7040.090-5M		11970	79,7	150	13668	71,5	50
STYLO PC 5P5 7040.100-5M		13190	88,6	148	15115	79,8	50
STYLO PC 5P5 7040.120-5M		15580	107	145	17962	96,5	50
STYLO PC 5P5 7040.140-5M		17880	125	143	20748	113	50
STYLO PC 5P5 7040.160-5M		20110	144	139	23471	130	35
STYLO PC 5P5 7040.180-5M		22260	164	135	26133	148	35
STYLO PC 5P5 7040.060-6M		9780	63,9	153	11081	56,4	50
STYLO PC 5P5 7040.070-6M		11320	74,3	152	12873	66,1	50
STYLO PC 5P5 7040.080-6M		12850	84,8	151	14647	75,9	50
STYLO PC 5P5 7040.090-6M		14340	95,4	150	16402	85,8	50
STYLO PC 5P5 7040.100-6M		15800	106	149	18138	95,7	50
STYLO PC 5P5 7040.120-6M		18640	128	145	21555	116	50
STYLO PC 5P5 7040.140-6M		21380	150	142	24897	136	50
STYLO PC 5P5 7040.160-6M		24010	173	138	28165	157	35
STYLO PC 5P5 7040.180-6M		26540	197	134	31359	177	35
STYLO PC 5P5 7040.060-7M		11380	74,4	152	12928	65,8	50
STYLO PC 5P5 7040.070-7M		13190	87	151	15019	77,2	50
STYLO PC 5P5 7040.080-7M		14980	99,6	150	17088	88,6	50
STYLO PC 5P5 7040.090-7M		16760	112	149	19135	100	50

AEC Illuminazione

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7040.100-7M		18510	125	148	21161	112	50
STYLO PC 5P5 7040.120-7M		21940	151	145	25147	135	50
STYLO PC 5P5 7040.140-7M		25250	177	142	29047	159	50
STYLO PC 5P5 7040.040-1M		1140	8,5	134	1240	6,2	50
STYLO PC 5P5 7040.050-1M		1390	10,2	136	1545	7,8	50
STYLO PC 5P5 7040.060-1M		1650	11,9	138	1847	9,4	50
STYLO PC 5P5 7040.070-1M		1910	13,6	140	2146	11	50
STYLO PC 5P5 7040.080-1M		2180	15,4	141	2441	12,7	50
STYLO PC 5P5 7040.090-1M		2440	17,2	141	2734	14,3	50
STYLO PC 5P5 7040.100-1M		2700	19,1	141	3023	16	50
STYLO PC 5P5 7040.120-1M		3220	22,9	140	3592	19,3	50
STYLO PC 5P5 7040.140-1M		3720	26,8	138	4150	22,7	50
STYLO PC 5P5 7040.160-1M		4200	30,8	136	4694	26,1	50
STYLO PC 5P5 7040.180-1M		4640	34,8	133	5227	29,6	50
STYLO PC 5P5 7040.200-1M		5050	38,8	130	5746	33,1	50
STYLO PC 5P5 7040.040-2M		2270	16	141	2480	12,4	50
STYLO PC 5P5 7040.050-2M		2780	19,5	142	3090	15,6	50
STYLO PC 5P5 7040.060-2M		3300	23	143	3694	18,8	50
STYLO PC 5P5 7040.070-2M		3820	26,6	143	4291	22	50
STYLO PC 5P5 7040.080-2M		4350	30,1	144	4882	25,3	50
STYLO PC 5P5 7040.090-2M		4870	33,8	144	5467	28,6	50
STYLO PC 5P5 7040.100-2M		5390	37,4	144	6046	31,9	50
STYLO PC 5P5 7040.120-2M		6420	44,8	143	7185	38,6	50
STYLO PC 5P5 7040.140-2M		7410	52,3	141	8299	45,4	50
STYLO PC 5P5 7040.160-2M		8350	59,9	139	9388	52,2	50
STYLO PC 5P5 7040.180-2M		9230	67,7	136	10453	59,1	50
STYLO PC 5P5 7040.200-2M		10030	75,6	132	11493	66,1	50
STYLO PC 5P5 7040.040-3M		3400	23,3	145	3721	18,5	50
STYLO PC 5P5 7040.050-3M		4180	28,5	146	4635	23,3	50
STYLO PC 5P5 7040.060-3M		4970	33,8	147	5541	28,2	50
STYLO PC 5P5 7040.070-3M		5760	39	147	6437	33,1	50
STYLO PC 5P5 7040.080-3M		6540	44,2	147	7323	38	50
STYLO PC 5P5 7040.090-3M		7320	49,5	147	8201	42,9	50
STYLO PC 5P5 7040.100-3M		8090	54,8	147	9069	47,9	50
STYLO PC 5P5 7040.120-3M		9610	65,6	146	10777	57,9	50
STYLO PC 5P5 7040.140-3M	STE-M	11070	76,7	144	12449	68	50
STYLO PC 5P5 7040.160-3M	STU-M	12460	88,2	141	14083	78,3	50
STYLO PC 5P5 7040.180-3M	SV	13770	100	137	15680	88,7	50
STYLO PC 5P5 7040.200-3M	STW	14970	113	132	17239	99,2	35
STYLO PC 5P5 7040.040-4M		4520	30	150	4961	24,7	50
STYLO PC 5P5 7040.050-4M		5620	36,6	153	6180	31,1	50
STYLO PC 5P5 7040.060-4M		6690	43,4	154	7387	37,6	50
STYLO PC 5P5 7040.070-4M		7750	50,4	153	8582	44,1	50
STYLO PC 5P5 7040.080-4M		8780	57,4	152	9765	50,6	50
STYLO PC 5P5 7040.090-4M		9790	64,7	151	10934	57,2	50
STYLO PC 5P5 7040.100-4M		10780	72	149	12092	63,8	50
STYLO PC 5P5 7040.120-4M		12710	86,9	146	14370	77,2	50
STYLO PC 5P5 7040.140-4M		14570	102	142	16598	90,7	50
STYLO PC 5P5 7040.160-4M		16370	117	139	18777	104	50
STYLO PC 5P5 7040.180-4M		18120	132	137	20906	118	35
STYLO PC 5P5 7040.200-4M		19820	147	134	22986	132	35
STYLO PC 5P5 7040.060-5M		8350	53,4	156	9234	47	50
STYLO PC 5P5 7040.070-5M		9670	62,2	155	10728	55,1	50
STYLO PC 5P5 7040.080-5M		10980	71	154	12206	63,3	50
STYLO PC 5P5 7040.090-5M		12250	79,7	153	13668	71,5	50
STYLO PC 5P5 7040.100-5M		13510	88,6	152	15115	79,8	50
STYLO PC 5P5 7040.120-5M		15960	107	149	17962	96,5	50
STYLO PC 5P5 7040.140-5M		18320	125	146	20748	113	50
STYLO PC 5P5 7040.160-5M		20600	144	143	23471	130	35
STYLO PC 5P5 7040.180-5M		22810	164	139	26133	148	35
STYLO PC 5P5 7040.060-6M		10020	63,9	156	11081	56,4	50
STYLO PC 5P5 7040.070-6M		11610	74,3	156	12873	66,1	50
STYLO PC 5P5 7040.080-6M		13160	84,8	155	14647	75,9	50
STYLO PC 5P5 7040.090-6M		14690	95,4	153	16402	85,8	50
STYLO PC 5P5 7040.100-6M		16190	106	152	18138	95,7	50
STYLO PC 5P5 7040.120-6M		19100	128	149	21555	116	50
STYLO PC 5P5 7040.140-6M		21900	150	146	24897	136	50
STYLO PC 5P5 7040.160-6M		24590	173	142	28165	157	35
STYLO PC 5P5 7040.180-6M		27190	197	138	31359	177	35
STYLO PC 5P5 7040.060-7M		11660	74,4	156	12928	65,8	50
STYLO PC 5P5 7040.070-7M		13510	87	155	15019	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7040.080-7M		15350	99,6	154	17088	88,6	50
STYLO PC 5P5 7040.090-7M		17170	112	153	19135	100	50
STYLO PC 5P5 7040.100-7M		18960	125	151	21161	112	50
STYLO PC 5P5 7040.120-7M		22470	151	148	25147	135	50
STYLO PC 5P5 7040.140-7M		25860	177	146	29047	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 5P5 3000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7030.040-1M		1040	8,5	122	1166	6,2	50
STYLO PC 5P5 7030.050-1M		1280	10,2	125	1452	7,8	50
STYLO PC 5P5 7030.060-1M		1520	11,9	127	1736	9,4	50
STYLO PC 5P5 7030.070-1M		1760	13,6	129	2017	11	50
STYLO PC 5P5 7030.080-1M		2000	15,4	129	2295	12,7	50
STYLO PC 5P5 7030.090-1M		2240	17,2	130	2570	14,3	50
STYLO PC 5P5 7030.100-1M		2480	19,1	129	2842	16	50
STYLO PC 5P5 7030.120-1M		2950	22,9	128	3377	19,3	50
STYLO PC 5P5 7030.140-1M		3410	26,8	127	3901	22,7	50
STYLO PC 5P5 7030.160-1M		3850	30,8	125	4413	26,1	50
STYLO PC 5P5 7030.180-1M		4260	34,8	122	4913	29,6	50
STYLO PC 5P5 7030.200-1M		4630	38,8	119	5402	33,1	50
STYLO PC 5P5 7030.040-2M		2090	16	130	2332	12,4	50
STYLO PC 5P5 7030.050-2M		2560	19,5	131	2905	15,6	50
STYLO PC 5P5 7030.060-2M		3030	23	131	3472	18,8	50
STYLO PC 5P5 7030.070-2M		3510	26,6	131	4034	22	50
STYLO PC 5P5 7030.080-2M		3990	30,1	132	4589	25,3	50
STYLO PC 5P5 7030.090-2M		4470	33,8	132	5139	28,6	50
STYLO PC 5P5 7030.100-2M		4940	37,4	132	5683	31,9	50
STYLO PC 5P5 7030.120-2M		5890	44,8	131	6754	38,6	50
STYLO PC 5P5 7030.140-2M		6800	52,3	130	7801	45,4	50
STYLO PC 5P5 7030.160-2M		7660	59,9	127	8825	52,2	50
STYLO PC 5P5 7030.180-2M		8470	67,7	125	9826	59,1	50
STYLO PC 5P5 7030.200-2M		9200	75,6	121	10803	66,1	50
STYLO PC 5P5 7030.040-3M		3120	23,3	133	3497	18,5	50
STYLO PC 5P5 7030.050-3M		3840	28,5	134	4357	23,3	50
STYLO PC 5P5 7030.060-3M		4560	33,8	134	5208	28,2	50
STYLO PC 5P5 7030.070-3M		5280	39	135	6050	33,1	50
STYLO PC 5P5 7030.080-3M		6000	44,2	135	6884	38	50
STYLO PC 5P5 7030.090-3M		6720	49,5	135	7709	42,9	50
STYLO PC 5P5 7030.100-3M		7430	54,8	135	8525	47,9	50
STYLO PC 5P5 7030.120-3M		8820	65,6	134	10131	57,9	50
STYLO PC 5P5 7030.140-3M	S05	10160	76,7	132	11702	68	50
STYLO PC 5P5 7030.160-3M	S07	11440	88,2	129	13238	78,3	50
STYLO PC 5P5 7030.180-3M	STA	12640	100	126	14739	88,7	50
STYLO PC 5P5 7030.200-3M	STA1	13730	113	121	16205	99,2	35
STYLO PC 5P5 7030.040-4M	STE-S	4150	30	138	4663	24,7	50
STYLO PC 5P5 7030.050-4M	STU-S	5150	36,6	140	5809	31,1	50
STYLO PC 5P5 7030.060-4M		6140	43,4	141	6944	37,6	50
STYLO PC 5P5 7030.070-4M		7100	50,4	140	8067	44,1	50
STYLO PC 5P5 7030.080-4M		8050	57,4	140	9179	50,6	50
STYLO PC 5P5 7030.090-4M		8980	64,7	138	10278	57,2	50
STYLO PC 5P5 7030.100-4M		9890	72	137	11367	63,8	50
STYLO PC 5P5 7030.120-4M		11660	86,9	134	13508	77,2	50
STYLO PC 5P5 7030.140-4M		13370	102	131	15602	90,7	50
STYLO PC 5P5 7030.160-4M		15020	117	128	17650	104	50
STYLO PC 5P5 7030.180-4M		16620	132	125	19652	118	35
STYLO PC 5P5 7030.200-4M		18180	147	123	21606	132	35
STYLO PC 5P5 7030.060-5M		7670	53,4	143	8680	47	50
STYLO PC 5P5 7030.070-5M		8880	62,2	142	10084	55,1	50
STYLO PC 5P5 7030.080-5M		10080	71	141	11473	63,3	50
STYLO PC 5P5 7030.090-5M		11250	79,7	141	12848	71,5	50
STYLO PC 5P5 7030.100-5M		12400	88,6	139	14208	79,8	50
STYLO PC 5P5 7030.120-5M		14640	107	136	16885	96,5	50
STYLO PC 5P5 7030.140-5M		16810	125	134	19503	113	50
STYLO PC 5P5 7030.160-5M		18900	144	131	22063	130	35
STYLO PC 5P5 7030.180-5M		20930	164	127	24565	148	35
STYLO PC 5P5 7030.060-6M		9190	63,9	143	10416	56,4	50
STYLO PC 5P5 7030.070-6M		10650	74,3	143	12101	66,1	50
STYLO PC 5P5 7030.080-6M		12070	84,8	142	13768	75,9	50
STYLO PC 5P5 7030.090-6M		13480	95,4	141	15418	85,8	50
STYLO PC 5P5 7030.100-6M		14850	106	140	17050	95,7	50
STYLO PC 5P5 7030.120-6M		17530	128	136	20262	116	50
STYLO PC 5P5 7030.140-6M		20100	150	134	23404	136	50
STYLO PC 5P5 7030.160-6M		22570	173	130	26476	157	35
STYLO PC 5P5 7030.180-6M		24950	197	126	29478	177	35
STYLO PC 5P5 7030.060-7M		10690	74,4	143	12152	65,8	50
STYLO PC 5P5 7030.070-7M		12400	87	142	14118	77,2	50
STYLO PC 5P5 7030.080-7M		14080	99,6	141	16063	88,6	50
STYLO PC 5P5 7030.090-7M		15750	112	140	17987	100	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7030.100-7M		17400	125	139	19891	112	50
STYLO PC 5P5 7030.120-7M		20620	151	136	23639	135	50
STYLO PC 5P5 7030.140-7M		23740	177	134	27304	159	50
STYLO PC 5P5 7030.040-1M		1070	8,5	125	1166	6,2	50
STYLO PC 5P5 7030.050-1M		1310	10,2	128	1452	7,8	50
STYLO PC 5P5 7030.060-1M		1550	11,9	130	1736	9,4	50
STYLO PC 5P5 7030.070-1M		1800	13,6	132	2017	11	50
STYLO PC 5P5 7030.080-1M		2040	15,4	132	2295	12,7	50
STYLO PC 5P5 7030.090-1M		2290	17,2	133	2570	14,3	50
STYLO PC 5P5 7030.100-1M		2540	19,1	132	2842	16	50
STYLO PC 5P5 7030.120-1M		3020	22,9	131	3377	19,3	50
STYLO PC 5P5 7030.140-1M		3500	26,8	130	3901	22,7	50
STYLO PC 5P5 7030.160-1M		3950	30,8	128	4413	26,1	50
STYLO PC 5P5 7030.180-1M		4370	34,8	125	4913	29,6	50
STYLO PC 5P5 7030.200-1M		4750	38,8	122	5402	33,1	50
STYLO PC 5P5 7030.040-2M		2130	16	133	2332	12,4	50
STYLO PC 5P5 7030.050-2M		2620	19,5	134	2905	15,6	50
STYLO PC 5P5 7030.060-2M		3100	23	134	3472	18,8	50
STYLO PC 5P5 7030.070-2M		3590	26,6	134	4034	22	50
STYLO PC 5P5 7030.080-2M		4090	30,1	135	4589	25,3	50
STYLO PC 5P5 7030.090-2M		4580	33,8	135	5139	28,6	50
STYLO PC 5P5 7030.100-2M		5070	37,4	135	5683	31,9	50
STYLO PC 5P5 7030.120-2M		6030	44,8	134	6754	38,6	50
STYLO PC 5P5 7030.140-2M		6970	52,3	133	7801	45,4	50
STYLO PC 5P5 7030.160-2M		7850	59,9	131	8825	52,2	50
STYLO PC 5P5 7030.180-2M		8680	67,7	128	9826	59,1	50
STYLO PC 5P5 7030.200-2M		9430	75,6	124	10803	66,1	50
STYLO PC 5P5 7030.040-3M		3200	23,3	137	3497	18,5	50
STYLO PC 5P5 7030.050-3M		3930	28,5	137	4357	23,3	50
STYLO PC 5P5 7030.060-3M		4670	33,8	138	5208	28,2	50
STYLO PC 5P5 7030.070-3M		5410	39	138	6050	33,1	50
STYLO PC 5P5 7030.080-3M		6150	44,2	139	6884	38	50
STYLO PC 5P5 7030.090-3M		6880	49,5	138	7709	42,9	50
STYLO PC 5P5 7030.100-3M		7600	54,8	138	8525	47,9	50
STYLO PC 5P5 7030.120-3M		9030	65,6	137	10131	57,9	50
STYLO PC 5P5 7030.140-3M	STE-M	10410	76,7	135	11702	68	50
STYLO PC 5P5 7030.160-3M	STU-M	11720	88,2	132	13238	78,3	50
STYLO PC 5P5 7030.180-3M	SV	12940	100	129	14739	88,7	50
STYLO PC 5P5 7030.200-3M	STW	14070	113	124	16205	99,2	35
STYLO PC 5P5 7030.040-4M		4250	30	141	4663	24,7	50
STYLO PC 5P5 7030.050-4M		5280	36,6	144	5809	31,1	50
STYLO PC 5P5 7030.060-4M		6290	43,4	144	6944	37,6	50
STYLO PC 5P5 7030.070-4M		7280	50,4	144	8067	44,1	50
STYLO PC 5P5 7030.080-4M		8250	57,4	143	9179	50,6	50
STYLO PC 5P5 7030.090-4M		9200	64,7	142	10278	57,2	50
STYLO PC 5P5 7030.100-4M		10130	72	140	11367	63,8	50
STYLO PC 5P5 7030.120-4M		11950	86,9	137	13508	77,2	50
STYLO PC 5P5 7030.140-4M		13700	102	134	15602	90,7	50
STYLO PC 5P5 7030.160-4M		15390	117	131	17650	104	50
STYLO PC 5P5 7030.180-4M		17030	132	129	19652	118	35
STYLO PC 5P5 7030.200-4M		18630	147	126	21606	132	35
STYLO PC 5P5 7030.060-5M		7850	53,4	147	8680	47	50
STYLO PC 5P5 7030.070-5M		9090	62,2	146	10084	55,1	50
STYLO PC 5P5 7030.080-5M		10320	71	145	11473	63,3	50
STYLO PC 5P5 7030.090-5M		11520	79,7	144	12848	71,5	50
STYLO PC 5P5 7030.100-5M		12700	88,6	143	14208	79,8	50
STYLO PC 5P5 7030.120-5M		15000	107	140	16885	96,5	50
STYLO PC 5P5 7030.140-5M		17220	125	137	19503	113	50
STYLO PC 5P5 7030.160-5M		19370	144	134	22063	130	35
STYLO PC 5P5 7030.180-5M		21440	164	130	24565	148	35
STYLO PC 5P5 7030.060-6M		9420	63,9	147	10416	56,4	50
STYLO PC 5P5 7030.070-6M		10910	74,3	146	12101	66,1	50
STYLO PC 5P5 7030.080-6M		12370	84,8	145	13768	75,9	50
STYLO PC 5P5 7030.090-6M		13810	95,4	144	15418	85,8	50
STYLO PC 5P5 7030.100-6M		15220	106	143	17050	95,7	50
STYLO PC 5P5 7030.120-6M		17950	128	140	20262	116	50
STYLO PC 5P5 7030.140-6M		20590	150	137	23404	136	50
STYLO PC 5P5 7030.160-6M		23120	173	133	26476	157	35
STYLO PC 5P5 7030.180-6M		25550	197	129	29478	177	35
STYLO PC 5P5 7030.060-7M		10960	74,4	147	12152	65,8	50
STYLO PC 5P5 7030.070-7M		12700	87	145	14118	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7030.080-7M		14430	99,6	144	16063	88,6	50
STYLO PC 5P5 7030.090-7M		16140	112	144	17987	100	50
STYLO PC 5P5 7030.100-7M		17820	125	142	19891	112	50
STYLO PC 5P5 7030.120-7M		21120	151	139	23639	135	50
STYLO PC 5P5 7030.140-7M		24310	177	137	27304	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 5P5 2700K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7027.040-1M		1000	8,5	117	1116	6,2	50
STYLO PC 5P5 7027.050-1M		1230	10,2	120	1391	7,8	50
STYLO PC 5P5 7027.060-1M		1460	11,9	122	1662	9,4	50
STYLO PC 5P5 7027.070-1M		1690	13,6	124	1931	11	50
STYLO PC 5P5 7027.080-1M		1920	15,4	124	2197	12,7	50
STYLO PC 5P5 7027.090-1M		2150	17,2	125	2460	14,3	50
STYLO PC 5P5 7027.100-1M		2380	19,1	124	2721	16	50
STYLO PC 5P5 7027.120-1M		2830	22,9	123	3233	19,3	50
STYLO PC 5P5 7027.140-1M		3270	26,8	122	3735	22,7	50
STYLO PC 5P5 7027.160-1M		3690	30,8	119	4225	26,1	50
STYLO PC 5P5 7027.180-1M		4080	34,8	117	4704	29,6	50
STYLO PC 5P5 7027.200-1M		4440	38,8	114	5172	33,1	50
STYLO PC 5P5 7027.040-2M		2000	16	125	2232	12,4	50
STYLO PC 5P5 7027.050-2M		2450	19,5	125	2781	15,6	50
STYLO PC 5P5 7027.060-2M		2900	23	126	3324	18,8	50
STYLO PC 5P5 7027.070-2M		3360	26,6	126	3862	22	50
STYLO PC 5P5 7027.080-2M		3820	30,1	126	4394	25,3	50
STYLO PC 5P5 7027.090-2M		4280	33,8	126	4921	28,6	50
STYLO PC 5P5 7027.100-2M		4730	37,4	126	5441	31,9	50
STYLO PC 5P5 7027.120-2M		5630	44,8	125	6466	38,6	50
STYLO PC 5P5 7027.140-2M		6510	52,3	124	7469	45,4	50
STYLO PC 5P5 7027.160-2M		7340	59,9	122	8450	52,2	50
STYLO PC 5P5 7027.180-2M		8110	67,7	119	9408	59,1	50
STYLO PC 5P5 7027.200-2M		8810	75,6	116	10344	66,1	50
STYLO PC 5P5 7027.040-3M		2990	23,3	128	3348	18,5	50
STYLO PC 5P5 7027.050-3M		3680	28,5	129	4172	23,3	50
STYLO PC 5P5 7027.060-3M		4370	33,8	129	4986	28,2	50
STYLO PC 5P5 7027.070-3M		5060	39	129	5793	33,1	50
STYLO PC 5P5 7027.080-3M		5750	44,2	130	6591	38	50
STYLO PC 5P5 7027.090-3M		6430	49,5	129	7381	42,9	50
STYLO PC 5P5 7027.100-3M		7110	54,8	129	8162	47,9	50
STYLO PC 5P5 7027.120-3M		8440	65,6	128	9700	57,9	50
STYLO PC 5P5 7027.140-3M	S05	9730	76,7	126	11204	68	50
STYLO PC 5P5 7027.160-3M	S07	10950	88,2	124	12674	78,3	50
STYLO PC 5P5 7027.180-3M	STA	12100	100	121	14112	88,7	50
STYLO PC 5P5 7027.200-3M	STA1	13150	113	116	15515	99,2	35
STYLO PC 5P5 7027.040-4M	STE-S	3970	30	132	4465	24,7	50
STYLO PC 5P5 7027.050-4M	STU-S	4930	36,6	134	5562	31,1	50
STYLO PC 5P5 7027.060-4M		5880	43,4	135	6649	37,6	50
STYLO PC 5P5 7027.070-4M		6800	50,4	134	7724	44,1	50
STYLO PC 5P5 7027.080-4M		7710	57,4	134	8788	50,6	50
STYLO PC 5P5 7027.090-4M		8600	64,7	132	9841	57,2	50
STYLO PC 5P5 7027.100-4M		9470	72	131	10883	63,8	50
STYLO PC 5P5 7027.120-4M		11160	86,9	128	12933	77,2	50
STYLO PC 5P5 7027.140-4M		12800	102	125	14938	90,7	50
STYLO PC 5P5 7027.160-4M		14380	117	122	16899	104	50
STYLO PC 5P5 7027.180-4M		15910	132	120	18816	118	35
STYLO PC 5P5 7027.200-4M		17410	147	118	20687	132	35
STYLO PC 5P5 7027.060-5M		7340	53,4	137	8311	47	50
STYLO PC 5P5 7027.070-5M		8500	62,2	136	9655	55,1	50
STYLO PC 5P5 7027.080-5M		9650	71	135	10985	63,3	50
STYLO PC 5P5 7027.090-5M		10770	79,7	135	12301	71,5	50
STYLO PC 5P5 7027.100-5M		11870	88,6	133	13604	79,8	50
STYLO PC 5P5 7027.120-5M		14020	107	131	16166	96,5	50
STYLO PC 5P5 7027.140-5M		16090	125	128	18673	113	50
STYLO PC 5P5 7027.160-5M		18100	144	125	21124	130	35
STYLO PC 5P5 7027.180-5M		20040	164	122	23519	148	35
STYLO PC 5P5 7027.060-6M		8800	63,9	137	9973	56,4	50
STYLO PC 5P5 7027.070-6M		10190	74,3	137	11586	66,1	50
STYLO PC 5P5 7027.080-6M		11560	84,8	136	13182	75,9	50
STYLO PC 5P5 7027.090-6M		12900	95,4	135	14762	85,8	50
STYLO PC 5P5 7027.100-6M		14220	106	134	16324	95,7	50
STYLO PC 5P5 7027.120-6M		16780	128	131	19399	116	50
STYLO PC 5P5 7027.140-6M		19240	150	128	22408	136	50
STYLO PC 5P5 7027.160-6M		21610	173	124	25349	157	35
STYLO PC 5P5 7027.180-6M		23890	197	121	28223	177	35
STYLO PC 5P5 7027.060-7M		10240	74,4	137	11635	65,8	50
STYLO PC 5P5 7027.070-7M		11870	87	136	13517	77,2	50
STYLO PC 5P5 7027.080-7M		13480	99,6	135	15379	88,6	50
STYLO PC 5P5 7027.090-7M		15080	112	134	17222	100	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7027.100-7M		16660	125	133	19045	112	50
STYLO PC 5P5 7027.120-7M		19750	151	130	22633	135	50
STYLO PC 5P5 7027.140-7M		22730	177	128	26142	159	50
STYLO PC 5P5 7027.040-1M		1030	8,5	121	1116	6,2	50
STYLO PC 5P5 7027.050-1M		1260	10,2	123	1391	7,8	50
STYLO PC 5P5 7027.060-1M		1490	11,9	125	1662	9,4	50
STYLO PC 5P5 7027.070-1M		1720	13,6	126	1931	11	50
STYLO PC 5P5 7027.080-1M		1960	15,4	127	2197	12,7	50
STYLO PC 5P5 7027.090-1M		2190	17,2	127	2460	14,3	50
STYLO PC 5P5 7027.100-1M		2430	19,1	127	2721	16	50
STYLO PC 5P5 7027.120-1M		2900	22,9	126	3233	19,3	50
STYLO PC 5P5 7027.140-1M		3350	26,8	125	3735	22,7	50
STYLO PC 5P5 7027.160-1M		3780	30,8	122	4225	26,1	50
STYLO PC 5P5 7027.180-1M		4180	34,8	120	4704	29,6	50
STYLO PC 5P5 7027.200-1M		4550	38,8	117	5172	33,1	50
STYLO PC 5P5 7027.040-2M		2040	16	127	2232	12,4	50
STYLO PC 5P5 7027.050-2M		2500	19,5	128	2781	15,6	50
STYLO PC 5P5 7027.060-2M		2970	23	129	3324	18,8	50
STYLO PC 5P5 7027.070-2M		3440	26,6	129	3862	22	50
STYLO PC 5P5 7027.080-2M		3910	30,1	129	4394	25,3	50
STYLO PC 5P5 7027.090-2M		4380	33,8	129	4921	28,6	50
STYLO PC 5P5 7027.100-2M		4850	37,4	129	5441	31,9	50
STYLO PC 5P5 7027.120-2M		5780	44,8	129	6466	38,6	50
STYLO PC 5P5 7027.140-2M		6670	52,3	127	7469	45,4	50
STYLO PC 5P5 7027.160-2M		7520	59,9	125	8450	52,2	50
STYLO PC 5P5 7027.180-2M		8310	67,7	122	9408	59,1	50
STYLO PC 5P5 7027.200-2M		9030	75,6	119	10344	66,1	50
STYLO PC 5P5 7027.040-3M		3060	23,3	131	3348	18,5	50
STYLO PC 5P5 7027.050-3M		3770	28,5	132	4172	23,3	50
STYLO PC 5P5 7027.060-3M		4470	33,8	132	4986	28,2	50
STYLO PC 5P5 7027.070-3M		5180	39	132	5793	33,1	50
STYLO PC 5P5 7027.080-3M		5880	44,2	133	6591	38	50
STYLO PC 5P5 7027.090-3M		6590	49,5	133	7381	42,9	50
STYLO PC 5P5 7027.100-3M		7280	54,8	132	8162	47,9	50
STYLO PC 5P5 7027.120-3M		8650	65,6	131	9700	57,9	50
STYLO PC 5P5 7027.140-3M	STE-M	9960	76,7	129	11204	68	50
STYLO PC 5P5 7027.160-3M	STU-M	11220	88,2	127	12674	78,3	50
STYLO PC 5P5 7027.180-3M	SV	12390	100	123	14112	88,7	50
STYLO PC 5P5 7027.200-3M	STW	13470	113	119	15515	99,2	35
STYLO PC 5P5 7027.040-4M		4070	30	135	4465	24,7	50
STYLO PC 5P5 7027.050-4M		5060	36,6	138	5562	31,1	50
STYLO PC 5P5 7027.060-4M		6020	43,4	138	6649	37,6	50
STYLO PC 5P5 7027.070-4M		6970	50,4	138	7724	44,1	50
STYLO PC 5P5 7027.080-4M		7900	57,4	137	8788	50,6	50
STYLO PC 5P5 7027.090-4M		8810	64,7	136	9841	57,2	50
STYLO PC 5P5 7027.100-4M		9700	72	134	10883	63,8	50
STYLO PC 5P5 7027.120-4M		11440	86,9	131	12933	77,2	50
STYLO PC 5P5 7027.140-4M		13110	102	128	14938	90,7	50
STYLO PC 5P5 7027.160-4M		14730	117	125	16899	104	50
STYLO PC 5P5 7027.180-4M		16310	132	123	18816	118	35
STYLO PC 5P5 7027.200-4M		17840	147	121	20687	132	35
STYLO PC 5P5 7027.060-5M		7520	53,4	140	8311	47	50
STYLO PC 5P5 7027.070-5M		8710	62,2	140	9655	55,1	50
STYLO PC 5P5 7027.080-5M		9880	71	139	10985	63,3	50
STYLO PC 5P5 7027.090-5M		11030	79,7	138	12301	71,5	50
STYLO PC 5P5 7027.100-5M		12160	88,6	137	13604	79,8	50
STYLO PC 5P5 7027.120-5M		14360	107	134	16166	96,5	50
STYLO PC 5P5 7027.140-5M		16490	125	131	18673	113	50
STYLO PC 5P5 7027.160-5M		18540	144	128	21124	130	35
STYLO PC 5P5 7027.180-5M		20530	164	125	23519	148	35
STYLO PC 5P5 7027.060-6M		9020	63,9	141	9973	56,4	50
STYLO PC 5P5 7027.070-6M		10450	74,3	140	11586	66,1	50
STYLO PC 5P5 7027.080-6M		11850	84,8	139	13182	75,9	50
STYLO PC 5P5 7027.090-6M		13220	95,4	138	14762	85,8	50
STYLO PC 5P5 7027.100-6M		14570	106	137	16324	95,7	50
STYLO PC 5P5 7027.120-6M		17190	128	134	19399	116	50
STYLO PC 5P5 7027.140-6M		19710	150	131	22408	136	50
STYLO PC 5P5 7027.160-6M		22130	173	127	25349	157	35
STYLO PC 5P5 7027.180-6M		24470	197	124	28223	177	35
STYLO PC 5P5 7027.060-7M		10490	74,4	140	11635	65,8	50
STYLO PC 5P5 7027.070-7M		12160	87	139	13517	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7027.080-7M		13810	99,6	138	15379	88,6	50
STYLO PC 5P5 7027.090-7M		15450	112	137	17222	100	50
STYLO PC 5P5 7027.100-7M		17060	125	136	19045	112	50
STYLO PC 5P5 7027.120-7M		20220	151	133	22633	135	50
STYLO PC 5P5 7027.140-7M		23270	177	131	26142	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 5P5 2200K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7022.040-1M		900	8,5	105	1005	6,2	50
STYLO PC 5P5 7022.050-1M		1100	10,2	107	1251	7,8	50
STYLO PC 5P5 7022.060-1M		1310	11,9	110	1496	9,4	50
STYLO PC 5P5 7022.070-1M		1520	13,6	111	1738	11	50
STYLO PC 5P5 7022.080-1M		1720	15,4	111	1977	12,7	50
STYLO PC 5P5 7022.090-1M		1930	17,2	112	2214	14,3	50
STYLO PC 5P5 7022.100-1M		2140	19,1	112	2449	16	50
STYLO PC 5P5 7022.120-1M		2550	22,9	111	2910	19,3	50
STYLO PC 5P5 7022.140-1M		2940	26,8	109	3361	22,7	50
STYLO PC 5P5 7022.160-1M		3320	30,8	107	3802	26,1	50
STYLO PC 5P5 7022.180-1M		3670	34,8	105	4233	29,6	50
STYLO PC 5P5 7022.200-1M		3990	38,8	102	4655	33,1	50
STYLO PC 5P5 7022.040-2M		1800	16	112	2009	12,4	50
STYLO PC 5P5 7022.050-2M		2200	19,5	112	2503	15,6	50
STYLO PC 5P5 7022.060-2M		2610	23	113	2992	18,8	50
STYLO PC 5P5 7022.070-2M		3020	26,6	113	3476	22	50
STYLO PC 5P5 7022.080-2M		3440	30,1	114	3955	25,3	50
STYLO PC 5P5 7022.090-2M		3850	33,8	113	4428	28,6	50
STYLO PC 5P5 7022.100-2M		4260	37,4	113	4897	31,9	50
STYLO PC 5P5 7022.120-2M		5070	44,8	113	5820	38,6	50
STYLO PC 5P5 7022.140-2M		5860	52,3	112	6722	45,4	50
STYLO PC 5P5 7022.160-2M		6600	59,9	110	7605	52,2	50
STYLO PC 5P5 7022.180-2M		7300	67,7	107	8467	59,1	50
STYLO PC 5P5 7022.200-2M		7930	75,6	104	9309	66,1	50
STYLO PC 5P5 7022.040-3M		2690	23,3	115	3014	18,5	50
STYLO PC 5P5 7022.050-3M		3310	28,5	116	3754	23,3	50
STYLO PC 5P5 7022.060-3M		3930	33,8	116	4488	28,2	50
STYLO PC 5P5 7022.070-3M		4550	39	116	5214	33,1	50
STYLO PC 5P5 7022.080-3M		5170	44,2	116	5932	38	50
STYLO PC 5P5 7022.090-3M		5790	49,5	116	6643	42,9	50
STYLO PC 5P5 7022.100-3M		6400	54,8	116	7346	47,9	50
STYLO PC 5P5 7022.120-3M		7600	65,6	115	8730	57,9	50
STYLO PC 5P5 7022.140-3M	S05	8760	76,7	114	10083	68	50
STYLO PC 5P5 7022.160-3M	S07	9860	88,2	111	11407	78,3	50
STYLO PC 5P5 7022.180-3M	STA	10890	100	108	12700	88,7	50
STYLO PC 5P5 7022.200-3M	STA1	11830	113	104	13964	99,2	35
STYLO PC 5P5 7022.040-4M	STE-S	3570	30	119	4018	24,7	50
STYLO PC 5P5 7022.050-4M	STU-S	4440	36,6	121	5006	31,1	50
STYLO PC 5P5 7022.060-4M		5290	43,4	121	5984	37,6	50
STYLO PC 5P5 7022.070-4M		6120	50,4	121	6952	44,1	50
STYLO PC 5P5 7022.080-4M		6940	57,4	120	7909	50,6	50
STYLO PC 5P5 7022.090-4M		7740	64,7	119	8857	57,2	50
STYLO PC 5P5 7022.100-4M		8520	72	118	9795	63,8	50
STYLO PC 5P5 7022.120-4M		10050	86,9	115	11640	77,2	50
STYLO PC 5P5 7022.140-4M		11520	102	112	13445	90,7	50
STYLO PC 5P5 7022.160-4M		12940	117	110	15209	104	50
STYLO PC 5P5 7022.180-4M		14320	132	108	16934	118	35
STYLO PC 5P5 7022.200-4M		15670	147	106	18618	132	35
STYLO PC 5P5 7022.060-5M		6610	53,4	123	7480	47	50
STYLO PC 5P5 7022.070-5M		7650	62,2	122	8689	55,1	50
STYLO PC 5P5 7022.080-5M		8680	71	122	9887	63,3	50
STYLO PC 5P5 7022.090-5M		9690	79,7	121	11071	71,5	50
STYLO PC 5P5 7022.100-5M		10680	88,6	120	12243	79,8	50
STYLO PC 5P5 7022.120-5M		12620	107	117	14550	96,5	50
STYLO PC 5P5 7022.140-5M		14480	125	115	16806	113	50
STYLO PC 5P5 7022.160-5M		16290	144	113	19012	130	35
STYLO PC 5P5 7022.180-5M		18030	164	109	21167	148	35
STYLO PC 5P5 7022.060-6M		7920	63,9	123	8976	56,4	50
STYLO PC 5P5 7022.070-6M		9170	74,3	123	10427	66,1	50
STYLO PC 5P5 7022.080-6M		10400	84,8	122	11864	75,9	50
STYLO PC 5P5 7022.090-6M		11610	95,4	121	13285	85,8	50
STYLO PC 5P5 7022.100-6M		12800	106	120	14692	95,7	50
STYLO PC 5P5 7022.120-6M		15100	128	117	17459	116	50
STYLO PC 5P5 7022.140-6M		17320	150	115	20167	136	50
STYLO PC 5P5 7022.160-6M		19450	173	112	22814	157	35
STYLO PC 5P5 7022.180-6M		21500	197	109	25401	177	35
STYLO PC 5P5 7022.060-7M		9210	74,4	123	10472	65,8	50
STYLO PC 5P5 7022.070-7M		10680	87	122	12165	77,2	50
STYLO PC 5P5 7022.080-7M		12140	99,6	121	13841	88,6	50
STYLO PC 5P5 7022.090-7M		13570	112	121	15500	100	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7022.100-7M		14990	125	119	17140	112	50
STYLO PC 5P5 7022.120-7M		17770	151	117	20369	135	50
STYLO PC 5P5 7022.140-7M		20450	177	115	23528	159	50
STYLO PC 5P5 7022.040-1M		920	8,5	108	1005	6,2	50
STYLO PC 5P5 7022.050-1M		1130	10,2	110	1251	7,8	50
STYLO PC 5P5 7022.060-1M		1340	11,9	112	1496	9,4	50
STYLO PC 5P5 7022.070-1M		1550	13,6	113	1738	11	50
STYLO PC 5P5 7022.080-1M		1760	15,4	114	1977	12,7	50
STYLO PC 5P5 7022.090-1M		1970	17,2	114	2214	14,3	50
STYLO PC 5P5 7022.100-1M		2190	19,1	114	2449	16	50
STYLO PC 5P5 7022.120-1M		2610	22,9	113	2910	19,3	50
STYLO PC 5P5 7022.140-1M		3010	26,8	112	3361	22,7	50
STYLO PC 5P5 7022.160-1M		3400	30,8	110	3802	26,1	50
STYLO PC 5P5 7022.180-1M		3760	34,8	108	4233	29,6	50
STYLO PC 5P5 7022.200-1M		4090	38,8	105	4655	33,1	50
STYLO PC 5P5 7022.040-2M		1840	16	115	2009	12,4	50
STYLO PC 5P5 7022.050-2M		2250	19,5	115	2503	15,6	50
STYLO PC 5P5 7022.060-2M		2670	23	116	2992	18,8	50
STYLO PC 5P5 7022.070-2M		3100	26,6	116	3476	22	50
STYLO PC 5P5 7022.080-2M		3520	30,1	116	3955	25,3	50
STYLO PC 5P5 7022.090-2M		3940	33,8	116	4428	28,6	50
STYLO PC 5P5 7022.100-2M		4370	37,4	116	4897	31,9	50
STYLO PC 5P5 7022.120-2M		5200	44,8	116	5820	38,6	50
STYLO PC 5P5 7022.140-2M		6000	52,3	114	6722	45,4	50
STYLO PC 5P5 7022.160-2M		6770	59,9	113	7605	52,2	50
STYLO PC 5P5 7022.180-2M		7480	67,7	110	8467	59,1	50
STYLO PC 5P5 7022.200-2M		8120	75,6	107	9309	66,1	50
STYLO PC 5P5 7022.040-3M		2750	23,3	118	3014	18,5	50
STYLO PC 5P5 7022.050-3M		3390	28,5	118	3754	23,3	50
STYLO PC 5P5 7022.060-3M		4030	33,8	119	4488	28,2	50
STYLO PC 5P5 7022.070-3M		4660	39	119	5214	33,1	50
STYLO PC 5P5 7022.080-3M		5300	44,2	119	5932	38	50
STYLO PC 5P5 7022.090-3M		5930	49,5	119	6643	42,9	50
STYLO PC 5P5 7022.100-3M		6550	54,8	119	7346	47,9	50
STYLO PC 5P5 7022.120-3M		7780	65,6	118	8730	57,9	50
STYLO PC 5P5 7022.140-3M	STE-M	8970	76,7	116	10083	68	50
STYLO PC 5P5 7022.160-3M	STU-M	10100	88,2	114	11407	78,3	50
STYLO PC 5P5 7022.180-3M	SV	11150	100	111	12700	88,7	50
STYLO PC 5P5 7022.200-3M	STW	12130	113	107	13964	99,2	35
STYLO PC 5P5 7022.040-4M		3660	30	122	4018	24,7	50
STYLO PC 5P5 7022.050-4M		4550	36,6	124	5006	31,1	50
STYLO PC 5P5 7022.060-4M		5420	43,4	124	5984	37,6	50
STYLO PC 5P5 7022.070-4M		6270	50,4	124	6952	44,1	50
STYLO PC 5P5 7022.080-4M		7110	57,4	123	7909	50,6	50
STYLO PC 5P5 7022.090-4M		7930	64,7	122	8857	57,2	50
STYLO PC 5P5 7022.100-4M		8730	72	121	9795	63,8	50
STYLO PC 5P5 7022.120-4M		10290	86,9	118	11640	77,2	50
STYLO PC 5P5 7022.140-4M		11800	102	115	13445	90,7	50
STYLO PC 5P5 7022.160-4M		13260	117	113	15209	104	50
STYLO PC 5P5 7022.180-4M		14680	132	111	16934	118	35
STYLO PC 5P5 7022.200-4M		16050	147	109	18618	132	35
STYLO PC 5P5 7022.060-5M		6760	53,4	126	7480	47	50
STYLO PC 5P5 7022.070-5M		7840	62,2	126	8689	55,1	50
STYLO PC 5P5 7022.080-5M		8890	71	125	9887	63,3	50
STYLO PC 5P5 7022.090-5M		9930	79,7	124	11071	71,5	50
STYLO PC 5P5 7022.100-5M		10940	88,6	123	12243	79,8	50
STYLO PC 5P5 7022.120-5M		12930	107	120	14550	96,5	50
STYLO PC 5P5 7022.140-5M		14840	125	118	16806	113	50
STYLO PC 5P5 7022.160-5M		16690	144	115	19012	130	35
STYLO PC 5P5 7022.180-5M		18470	164	112	21167	148	35
STYLO PC 5P5 7022.060-6M		8120	63,9	127	8976	56,4	50
STYLO PC 5P5 7022.070-6M		9400	74,3	126	10427	66,1	50
STYLO PC 5P5 7022.080-6M		10660	84,8	125	11864	75,9	50
STYLO PC 5P5 7022.090-6M		11900	95,4	124	13285	85,8	50
STYLO PC 5P5 7022.100-6M		13110	106	123	14692	95,7	50
STYLO PC 5P5 7022.120-6M		15470	128	120	17459	116	50
STYLO PC 5P5 7022.140-6M		17740	150	118	20167	136	50
STYLO PC 5P5 7022.160-6M		19920	173	115	22814	157	35
STYLO PC 5P5 7022.180-6M		22020	197	111	25401	177	35
STYLO PC 5P5 7022.060-7M		9440	74,4	126	10472	65,8	50
STYLO PC 5P5 7022.070-7M		10940	87	125	12165	77,2	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 5P5 7022.080-7M		12430	99,6	124	13841	88,6	50
STYLO PC 5P5 7022.090-7M		13900	112	124	15500	100	50
STYLO PC 5P5 7022.100-7M		15360	125	122	17140	112	50
STYLO PC 5P5 7022.120-7M		18200	151	120	20369	135	50
STYLO PC 5P5 7022.140-7M		20950	177	118	23528	159	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 4P4 4000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7040.050-1M		1080	8,3	130	1236	6,2	50
STYLO PC 4P4 7040.060-1M		1290	9,6	134	1477	7,5	50
STYLO PC 4P4 7040.070-1M		1500	11	136	1716	8,8	50
STYLO PC 4P4 7040.080-1M		1700	12,4	137	1953	10,1	50
STYLO PC 4P4 7040.090-1M		1910	13,8	138	2187	11,4	50
STYLO PC 4P4 7040.100-1M		2110	15,3	137	2418	12,8	50
STYLO PC 4P4 7040.120-1M		2510	18,4	136	2874	15,4	50
STYLO PC 4P4 7040.140-1M		2900	21,5	134	3320	18,1	50
STYLO PC 4P4 7040.160-1M		3270	24,7	132	3755	20,9	50
STYLO PC 4P4 7040.180-1M		3620	27,9	129	4181	23,6	50
STYLO PC 4P4 7040.200-1M		3940	31	127	4597	26,4	50
STYLO PC 4P4 7040.050-2M		2170	16	135	2472	12,5	50
STYLO PC 4P4 7040.060-2M		2570	18,7	137	2955	15	50
STYLO PC 4P4 7040.070-2M		2980	21,5	138	3433	17,6	50
STYLO PC 4P4 7040.080-2M		3390	24,3	139	3906	20,3	50
STYLO PC 4P4 7040.090-2M		3800	27,1	140	4374	22,9	50
STYLO PC 4P4 7040.100-2M		4200	30	140	4837	25,5	50
STYLO PC 4P4 7040.120-2M		5000	35,9	139	5748	30,9	50
STYLO PC 4P4 7040.140-2M		5770	41,9	137	6639	36,3	50
STYLO PC 4P4 7040.160-2M		6510	48	135	7511	41,8	50
STYLO PC 4P4 7040.180-2M		7190	54,2	132	8362	47,3	50
STYLO PC 4P4 7040.200-2M		7820	60,5	129	9194	52,9	50
STYLO PC 4P4 7040.050-3M		3260	23,3	139	3708	18,7	50
STYLO PC 4P4 7040.060-3M		3880	27,4	141	4432	22,6	50
STYLO PC 4P4 7040.070-3M		4490	31,5	142	5149	26,5	50
STYLO PC 4P4 7040.080-3M		5100	35,6	143	5859	30,4	50
STYLO PC 4P4 7040.090-3M		5710	39,8	143	6561	34,3	50
STYLO PC 4P4 7040.100-3M		6310	44	143	7255	38,3	50
STYLO PC 4P4 7040.120-3M		7490	52,6	142	8622	46,3	50
STYLO PC 4P4 7040.140-3M		8630	61,5	140	9959	54,4	50
STYLO PC 4P4 7040.160-3M	S05	9720	70,7	137	11266	62,6	50
STYLO PC 4P4 7040.180-3M	S07	10730	80,3	133	12544	70,9	50
STYLO PC 4P4 7040.200-3M	STE-S	11670	90,4	129	13791	79,3	35
STYLO PC 4P4 7040.050-4M		4370	30	145	4944	24,9	50
STYLO PC 4P4 7040.060-4M		5210	35,3	147	5910	30,1	50
STYLO PC 4P4 7040.070-4M		6030	40,7	148	6866	35,3	50
STYLO PC 4P4 7040.080-4M		6840	46,3	147	7812	40,5	50
STYLO PC 4P4 7040.090-4M		7630	52	146	8748	45,8	50
STYLO PC 4P4 7040.100-4M		8400	57,8	145	9674	51,1	50
STYLO PC 4P4 7040.120-4M		9910	69,7	142	11496	61,7	50
STYLO PC 4P4 7040.140-4M		11360	81,8	138	13279	72,6	50
STYLO PC 4P4 7040.160-4M		12770	94	135	15022	83,5	50
STYLO PC 4P4 7040.180-4M		14130	106	133	16725	94,6	35
STYLO PC 4P4 7040.200-4M		15450	118	130	18389	106	35
STYLO PC 4P4 7040.080-5M		8550	57,2	149	9765	50,6	50
STYLO PC 4P4 7040.090-5M		9550	64,1	148	10934	57,2	50
STYLO PC 4P4 7040.100-5M		10530	71,1	148	12092	63,8	50
STYLO PC 4P4 7040.120-5M		12440	85,3	145	14370	77,2	50
STYLO PC 4P4 7040.140-5M		14280	100	142	16598	90,7	50
STYLO PC 4P4 7040.160-5M		16060	115	139	18777	104	35
STYLO PC 4P4 7040.180-5M		17780	131	135	20906	118	35
STYLO PC 4P4 7040.080-6M		10260	68,4	150	11717	60,8	50
STYLO PC 4P4 7040.090-6M		11450	76,7	149	13121	68,6	50
STYLO PC 4P4 7040.100-6M		12620	85,1	148	14510	76,6	50
STYLO PC 4P4 7040.120-6M		14890	102	145	17244	92,6	50
STYLO PC 4P4 7040.140-6M		17070	120	142	19918	109	50
STYLO PC 4P4 7040.160-6M		19170	138	138	22532	125	35
STYLO PC 4P4 7040.180-6M		21190	158	134	25087	142	35
STYLO PC 4P4 7040.080-7M		11970	79,7	150	13670	70,9	50
STYLO PC 4P4 7040.090-7M		13380	89,8	148	15308	80,1	50
STYLO PC 4P4 7040.100-7M		14780	100	147	16929	89,4	50
STYLO PC 4P4 7040.120-7M		17520	121	144	20118	108	50
STYLO PC 4P4 7040.140-7M		20160	142	141	23238	127	50
STYLO PC 4P4 7040.050-1M		1100	8,3	132	1236	6,2	50
STYLO PC 4P4 7040.060-1M		1300	9,6	135	1477	7,5	50
STYLO PC 4P4 7040.070-1M	STA	1510	11	137	1716	8,8	50
STYLO PC 4P4 7040.080-1M	STA1	1710	12,4	137	1953	10,1	50
STYLO PC 4P4 7040.090-1M	STU-S	1920	13,8	139	2187	11,4	50
STYLO PC 4P4 7040.100-1M		2130	15,3	139	2418	12,8	50
STYLO PC 4P4 7040.120-1M		2540	18,4	138	2874	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7040.140-1M		2940	21,5	136	3320	18,1	50
STYLO PC 4P4 7040.160-1M		3320	24,7	134	3755	20,9	50
STYLO PC 4P4 7040.180-1M		3670	27,9	131	4181	23,6	50
STYLO PC 4P4 7040.200-1M		3990	31	128	4597	26,4	50
STYLO PC 4P4 7040.050-2M		2200	16	137	2472	12,5	50
STYLO PC 4P4 7040.060-2M		2610	18,7	139	2955	15	50
STYLO PC 4P4 7040.070-2M		3020	21,5	140	3433	17,6	50
STYLO PC 4P4 7040.080-2M		3440	24,3	141	3906	20,3	50
STYLO PC 4P4 7040.090-2M		3850	27,1	142	4374	22,9	50
STYLO PC 4P4 7040.100-2M		4260	30	142	4837	25,5	50
STYLO PC 4P4 7040.120-2M		5070	35,9	141	5748	30,9	50
STYLO PC 4P4 7040.140-2M		5850	41,9	139	6639	36,3	50
STYLO PC 4P4 7040.160-2M		6590	48	137	7511	41,8	50
STYLO PC 4P4 7040.180-2M		7290	54,2	134	8362	47,3	50
STYLO PC 4P4 7040.200-2M		7920	60,5	130	9194	52,9	50
STYLO PC 4P4 7040.050-3M		3300	23,3	141	3708	18,7	50
STYLO PC 4P4 7040.060-3M		3920	27,4	143	4432	22,6	50
STYLO PC 4P4 7040.070-3M		4550	31,5	144	5149	26,5	50
STYLO PC 4P4 7040.080-3M		5160	35,6	144	5859	30,4	50
STYLO PC 4P4 7040.090-3M		5780	39,8	145	6561	34,3	50
STYLO PC 4P4 7040.100-3M		6390	44	145	7255	38,3	50
STYLO PC 4P4 7040.120-3M		7590	52,6	144	8622	46,3	50
STYLO PC 4P4 7040.140-3M		8740	61,5	142	9959	54,4	50
STYLO PC 4P4 7040.160-3M		9840	70,7	139	11266	62,6	50
STYLO PC 4P4 7040.180-3M		10870	80,3	135	12544	70,9	50
STYLO PC 4P4 7040.200-3M		11810	90,4	130	13791	79,3	35
STYLO PC 4P4 7040.050-4M		4430	30	147	4944	24,9	50
STYLO PC 4P4 7040.060-4M		5280	35,3	149	5910	30,1	50
STYLO PC 4P4 7040.070-4M		6110	40,7	150	6866	35,3	50
STYLO PC 4P4 7040.080-4M		6930	46,3	149	7812	40,5	50
STYLO PC 4P4 7040.090-4M		7730	52	148	8748	45,8	50
STYLO PC 4P4 7040.100-4M		8510	57,8	147	9674	51,1	50
STYLO PC 4P4 7040.120-4M		10030	69,7	143	11496	61,7	50
STYLO PC 4P4 7040.140-4M		11500	81,8	140	13279	72,6	50
STYLO PC 4P4 7040.160-4M		12920	94	137	15022	83,5	50
STYLO PC 4P4 7040.180-4M		14300	106	134	16725	94,6	35
STYLO PC 4P4 7040.200-4M		15640	118	132	18389	106	35
STYLO PC 4P4 7040.080-5M		8660	57,2	151	9765	50,6	50
STYLO PC 4P4 7040.090-5M		9670	64,1	150	10934	57,2	50
STYLO PC 4P4 7040.100-5M		10660	71,1	149	12092	63,8	50
STYLO PC 4P4 7040.120-5M		12590	85,3	147	14370	77,2	50
STYLO PC 4P4 7040.140-5M		14460	100	144	16598	90,7	50
STYLO PC 4P4 7040.160-5M		16260	115	141	18777	104	35
STYLO PC 4P4 7040.180-5M		18010	131	137	20906	118	35
STYLO PC 4P4 7040.080-6M		10390	68,4	151	11717	60,8	50
STYLO PC 4P4 7040.090-6M		11600	76,7	151	13121	68,6	50
STYLO PC 4P4 7040.100-6M		12780	85,1	150	14510	76,6	50
STYLO PC 4P4 7040.120-6M		15070	102	147	17244	92,6	50
STYLO PC 4P4 7040.140-6M		17280	120	144	19918	109	50
STYLO PC 4P4 7040.160-6M		19400	138	140	22532	125	35
STYLO PC 4P4 7040.180-6M		21450	158	135	25087	142	35
STYLO PC 4P4 7040.080-7M		12120	79,7	152	13670	70,9	50
STYLO PC 4P4 7040.090-7M		13560	89,8	151	15308	80,1	50
STYLO PC 4P4 7040.100-7M		14970	100	149	16929	89,4	50
STYLO PC 4P4 7040.120-7M		17740	121	146	20118	108	50
STYLO PC 4P4 7040.140-7M		20410	142	143	23238	127	50
STYLO PC 4P4 7040.050-1M		1130	8,3	136	1236	6,2	50
STYLO PC 4P4 7040.060-1M		1340	9,6	139	1477	7,5	50
STYLO PC 4P4 7040.070-1M		1550	11	140	1716	8,8	50
STYLO PC 4P4 7040.080-1M		1770	12,4	142	1953	10,1	50
STYLO PC 4P4 7040.090-1M		1980	13,8	143	2187	11,4	50
STYLO PC 4P4 7040.100-1M		2190	15,3	143	2418	12,8	50
STYLO PC 4P4 7040.120-1M		2610	18,4	141	2874	15,4	50
STYLO PC 4P4 7040.140-1M		3010	21,5	140	3320	18,1	50
STYLO PC 4P4 7040.160-1M		3390	24,7	137	3755	20,9	50
STYLO PC 4P4 7040.180-1M		3750	27,9	134	4181	23,6	50
STYLO PC 4P4 7040.200-1M		4080	31	131	4597	26,4	50
STYLO PC 4P4 7040.050-2M		2250	16	140	2472	12,5	50
STYLO PC 4P4 7040.060-2M		2670	18,7	142	2955	15	50
STYLO PC 4P4 7040.070-2M		3090	21,5	143	3433	17,6	50
STYLO PC 4P4 7040.080-2M		3520	24,3	144	3906	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(4000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(4000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7040.090-2M		3940	27,1	145	4374	22,9	50
STYLO PC 4P4 7040.100-2M		4360	30	145	4837	25,5	50
STYLO PC 4P4 7040.120-2M		5190	35,9	144	5748	30,9	50
STYLO PC 4P4 7040.140-2M		5990	41,9	142	6639	36,3	50
STYLO PC 4P4 7040.160-2M		6750	48	140	7511	41,8	50
STYLO PC 4P4 7040.180-2M		7460	54,2	137	8362	47,3	50
STYLO PC 4P4 7040.200-2M		8110	60,5	134	9194	52,9	50
STYLO PC 4P4 7040.050-3M		3390	23,3	145	3708	18,7	50
STYLO PC 4P4 7040.060-3M		4030	27,4	147	4432	22,6	50
STYLO PC 4P4 7040.070-3M		4660	31,5	147	5149	26,5	50
STYLO PC 4P4 7040.080-3M		5300	35,6	148	5859	30,4	50
STYLO PC 4P4 7040.090-3M		5930	39,8	148	6561	34,3	50
STYLO PC 4P4 7040.100-3M		6550	44	148	7255	38,3	50
STYLO PC 4P4 7040.120-3M		7770	52,6	147	8622	46,3	50
STYLO PC 4P4 7040.140-3M		8950	61,5	145	9959	54,4	50
STYLO PC 4P4 7040.160-3M		10070	70,7	142	11266	62,6	50
STYLO PC 4P4 7040.180-3M		11130	80,3	138	12544	70,9	50
STYLO PC 4P4 7040.200-3M		12100	90,4	133	13791	79,3	35
STYLO PC 4P4 7040.050-4M		4540	30	151	4944	24,9	50
STYLO PC 4P4 7040.060-4M		5410	35,3	153	5910	30,1	50
STYLO PC 4P4 7040.070-4M		6270	40,7	154	6866	35,3	50
STYLO PC 4P4 7040.080-4M		7100	46,3	153	7812	40,5	50
STYLO PC 4P4 7040.090-4M		7920	52	152	8748	45,8	50
STYLO PC 4P4 7040.100-4M		8720	57,8	150	9674	51,1	50
STYLO PC 4P4 7040.120-4M		10280	69,7	147	11496	61,7	50
STYLO PC 4P4 7040.140-4M		11780	81,8	144	13279	72,6	50
STYLO PC 4P4 7040.160-4M		13240	94	140	15022	83,5	50
STYLO PC 4P4 7040.180-4M		14650	106	138	16725	94,6	35
STYLO PC 4P4 7040.200-4M		16030	118	135	18389	106	35
STYLO PC 4P4 7040.080-5M		8870	57,2	155	9765	50,6	50
STYLO PC 4P4 7040.090-5M		9910	64,1	154	10934	57,2	50
STYLO PC 4P4 7040.100-5M		10920	71,1	153	12092	63,8	50
STYLO PC 4P4 7040.120-5M		12900	85,3	151	14370	77,2	50
STYLO PC 4P4 7040.140-5M		14810	100	148	16598	90,7	50
STYLO PC 4P4 7040.160-5M		16660	115	144	18777	104	35
STYLO PC 4P4 7040.180-5M		18440	131	140	20906	118	35
STYLO PC 4P4 7040.080-6M		10640	68,4	155	11717	60,8	50
STYLO PC 4P4 7040.090-6M		11880	76,7	154	13121	68,6	50
STYLO PC 4P4 7040.100-6M		13090	85,1	153	14510	76,6	50
STYLO PC 4P4 7040.120-6M		15440	102	151	17244	92,6	50
STYLO PC 4P4 7040.140-6M		17710	120	147	19918	109	50
STYLO PC 4P4 7040.160-6M		19890	138	144	22532	125	35
STYLO PC 4P4 7040.180-6M		21980	158	139	25087	142	35
STYLO PC 4P4 7040.080-7M		12420	79,7	155	13670	70,9	50
STYLO PC 4P4 7040.090-7M		13890	89,8	154	15308	80,1	50
STYLO PC 4P4 7040.100-7M		15340	100	153	16929	89,4	50
STYLO PC 4P4 7040.120-7M		18180	121	150	20118	108	50
STYLO PC 4P4 7040.140-7M		20920	142	147	23238	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 4P4 3000K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7030.050-1M	STE-S	1020	8,3	122	1162	6,2	50
STYLO PC 4P4 7030.060-1M		1210	9,6	126	1389	7,5	50
STYLO PC 4P4 7030.070-1M		1410	11	128	1613	8,8	50
STYLO PC 4P4 7030.080-1M		1600	12,4	129	1836	10,1	50
STYLO PC 4P4 7030.090-1M		1790	13,8	129	2056	11,4	50
STYLO PC 4P4 7030.100-1M		1980	15,3	129	2273	12,8	50
STYLO PC 4P4 7030.120-1M		2360	18,4	128	2702	15,4	50
STYLO PC 4P4 7030.140-1M		2730	21,5	126	3120	18,1	50
STYLO PC 4P4 7030.160-1M		3070	24,7	124	3530	20,9	50
STYLO PC 4P4 7030.180-1M		3400	27,9	121	3930	23,6	50
STYLO PC 4P4 7030.200-1M		3700	31	119	4321	26,4	50
STYLO PC 4P4 7030.050-2M		2040	16	127	2324	12,5	50
STYLO PC 4P4 7030.060-2M		2420	18,7	129	2778	15	50
STYLO PC 4P4 7030.070-2M		2800	21,5	130	3227	17,6	50
STYLO PC 4P4 7030.080-2M		3190	24,3	131	3671	20,3	50
STYLO PC 4P4 7030.090-2M		3570	27,1	131	4111	22,9	50
STYLO PC 4P4 7030.100-2M		3950	30	131	4547	25,5	50
STYLO PC 4P4 7030.120-2M		4700	35,9	130	5403	30,9	50
STYLO PC 4P4 7030.140-2M		5420	41,9	129	6241	36,3	50
STYLO PC 4P4 7030.160-2M		6120	48	127	7060	41,8	50
STYLO PC 4P4 7030.180-2M		6760	54,2	124	7861	47,3	50
STYLO PC 4P4 7030.200-2M		7350	60,5	121	8643	52,9	50
STYLO PC 4P4 7030.050-3M		3070	23,3	131	3486	18,7	50
STYLO PC 4P4 7030.060-3M		3640	27,4	132	4166	22,6	50
STYLO PC 4P4 7030.070-3M		4220	31,5	133	4840	26,5	50
STYLO PC 4P4 7030.080-3M		4790	35,6	134	5507	30,4	50
STYLO PC 4P4 7030.090-3M		5370	39,8	134	6167	34,3	50
STYLO PC 4P4 7030.100-3M		5930	44	134	6820	38,3	50
STYLO PC 4P4 7030.120-3M		7040	52,6	133	8105	46,3	50
STYLO PC 4P4 7030.140-3M		8110	61,5	131	9361	54,4	50
STYLO PC 4P4 7030.160-3M		9130	70,7	129	10590	62,6	50
STYLO PC 4P4 7030.180-3M		10090	80,3	125	11791	70,9	50
STYLO PC 4P4 7030.200-3M		10970	90,4	121	12964	79,3	35
STYLO PC 4P4 7030.050-4M		4110	30	137	4648	24,9	50
STYLO PC 4P4 7030.060-4M		4900	35,3	138	5555	30,1	50
STYLO PC 4P4 7030.070-4M		5670	40,7	139	6454	35,3	50
STYLO PC 4P4 7030.080-4M		6430	46,3	138	7343	40,5	50
STYLO PC 4P4 7030.090-4M		7170	52	137	8223	45,8	50
STYLO PC 4P4 7030.100-4M		7900	57,8	136	9093	51,1	50
STYLO PC 4P4 7030.120-4M		9310	69,7	133	10806	61,7	50
STYLO PC 4P4 7030.140-4M		10680	81,8	130	12482	72,6	50
STYLO PC 4P4 7030.160-4M		12000	94	127	14120	83,5	50
STYLO PC 4P4 7030.180-4M		13280	106	125	15721	94,6	35
STYLO PC 4P4 7030.200-4M		14520	118	123	17285	106	35
STYLO PC 4P4 7030.080-5M		8040	57,2	140	9179	50,6	50
STYLO PC 4P4 7030.090-5M		8980	64,1	140	10278	57,2	50
STYLO PC 4P4 7030.100-5M		9900	71,1	139	11367	63,8	50
STYLO PC 4P4 7030.120-5M		11690	85,3	137	13508	77,2	50
STYLO PC 4P4 7030.140-5M		13420	100	134	15602	90,7	50
STYLO PC 4P4 7030.160-5M		15100	115	131	17650	104	35
STYLO PC 4P4 7030.180-5M		16710	131	127	19652	118	35
STYLO PC 4P4 7030.080-6M		9650	68,4	141	11014	60,8	50
STYLO PC 4P4 7030.090-6M		10770	76,7	140	12334	68,6	50
STYLO PC 4P4 7030.100-6M		11860	85,1	139	13640	76,6	50
STYLO PC 4P4 7030.120-6M		14000	102	137	16209	92,6	50
STYLO PC 4P4 7030.140-6M		16050	120	133	18723	109	50
STYLO PC 4P4 7030.160-6M		18020	138	130	21180	125	35
STYLO PC 4P4 7030.180-6M		19920	158	126	23582	142	35
STYLO PC 4P4 7030.080-7M		11250	79,7	141	12850	70,9	50
STYLO PC 4P4 7030.090-7M		12580	89,8	140	14390	80,1	50
STYLO PC 4P4 7030.100-7M		13890	100	138	15913	89,4	50
STYLO PC 4P4 7030.120-7M		16470	121	136	18911	108	50
STYLO PC 4P4 7030.140-7M		18950	142	133	21843	127	50
STYLO PC 4P4 7030.050-1M	STA STA1 STU-S	1030	8,3	124	1162	6,2	50
STYLO PC 4P4 7030.060-1M		1220	9,6	127	1389	7,5	50
STYLO PC 4P4 7030.070-1M		1420	11	129	1613	8,8	50
STYLO PC 4P4 7030.080-1M		1610	12,4	129	1836	10,1	50
STYLO PC 4P4 7030.090-1M		1810	13,8	131	2056	11,4	50
STYLO PC 4P4 7030.100-1M		2000	15,3	130	2273	12,8	50
STYLO PC 4P4 7030.120-1M		2390	18,4	129	2702	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7030.140-1M		2760	21,5	128	3120	18,1	50
STYLO PC 4P4 7030.160-1M		3120	24,7	126	3530	20,9	50
STYLO PC 4P4 7030.180-1M		3450	27,9	123	3930	23,6	50
STYLO PC 4P4 7030.200-1M		3750	31	120	4321	26,4	50
STYLO PC 4P4 7030.050-2M		2070	16	129	2324	12,5	50
STYLO PC 4P4 7030.060-2M		2450	18,7	131	2778	15	50
STYLO PC 4P4 7030.070-2M		2840	21,5	132	3227	17,6	50
STYLO PC 4P4 7030.080-2M		3230	24,3	132	3671	20,3	50
STYLO PC 4P4 7030.090-2M		3620	27,1	133	4111	22,9	50
STYLO PC 4P4 7030.100-2M		4000	30	133	4547	25,5	50
STYLO PC 4P4 7030.120-2M		4760	35,9	132	5403	30,9	50
STYLO PC 4P4 7030.140-2M		5500	41,9	131	6241	36,3	50
STYLO PC 4P4 7030.160-2M		6200	48	129	7060	41,8	50
STYLO PC 4P4 7030.180-2M		6850	54,2	126	7861	47,3	50
STYLO PC 4P4 7030.200-2M		7440	60,5	122	8643	52,9	50
STYLO PC 4P4 7030.050-3M		3100	23,3	133	3486	18,7	50
STYLO PC 4P4 7030.060-3M		3690	27,4	134	4166	22,6	50
STYLO PC 4P4 7030.070-3M		4270	31,5	135	4840	26,5	50
STYLO PC 4P4 7030.080-3M		4850	35,6	136	5507	30,4	50
STYLO PC 4P4 7030.090-3M		5430	39,8	136	6167	34,3	50
STYLO PC 4P4 7030.100-3M		6010	44	136	6820	38,3	50
STYLO PC 4P4 7030.120-3M		7130	52,6	135	8105	46,3	50
STYLO PC 4P4 7030.140-3M		8220	61,5	133	9361	54,4	50
STYLO PC 4P4 7030.160-3M		9250	70,7	130	10590	62,6	50
STYLO PC 4P4 7030.180-3M		10210	80,3	127	11791	70,9	50
STYLO PC 4P4 7030.200-3M		11100	90,4	122	12964	79,3	35
STYLO PC 4P4 7030.050-4M		4160	30	138	4648	24,9	50
STYLO PC 4P4 7030.060-4M		4960	35,3	140	5555	30,1	50
STYLO PC 4P4 7030.070-4M		5750	40,7	141	6454	35,3	50
STYLO PC 4P4 7030.080-4M		6510	46,3	140	7343	40,5	50
STYLO PC 4P4 7030.090-4M		7260	52	139	8223	45,8	50
STYLO PC 4P4 7030.100-4M		8000	57,8	138	9093	51,1	50
STYLO PC 4P4 7030.120-4M		9430	69,7	135	10806	61,7	50
STYLO PC 4P4 7030.140-4M		10810	81,8	132	12482	72,6	50
STYLO PC 4P4 7030.160-4M		12140	94	129	14120	83,5	50
STYLO PC 4P4 7030.180-4M		13440	106	126	15721	94,6	35
STYLO PC 4P4 7030.200-4M		14700	118	124	17285	106	35
STYLO PC 4P4 7030.080-5M		8140	57,2	142	9179	50,6	50
STYLO PC 4P4 7030.090-5M		9090	64,1	141	10278	57,2	50
STYLO PC 4P4 7030.100-5M		10020	71,1	140	11367	63,8	50
STYLO PC 4P4 7030.120-5M		11840	85,3	138	13508	77,2	50
STYLO PC 4P4 7030.140-5M		13590	100	135	15602	90,7	50
STYLO PC 4P4 7030.160-5M		15290	115	132	17650	104	35
STYLO PC 4P4 7030.180-5M		16930	131	129	19652	118	35
STYLO PC 4P4 7030.080-6M		9770	68,4	142	11014	60,8	50
STYLO PC 4P4 7030.090-6M		10900	76,7	142	12334	68,6	50
STYLO PC 4P4 7030.100-6M		12010	85,1	141	13640	76,6	50
STYLO PC 4P4 7030.120-6M		14170	102	138	16209	92,6	50
STYLO PC 4P4 7030.140-6M		16240	120	135	18723	109	50
STYLO PC 4P4 7030.160-6M		18240	138	132	21180	125	35
STYLO PC 4P4 7030.180-6M		20160	158	127	23582	142	35
STYLO PC 4P4 7030.080-7M		11390	79,7	142	12850	70,9	50
STYLO PC 4P4 7030.090-7M		12740	89,8	141	14390	80,1	50
STYLO PC 4P4 7030.100-7M		14070	100	140	15913	89,4	50
STYLO PC 4P4 7030.120-7M		16670	121	137	18911	108	50
STYLO PC 4P4 7030.140-7M		19190	142	135	21843	127	50
STYLO PC 4P4 7030.050-1M		1060	8,3	127	1162	6,2	50
STYLO PC 4P4 7030.060-1M		1260	9,6	131	1389	7,5	50
STYLO PC 4P4 7030.070-1M		1460	11	132	1613	8,8	50
STYLO PC 4P4 7030.080-1M		1660	12,4	133	1836	10,1	50
STYLO PC 4P4 7030.090-1M		1860	13,8	134	2056	11,4	50
STYLO PC 4P4 7030.100-1M		2060	15,3	134	2273	12,8	50
STYLO PC 4P4 7030.120-1M		2450	18,4	133	2702	15,4	50
STYLO PC 4P4 7030.140-1M		2830	21,5	131	3120	18,1	50
STYLO PC 4P4 7030.160-1M		3190	24,7	129	3530	20,9	50
STYLO PC 4P4 7030.180-1M		3530	27,9	126	3930	23,6	50
STYLO PC 4P4 7030.200-1M		3840	31	123	4321	26,4	50
STYLO PC 4P4 7030.050-2M		2120	16	132	2324	12,5	50
STYLO PC 4P4 7030.060-2M		2510	18,7	134	2778	15	50
STYLO PC 4P4 7030.070-2M		2910	21,5	135	3227	17,6	50
STYLO PC 4P4 7030.080-2M		3310	24,3	136	3671	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(3000K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(3000K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7030.090-2M		3700	27,1	136	4111	22,9	50
STYLO PC 4P4 7030.100-2M		4100	30	136	4547	25,5	50
STYLO PC 4P4 7030.120-2M		4880	35,9	135	5403	30,9	50
STYLO PC 4P4 7030.140-2M		5630	41,9	134	6241	36,3	50
STYLO PC 4P4 7030.160-2M		6350	48	132	7060	41,8	50
STYLO PC 4P4 7030.180-2M		7020	54,2	129	7861	47,3	50
STYLO PC 4P4 7030.200-2M		7620	60,5	125	8643	52,9	50
STYLO PC 4P4 7030.050-3M		3180	23,3	136	3486	18,7	50
STYLO PC 4P4 7030.060-3M		3790	27,4	138	4166	22,6	50
STYLO PC 4P4 7030.070-3M		4380	31,5	139	4840	26,5	50
STYLO PC 4P4 7030.080-3M		4980	35,6	139	5507	30,4	50
STYLO PC 4P4 7030.090-3M		5570	39,8	139	6167	34,3	50
STYLO PC 4P4 7030.100-3M		6160	44	140	6820	38,3	50
STYLO PC 4P4 7030.120-3M		7310	52,6	138	8105	46,3	50
STYLO PC 4P4 7030.140-3M		8410	61,5	136	9361	54,4	50
STYLO PC 4P4 7030.160-3M		9470	70,7	133	10590	62,6	50
STYLO PC 4P4 7030.180-3M		10460	80,3	130	11791	70,9	50
STYLO PC 4P4 7030.200-3M		11370	90,4	125	12964	79,3	35
STYLO PC 4P4 7030.050-4M		4270	30	142	4648	24,9	50
STYLO PC 4P4 7030.060-4M		5090	35,3	144	5555	30,1	50
STYLO PC 4P4 7030.070-4M		5890	40,7	144	6454	35,3	50
STYLO PC 4P4 7030.080-4M		6670	46,3	144	7343	40,5	50
STYLO PC 4P4 7030.090-4M		7440	52	143	8223	45,8	50
STYLO PC 4P4 7030.100-4M		8200	57,8	141	9093	51,1	50
STYLO PC 4P4 7030.120-4M		9660	69,7	138	10806	61,7	50
STYLO PC 4P4 7030.140-4M		11070	81,8	135	12482	72,6	50
STYLO PC 4P4 7030.160-4M		12440	94	132	14120	83,5	50
STYLO PC 4P4 7030.180-4M		13770	106	129	15721	94,6	35
STYLO PC 4P4 7030.200-4M		15070	118	127	17285	106	35
STYLO PC 4P4 7030.080-5M		8340	57,2	145	9179	50,6	50
STYLO PC 4P4 7030.090-5M		9310	64,1	145	10278	57,2	50
STYLO PC 4P4 7030.100-5M		10260	71,1	144	11367	63,8	50
STYLO PC 4P4 7030.120-5M		12120	85,3	142	13508	77,2	50
STYLO PC 4P4 7030.140-5M		13920	100	139	15602	90,7	50
STYLO PC 4P4 7030.160-5M		15660	115	136	17650	104	35
STYLO PC 4P4 7030.180-5M		17340	131	132	19652	118	35
STYLO PC 4P4 7030.080-6M		10000	68,4	146	11014	60,8	50
STYLO PC 4P4 7030.090-6M		11170	76,7	145	12334	68,6	50
STYLO PC 4P4 7030.100-6M		12300	85,1	144	13640	76,6	50
STYLO PC 4P4 7030.120-6M		14520	102	142	16209	92,6	50
STYLO PC 4P4 7030.140-6M		16650	120	138	18723	109	50
STYLO PC 4P4 7030.160-6M		18700	138	135	21180	125	35
STYLO PC 4P4 7030.180-6M		20670	158	130	23582	142	35
STYLO PC 4P4 7030.080-7M		11670	79,7	146	12850	70,9	50
STYLO PC 4P4 7030.090-7M		13060	89,8	145	14390	80,1	50
STYLO PC 4P4 7030.100-7M		14420	100	144	15913	89,4	50
STYLO PC 4P4 7030.120-7M		17090	121	141	18911	108	50
STYLO PC 4P4 7030.140-7M		19660	142	138	21843	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 4P4 2700K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7027.050-1M	STE-S	980	8,3	118	1112	6,2	50
STYLO PC 4P4 7027.060-1M		1160	9,6	120	1330	7,5	50
STYLO PC 4P4 7027.070-1M		1350	11	122	1545	8,8	50
STYLO PC 4P4 7027.080-1M		1530	12,4	123	1758	10,1	50
STYLO PC 4P4 7027.090-1M		1720	13,8	124	1968	11,4	50
STYLO PC 4P4 7027.100-1M		1900	15,3	124	2177	12,8	50
STYLO PC 4P4 7027.120-1M		2260	18,4	122	2587	15,4	50
STYLO PC 4P4 7027.140-1M		2610	21,5	121	2988	18,1	50
STYLO PC 4P4 7027.160-1M		2940	24,7	119	3380	20,9	50
STYLO PC 4P4 7027.180-1M		3260	27,9	116	3763	23,6	50
STYLO PC 4P4 7027.200-1M		3550	31	114	4137	26,4	50
STYLO PC 4P4 7027.050-2M		1950	16	121	2225	12,5	50
STYLO PC 4P4 7027.060-2M		2320	18,7	124	2659	15	50
STYLO PC 4P4 7027.070-2M		2680	21,5	124	3090	17,6	50
STYLO PC 4P4 7027.080-2M		3050	24,3	125	3515	20,3	50
STYLO PC 4P4 7027.090-2M		3420	27,1	126	3936	22,9	50
STYLO PC 4P4 7027.100-2M		3780	30	126	4353	25,5	50
STYLO PC 4P4 7027.120-2M		4500	35,9	125	5173	30,9	50
STYLO PC 4P4 7027.140-2M		5190	41,9	123	5975	36,3	50
STYLO PC 4P4 7027.160-2M		5850	48	121	6760	41,8	50
STYLO PC 4P4 7027.180-2M		6470	54,2	119	7526	47,3	50
STYLO PC 4P4 7027.200-2M		7040	60,5	116	8275	52,9	50
STYLO PC 4P4 7027.050-3M		2940	23,3	126	3337	18,7	50
STYLO PC 4P4 7027.060-3M		3490	27,4	127	3989	22,6	50
STYLO PC 4P4 7027.070-3M		4040	31,5	128	4634	26,5	50
STYLO PC 4P4 7027.080-3M		4590	35,6	128	5273	30,4	50
STYLO PC 4P4 7027.090-3M		5140	39,8	129	5905	34,3	50
STYLO PC 4P4 7027.100-3M		5680	44	129	6530	38,3	50
STYLO PC 4P4 7027.120-3M		6740	52,6	128	7760	46,3	50
STYLO PC 4P4 7027.140-3M		7770	61,5	126	8963	54,4	50
STYLO PC 4P4 7027.160-3M		8740	70,7	123	10140	62,6	50
STYLO PC 4P4 7027.180-3M		9660	80,3	120	11289	70,9	50
STYLO PC 4P4 7027.200-3M		10500	90,4	116	12412	79,3	35
STYLO PC 4P4 7027.050-4M		3940	30	131	4450	24,9	50
STYLO PC 4P4 7027.060-4M		4690	35,3	132	5319	30,1	50
STYLO PC 4P4 7027.070-4M		5430	40,7	133	6179	35,3	50
STYLO PC 4P4 7027.080-4M		6150	46,3	132	7030	40,5	50
STYLO PC 4P4 7027.090-4M		6860	52	131	7873	45,8	50
STYLO PC 4P4 7027.100-4M		7560	57,8	130	8706	51,1	50
STYLO PC 4P4 7027.120-4M		8920	69,7	127	10346	61,7	50
STYLO PC 4P4 7027.140-4M		10220	81,8	124	11951	72,6	50
STYLO PC 4P4 7027.160-4M		11490	94	122	13519	83,5	50
STYLO PC 4P4 7027.180-4M		12710	106	119	15052	94,6	35
STYLO PC 4P4 7027.200-4M		13910	118	117	16550	106	35
STYLO PC 4P4 7027.080-5M		7700	57,2	134	8788	50,6	50
STYLO PC 4P4 7027.090-5M		8600	64,1	134	9841	57,2	50
STYLO PC 4P4 7027.100-5M		9480	71,1	133	10883	63,8	50
STYLO PC 4P4 7027.120-5M		11190	85,3	131	12933	77,2	50
STYLO PC 4P4 7027.140-5M		12850	100	128	14938	90,7	50
STYLO PC 4P4 7027.160-5M		14450	115	125	16899	104	35
STYLO PC 4P4 7027.180-5M		16000	131	122	18816	118	35
STYLO PC 4P4 7027.080-6M		9240	68,4	135	10546	60,8	50
STYLO PC 4P4 7027.090-6M		10310	76,7	134	11809	68,6	50
STYLO PC 4P4 7027.100-6M		11360	85,1	133	13059	76,6	50
STYLO PC 4P4 7027.120-6M		13400	102	131	15520	92,6	50
STYLO PC 4P4 7027.140-6M		15360	120	128	17926	109	50
STYLO PC 4P4 7027.160-6M		17250	138	125	20279	125	35
STYLO PC 4P4 7027.180-6M		19070	158	120	22579	142	35
STYLO PC 4P4 7027.080-7M		10770	79,7	135	12303	70,9	50
STYLO PC 4P4 7027.090-7M		12040	89,8	134	13777	80,1	50
STYLO PC 4P4 7027.100-7M		13300	100	133	15236	89,4	50
STYLO PC 4P4 7027.120-7M		15770	121	130	18106	108	50
STYLO PC 4P4 7027.140-7M		18140	142	127	20914	127	50
STYLO PC 4P4 7027.050-1M	STA STA1 STU-S	990	8,3	119	1112	6,2	50
STYLO PC 4P4 7027.060-1M		1170	9,6	121	1330	7,5	50
STYLO PC 4P4 7027.070-1M		1360	11	123	1545	8,8	50
STYLO PC 4P4 7027.080-1M		1540	12,4	124	1758	10,1	50
STYLO PC 4P4 7027.090-1M		1730	13,8	125	1968	11,4	50
STYLO PC 4P4 7027.100-1M		1920	15,3	125	2177	12,8	50
STYLO PC 4P4 7027.120-1M		2290	18,4	124	2587	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7027.140-1M		2650	21,5	123	2988	18,1	50
STYLO PC 4P4 7027.160-1M		2990	24,7	121	3380	20,9	50
STYLO PC 4P4 7027.180-1M		3300	27,9	118	3763	23,6	50
STYLO PC 4P4 7027.200-1M		3590	31	115	4137	26,4	50
STYLO PC 4P4 7027.050-2M		1980	16	123	2225	12,5	50
STYLO PC 4P4 7027.060-2M		2350	18,7	125	2659	15	50
STYLO PC 4P4 7027.070-2M		2720	21,5	126	3090	17,6	50
STYLO PC 4P4 7027.080-2M		3090	24,3	127	3515	20,3	50
STYLO PC 4P4 7027.090-2M		3460	27,1	127	3936	22,9	50
STYLO PC 4P4 7027.100-2M		3830	30	127	4353	25,5	50
STYLO PC 4P4 7027.120-2M		4560	35,9	127	5173	30,9	50
STYLO PC 4P4 7027.140-2M		5270	41,9	125	5975	36,3	50
STYLO PC 4P4 7027.160-2M		5930	48	123	6760	41,8	50
STYLO PC 4P4 7027.180-2M		6560	54,2	121	7526	47,3	50
STYLO PC 4P4 7027.200-2M		7130	60,5	117	8275	52,9	50
STYLO PC 4P4 7027.050-3M		2970	23,3	127	3337	18,7	50
STYLO PC 4P4 7027.060-3M		3530	27,4	128	3989	22,6	50
STYLO PC 4P4 7027.070-3M		4090	31,5	129	4634	26,5	50
STYLO PC 4P4 7027.080-3M		4650	35,6	130	5273	30,4	50
STYLO PC 4P4 7027.090-3M		5200	39,8	130	5905	34,3	50
STYLO PC 4P4 7027.100-3M		5750	44	130	6530	38,3	50
STYLO PC 4P4 7027.120-3M		6830	52,6	129	7760	46,3	50
STYLO PC 4P4 7027.140-3M		7870	61,5	127	8963	54,4	50
STYLO PC 4P4 7027.160-3M		8850	70,7	125	10140	62,6	50
STYLO PC 4P4 7027.180-3M		9780	80,3	121	11289	70,9	50
STYLO PC 4P4 7027.200-3M		10630	90,4	117	12412	79,3	35
STYLO PC 4P4 7027.050-4M		3990	30	133	4450	24,9	50
STYLO PC 4P4 7027.060-4M		4750	35,3	134	5319	30,1	50
STYLO PC 4P4 7027.070-4M		5500	40,7	135	6179	35,3	50
STYLO PC 4P4 7027.080-4M		6240	46,3	134	7030	40,5	50
STYLO PC 4P4 7027.090-4M		6950	52	133	7873	45,8	50
STYLO PC 4P4 7027.100-4M		7660	57,8	132	8706	51,1	50
STYLO PC 4P4 7027.120-4M		9030	69,7	129	10346	61,7	50
STYLO PC 4P4 7027.140-4M		10350	81,8	126	11951	72,6	50
STYLO PC 4P4 7027.160-4M		11630	94	123	13519	83,5	50
STYLO PC 4P4 7027.180-4M		12870	106	121	15052	94,6	35
STYLO PC 4P4 7027.200-4M		14080	118	119	16550	106	35
STYLO PC 4P4 7027.080-5M		7790	57,2	136	8788	50,6	50
STYLO PC 4P4 7027.090-5M		8700	64,1	135	9841	57,2	50
STYLO PC 4P4 7027.100-5M		9590	71,1	134	10883	63,8	50
STYLO PC 4P4 7027.120-5M		11330	85,3	132	12933	77,2	50
STYLO PC 4P4 7027.140-5M		13010	100	130	14938	90,7	50
STYLO PC 4P4 7027.160-5M		14640	115	127	16899	104	35
STYLO PC 4P4 7027.180-5M		16210	131	123	18816	118	35
STYLO PC 4P4 7027.080-6M		9360	68,4	136	10546	60,8	50
STYLO PC 4P4 7027.090-6M		10440	76,7	136	11809	68,6	50
STYLO PC 4P4 7027.100-6M		11500	85,1	135	13059	76,6	50
STYLO PC 4P4 7027.120-6M		13570	102	133	15520	92,6	50
STYLO PC 4P4 7027.140-6M		15550	120	129	17926	109	50
STYLO PC 4P4 7027.160-6M		17460	138	126	20279	125	35
STYLO PC 4P4 7027.180-6M		19300	158	122	22579	142	35
STYLO PC 4P4 7027.080-7M		10910	79,7	136	12303	70,9	50
STYLO PC 4P4 7027.090-7M		12200	89,8	135	13777	80,1	50
STYLO PC 4P4 7027.100-7M		13470	100	134	15236	89,4	50
STYLO PC 4P4 7027.120-7M		15960	121	131	18106	108	50
STYLO PC 4P4 7027.140-7M		18370	142	129	20914	127	50
STYLO PC 4P4 7027.050-1M		1020	8,3	122	1112	6,2	50
STYLO PC 4P4 7027.060-1M		1210	9,6	126	1330	7,5	50
STYLO PC 4P4 7027.070-1M		1400	11	127	1545	8,8	50
STYLO PC 4P4 7027.080-1M		1590	12,4	128	1758	10,1	50
STYLO PC 4P4 7027.090-1M		1780	13,8	128	1968	11,4	50
STYLO PC 4P4 7027.100-1M		1970	15,3	128	2177	12,8	50
STYLO PC 4P4 7027.120-1M		2350	18,4	127	2587	15,4	50
STYLO PC 4P4 7027.140-1M		2710	21,5	126	2988	18,1	50
STYLO PC 4P4 7027.160-1M		3050	24,7	123	3380	20,9	50
STYLO PC 4P4 7027.180-1M		3380	27,9	121	3763	23,6	50
STYLO PC 4P4 7027.200-1M		3670	31	118	4137	26,4	50
STYLO PC 4P4 7027.050-2M		2030	16	126	2225	12,5	50
STYLO PC 4P4 7027.060-2M		2410	18,7	128	2659	15	50
STYLO PC 4P4 7027.070-2M		2790	21,5	129	3090	17,6	50
STYLO PC 4P4 7027.080-2M		3170	24,3	130	3515	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2700K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2700K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7027.090-2M		3550	27,1	130	3936	22,9	50
STYLO PC 4P4 7027.100-2M		3920	30	130	4353	25,5	50
STYLO PC 4P4 7027.120-2M		4670	35,9	130	5173	30,9	50
STYLO PC 4P4 7027.140-2M		5390	41,9	128	5975	36,3	50
STYLO PC 4P4 7027.160-2M		6080	48	126	6760	41,8	50
STYLO PC 4P4 7027.180-2M		6720	54,2	123	7526	47,3	50
STYLO PC 4P4 7027.200-2M		7300	60,5	120	8275	52,9	50
STYLO PC 4P4 7027.050-3M		3050	23,3	130	3337	18,7	50
STYLO PC 4P4 7027.060-3M		3620	27,4	132	3989	22,6	50
STYLO PC 4P4 7027.070-3M		4200	31,5	133	4634	26,5	50
STYLO PC 4P4 7027.080-3M		4770	35,6	133	5273	30,4	50
STYLO PC 4P4 7027.090-3M		5330	39,8	133	5905	34,3	50
STYLO PC 4P4 7027.100-3M		5900	44	134	6530	38,3	50
STYLO PC 4P4 7027.120-3M		6990	52,6	132	7760	46,3	50
STYLO PC 4P4 7027.140-3M		8060	61,5	131	8963	54,4	50
STYLO PC 4P4 7027.160-3M		9070	70,7	128	10140	62,6	50
STYLO PC 4P4 7027.180-3M		10010	80,3	124	11289	70,9	50
STYLO PC 4P4 7027.200-3M		10890	90,4	120	12412	79,3	35
STYLO PC 4P4 7027.050-4M		4090	30	136	4450	24,9	50
STYLO PC 4P4 7027.060-4M		4870	35,3	137	5319	30,1	50
STYLO PC 4P4 7027.070-4M		5640	40,7	138	6179	35,3	50
STYLO PC 4P4 7027.080-4M		6390	46,3	138	7030	40,5	50
STYLO PC 4P4 7027.090-4M		7130	52	137	7873	45,8	50
STYLO PC 4P4 7027.100-4M		7850	57,8	135	8706	51,1	50
STYLO PC 4P4 7027.120-4M		9250	69,7	132	10346	61,7	50
STYLO PC 4P4 7027.140-4M		10600	81,8	129	11951	72,6	50
STYLO PC 4P4 7027.160-4M		11910	94	126	13519	83,5	50
STYLO PC 4P4 7027.180-4M		13180	106	124	15052	94,6	35
STYLO PC 4P4 7027.200-4M		14430	118	122	16550	106	35
STYLO PC 4P4 7027.080-5M		7990	57,2	139	8788	50,6	50
STYLO PC 4P4 7027.090-5M		8910	64,1	139	9841	57,2	50
STYLO PC 4P4 7027.100-5M		9830	71,1	138	10883	63,8	50
STYLO PC 4P4 7027.120-5M		11610	85,3	136	12933	77,2	50
STYLO PC 4P4 7027.140-5M		13330	100	133	14938	90,7	50
STYLO PC 4P4 7027.160-5M		14990	115	130	16899	104	35
STYLO PC 4P4 7027.180-5M		16600	131	126	18816	118	35
STYLO PC 4P4 7027.080-6M		9580	68,4	140	10546	60,8	50
STYLO PC 4P4 7027.090-6M		10690	76,7	139	11809	68,6	50
STYLO PC 4P4 7027.100-6M		11780	85,1	138	13059	76,6	50
STYLO PC 4P4 7027.120-6M		13900	102	136	15520	92,6	50
STYLO PC 4P4 7027.140-6M		15940	120	132	17926	109	50
STYLO PC 4P4 7027.160-6M		17900	138	129	20279	125	35
STYLO PC 4P4 7027.180-6M		19790	158	125	22579	142	35
STYLO PC 4P4 7027.080-7M		11180	79,7	140	12303	70,9	50
STYLO PC 4P4 7027.090-7M		12500	89,8	139	13777	80,1	50
STYLO PC 4P4 7027.100-7M		13810	100	138	15236	89,4	50
STYLO PC 4P4 7027.120-7M		16360	121	135	18106	108	50
STYLO PC 4P4 7027.140-7M		18830	142	132	20914	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.

STYLO PC 4P4 2200K

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7022.050-1M	S05 S07 STE-S	880	8,3	106	1001	6,2	50
STYLO PC 4P4 7022.060-1M		1040	9,6	108	1197	7,5	50
STYLO PC 4P4 7022.070-1M		1210	11	110	1390	8,8	50
STYLO PC 4P4 7022.080-1M		1380	12,4	111	1582	10,1	50
STYLO PC 4P4 7022.090-1M		1540	13,8	111	1771	11,4	50
STYLO PC 4P4 7022.100-1M		1710	15,3	111	1959	12,8	50
STYLO PC 4P4 7022.120-1M		2030	18,4	110	2328	15,4	50
STYLO PC 4P4 7022.140-1M		2350	21,5	109	2689	18,1	50
STYLO PC 4P4 7022.160-1M		2650	24,7	107	3042	20,9	50
STYLO PC 4P4 7022.180-1M		2930	27,9	105	3387	23,6	50
STYLO PC 4P4 7022.200-1M		3190	31	102	3724	26,4	50
STYLO PC 4P4 7022.050-2M		1760	16	110	2002	12,5	50
STYLO PC 4P4 7022.060-2M		2090	18,7	111	2394	15	50
STYLO PC 4P4 7022.070-2M		2410	21,5	112	2781	17,6	50
STYLO PC 4P4 7022.080-2M		2740	24,3	112	3164	20,3	50
STYLO PC 4P4 7022.090-2M		3070	27,1	113	3543	22,9	50
STYLO PC 4P4 7022.100-2M		3400	30	113	3918	25,5	50
STYLO PC 4P4 7022.120-2M		4050	35,9	112	4656	30,9	50
STYLO PC 4P4 7022.140-2M		4670	41,9	111	5378	36,3	50
STYLO PC 4P4 7022.160-2M		5270	48	109	6084	41,8	50
STYLO PC 4P4 7022.180-2M		5830	54,2	107	6774	47,3	50
STYLO PC 4P4 7022.200-2M		6330	60,5	104	7447	52,9	50
STYLO PC 4P4 7022.050-3M		2640	23,3	113	3004	18,7	50
STYLO PC 4P4 7022.060-3M		3140	27,4	114	3590	22,6	50
STYLO PC 4P4 7022.070-3M		3640	31,5	115	4171	26,5	50
STYLO PC 4P4 7022.080-3M		4130	35,6	116	4746	30,4	50
STYLO PC 4P4 7022.090-3M		4620	39,8	116	5314	34,3	50
STYLO PC 4P4 7022.100-3M		5110	44	116	5877	38,3	50
STYLO PC 4P4 7022.120-3M		6070	52,6	115	6984	46,3	50
STYLO PC 4P4 7022.140-3M		6990	61,5	113	8067	54,4	50
STYLO PC 4P4 7022.160-3M		7870	70,7	111	9126	62,6	50
STYLO PC 4P4 7022.180-3M		8690	80,3	108	10160	70,9	50
STYLO PC 4P4 7022.200-3M		9450	90,4	104	11171	79,3	35
STYLO PC 4P4 7022.050-4M		3540	30	118	4005	24,9	50
STYLO PC 4P4 7022.060-4M		4220	35,3	119	4787	30,1	50
STYLO PC 4P4 7022.070-4M		4890	40,7	120	5561	35,3	50
STYLO PC 4P4 7022.080-4M		5540	46,3	119	6327	40,5	50
STYLO PC 4P4 7022.090-4M		6180	52	118	7086	45,8	50
STYLO PC 4P4 7022.100-4M		6800	57,8	117	7836	51,1	50
STYLO PC 4P4 7022.120-4M		8020	69,7	115	9312	61,7	50
STYLO PC 4P4 7022.140-4M		9200	81,8	112	10756	72,6	50
STYLO PC 4P4 7022.160-4M		10340	94	110	12167	83,5	50
STYLO PC 4P4 7022.180-4M		11440	106	107	13547	94,6	35
STYLO PC 4P4 7022.200-4M		12510	118	106	14895	106	35
STYLO PC 4P4 7022.080-5M		6930	57,2	121	7909	50,6	50
STYLO PC 4P4 7022.090-5M		7740	64,1	120	8857	57,2	50
STYLO PC 4P4 7022.100-5M		8530	71,1	119	9795	63,8	50
STYLO PC 4P4 7022.120-5M		10070	85,3	118	11640	77,2	50
STYLO PC 4P4 7022.140-5M		11570	100	115	13445	90,7	50
STYLO PC 4P4 7022.160-5M		13010	115	113	15209	104	35
STYLO PC 4P4 7022.180-5M		14400	131	109	16934	118	35
STYLO PC 4P4 7022.080-6M		8310	68,4	121	9491	60,8	50
STYLO PC 4P4 7022.090-6M		9280	76,7	120	10628	68,6	50
STYLO PC 4P4 7022.100-6M		10220	85,1	120	11753	76,6	50
STYLO PC 4P4 7022.120-6M		12060	102	118	13968	92,6	50
STYLO PC 4P4 7022.140-6M		13830	120	115	16134	109	50
STYLO PC 4P4 7022.160-6M		15530	138	112	18251	125	35
STYLO PC 4P4 7022.180-6M		17160	158	108	20321	142	35
STYLO PC 4P4 7022.080-7M		9690	79,7	121	11073	70,9	50
STYLO PC 4P4 7022.090-7M		10840	89,8	120	12400	80,1	50
STYLO PC 4P4 7022.100-7M		11970	100	119	13712	89,4	50
STYLO PC 4P4 7022.120-7M		14190	121	117	16296	108	50
STYLO PC 4P4 7022.140-7M		16330	142	115	18822	127	50
STYLO PC 4P4 7022.050-1M	STA STA1 STU-S	890	8,3	107	1001	6,2	50
STYLO PC 4P4 7022.060-1M		1050	9,6	109	1197	7,5	50
STYLO PC 4P4 7022.070-1M		1220	11	110	1390	8,8	50
STYLO PC 4P4 7022.080-1M		1390	12,4	112	1582	10,1	50
STYLO PC 4P4 7022.090-1M		1560	13,8	113	1771	11,4	50
STYLO PC 4P4 7022.100-1M		1730	15,3	113	1959	12,8	50
STYLO PC 4P4 7022.120-1M		2060	18,4	111	2328	15,4	50

AEC Illuminazione

www.aecilluminazione.it - www.aecilluminazione.com

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7022.140-1M		2380	21,5	110	2689	18,1	50
STYLO PC 4P4 7022.160-1M		2690	24,7	108	3042	20,9	50
STYLO PC 4P4 7022.180-1M		2970	27,9	106	3387	23,6	50
STYLO PC 4P4 7022.200-1M		3230	31	104	3724	26,4	50
STYLO PC 4P4 7022.050-2M		1780	16	111	2002	12,5	50
STYLO PC 4P4 7022.060-2M		2110	18,7	112	2394	15	50
STYLO PC 4P4 7022.070-2M		2450	21,5	113	2781	17,6	50
STYLO PC 4P4 7022.080-2M		2780	24,3	114	3164	20,3	50
STYLO PC 4P4 7022.090-2M		3120	27,1	115	3543	22,9	50
STYLO PC 4P4 7022.100-2M		3450	30	115	3918	25,5	50
STYLO PC 4P4 7022.120-2M		4110	35,9	114	4656	30,9	50
STYLO PC 4P4 7022.140-2M		4740	41,9	113	5378	36,3	50
STYLO PC 4P4 7022.160-2M		5340	48	111	6084	41,8	50
STYLO PC 4P4 7022.180-2M		5900	54,2	108	6774	47,3	50
STYLO PC 4P4 7022.200-2M		6420	60,5	106	7447	52,9	50
STYLO PC 4P4 7022.050-3M		2670	23,3	114	3004	18,7	50
STYLO PC 4P4 7022.060-3M		3180	27,4	116	3590	22,6	50
STYLO PC 4P4 7022.070-3M		3680	31,5	116	4171	26,5	50
STYLO PC 4P4 7022.080-3M		4180	35,6	117	4746	30,4	50
STYLO PC 4P4 7022.090-3M		4680	39,8	117	5314	34,3	50
STYLO PC 4P4 7022.100-3M		5180	44	117	5877	38,3	50
STYLO PC 4P4 7022.120-3M		6140	52,6	116	6984	46,3	50
STYLO PC 4P4 7022.140-3M		7080	61,5	115	8067	54,4	50
STYLO PC 4P4 7022.160-3M		7970	70,7	112	9126	62,6	50
STYLO PC 4P4 7022.180-3M		8800	80,3	109	10160	70,9	50
STYLO PC 4P4 7022.200-3M		9570	90,4	105	11171	79,3	35
STYLO PC 4P4 7022.050-4M		3590	30	119	4005	24,9	50
STYLO PC 4P4 7022.060-4M		4280	35,3	121	4787	30,1	50
STYLO PC 4P4 7022.070-4M		4950	40,7	121	5561	35,3	50
STYLO PC 4P4 7022.080-4M		5610	46,3	121	6327	40,5	50
STYLO PC 4P4 7022.090-4M		6260	52	120	7086	45,8	50
STYLO PC 4P4 7022.100-4M		6890	57,8	119	7836	51,1	50
STYLO PC 4P4 7022.120-4M		8130	69,7	116	9312	61,7	50
STYLO PC 4P4 7022.140-4M		9320	81,8	113	10756	72,6	50
STYLO PC 4P4 7022.160-4M		10470	94	111	12167	83,5	50
STYLO PC 4P4 7022.180-4M		11580	106	109	13547	94,6	35
STYLO PC 4P4 7022.200-4M		12670	118	107	14895	106	35
STYLO PC 4P4 7022.080-5M		7010	57,2	122	7909	50,6	50
STYLO PC 4P4 7022.090-5M		7830	64,1	122	8857	57,2	50
STYLO PC 4P4 7022.100-5M		8630	71,1	121	9795	63,8	50
STYLO PC 4P4 7022.120-5M		10200	85,3	119	11640	77,2	50
STYLO PC 4P4 7022.140-5M		11710	100	117	13445	90,7	50
STYLO PC 4P4 7022.160-5M		13170	115	114	15209	104	35
STYLO PC 4P4 7022.180-5M		14590	131	111	16934	118	35
STYLO PC 4P4 7022.080-6M		8420	68,4	123	9491	60,8	50
STYLO PC 4P4 7022.090-6M		9400	76,7	122	10628	68,6	50
STYLO PC 4P4 7022.100-6M		10350	85,1	121	11753	76,6	50
STYLO PC 4P4 7022.120-6M		12210	102	119	13968	92,6	50
STYLO PC 4P4 7022.140-6M		14000	120	116	16134	109	50
STYLO PC 4P4 7022.160-6M		15720	138	113	18251	125	35
STYLO PC 4P4 7022.180-6M		17370	158	109	20321	142	35
STYLO PC 4P4 7022.080-7M		9820	79,7	123	11073	70,9	50
STYLO PC 4P4 7022.090-7M		10980	89,8	122	12400	80,1	50
STYLO PC 4P4 7022.100-7M		12130	100	121	13712	89,4	50
STYLO PC 4P4 7022.120-7M		14370	121	118	16296	108	50
STYLO PC 4P4 7022.140-7M		16530	142	116	18822	127	50
STYLO PC 4P4 7022.050-1M		910	8,3	109	1001	6,2	50
STYLO PC 4P4 7022.060-1M		1090	9,6	113	1197	7,5	50
STYLO PC 4P4 7022.070-1M		1260	11	114	1390	8,8	50
STYLO PC 4P4 7022.080-1M		1430	12,4	115	1582	10,1	50
STYLO PC 4P4 7022.090-1M		1600	13,8	115	1771	11,4	50
STYLO PC 4P4 7022.100-1M		1770	15,3	115	1959	12,8	50
STYLO PC 4P4 7022.120-1M		2110	18,4	114	2328	15,4	50
STYLO PC 4P4 7022.140-1M		2440	21,5	113	2689	18,1	50
STYLO PC 4P4 7022.160-1M		2750	24,7	111	3042	20,9	50
STYLO PC 4P4 7022.180-1M		3040	27,9	108	3387	23,6	50
STYLO PC 4P4 7022.200-1M		3300	31	106	3724	26,4	50
STYLO PC 4P4 7022.050-2M		1830	16	114	2002	12,5	50
STYLO PC 4P4 7022.060-2M		2170	18,7	116	2394	15	50
STYLO PC 4P4 7022.070-2M		2510	21,5	116	2781	17,6	50
STYLO PC 4P4 7022.080-2M		2850	24,3	117	3164	20,3	50

LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX*(2200K, lm)	RATED LUMINAIRE POWER*(W)	LUMINAIRE EFFICACY (lm/W)	RATED LED FLUX*(2200K, lm)	RATED LED POWER*(W)	Ta MAX (°C)
STYLO PC 4P4 7022.090-2M		3190	27,1	117	3543	22,9	50
STYLO PC 4P4 7022.100-2M		3530	30	117	3918	25,5	50
STYLO PC 4P4 7022.120-2M		4200	35,9	116	4656	30,9	50
STYLO PC 4P4 7022.140-2M		4850	41,9	115	5378	36,3	50
STYLO PC 4P4 7022.160-2M		5470	48	113	6084	41,8	50
STYLO PC 4P4 7022.180-2M		6050	54,2	111	6774	47,3	50
STYLO PC 4P4 7022.200-2M		6570	60,5	108	7447	52,9	50
STYLO PC 4P4 7022.050-3M		2740	23,3	117	3004	18,7	50
STYLO PC 4P4 7022.060-3M		3260	27,4	118	3590	22,6	50
STYLO PC 4P4 7022.070-3M		3780	31,5	120	4171	26,5	50
STYLO PC 4P4 7022.080-3M		4290	35,6	120	4746	30,4	50
STYLO PC 4P4 7022.090-3M		4800	39,8	120	5314	34,3	50
STYLO PC 4P4 7022.100-3M		5310	44	120	5877	38,3	50
STYLO PC 4P4 7022.120-3M		6300	52,6	119	6984	46,3	50
STYLO PC 4P4 7022.140-3M		7250	61,5	117	8067	54,4	50
STYLO PC 4P4 7022.160-3M		8160	70,7	115	9126	62,6	50
STYLO PC 4P4 7022.180-3M		9010	80,3	112	10160	70,9	50
STYLO PC 4P4 7022.200-3M		9800	90,4	108	11171	79,3	35
STYLO PC 4P4 7022.050-4M		3680	30	122	4005	24,9	50
STYLO PC 4P4 7022.060-4M		4380	35,3	124	4787	30,1	50
STYLO PC 4P4 7022.070-4M		5080	40,7	124	5561	35,3	50
STYLO PC 4P4 7022.080-4M		5750	46,3	124	6327	40,5	50
STYLO PC 4P4 7022.090-4M		6410	52	123	7086	45,8	50
STYLO PC 4P4 7022.100-4M		7060	57,8	122	7836	51,1	50
STYLO PC 4P4 7022.120-4M		8320	69,7	119	9312	61,7	50
STYLO PC 4P4 7022.140-4M		9540	81,8	116	10756	72,6	50
STYLO PC 4P4 7022.160-4M		10720	94	114	12167	83,5	50
STYLO PC 4P4 7022.180-4M		11870	106	111	13547	94,6	35
STYLO PC 4P4 7022.200-4M		12980	118	110	14895	106	35
STYLO PC 4P4 7022.080-5M		7190	57,2	125	7909	50,6	50
STYLO PC 4P4 7022.090-5M		8020	64,1	125	8857	57,2	50
STYLO PC 4P4 7022.100-5M		8850	71,1	124	9795	63,8	50
STYLO PC 4P4 7022.120-5M		10450	85,3	122	11640	77,2	50
STYLO PC 4P4 7022.140-5M		12000	100	120	13445	90,7	50
STYLO PC 4P4 7022.160-5M		13490	115	117	15209	104	35
STYLO PC 4P4 7022.180-5M		14940	131	114	16934	118	35
STYLO PC 4P4 7022.080-6M		8620	68,4	126	9491	60,8	50
STYLO PC 4P4 7022.090-6M		9620	76,7	125	10628	68,6	50
STYLO PC 4P4 7022.100-6M		10600	85,1	124	11753	76,6	50
STYLO PC 4P4 7022.120-6M		12510	102	122	13968	92,6	50
STYLO PC 4P4 7022.140-6M		14350	120	119	16134	109	50
STYLO PC 4P4 7022.160-6M		16110	138	116	18251	125	35
STYLO PC 4P4 7022.180-6M		17810	158	112	20321	142	35
STYLO PC 4P4 7022.080-7M		10060	79,7	126	11073	70,9	50
STYLO PC 4P4 7022.090-7M		11250	89,8	125	12400	80,1	50
STYLO PC 4P4 7022.100-7M		12430	100	124	13712	89,4	50
STYLO PC 4P4 7022.120-7M		14720	121	121	16296	108	50
STYLO PC 4P4 7022.140-7M		16950	142	119	18822	127	50

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory. Tq=25°C, Vin=230Vac, F/DA/DAC.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet. Tj=85°C.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±7%.

Power tolerance with ZHAGA version or power supply D4i/SR: ±10%.

The characteristics of the product listed above are subjected to change without notice.